

CAF Validation Test Suite

Validation Results

HPCTools Group

University of Houston,
Texas, 77004

This report provides a list of features within the Fortran-2008 specification, that the test-codes target. It also provides the validation results of some of the CAF compilers, namely OpenUH (v3.0.x), Cray, Intel (v13.1) and G95 (v0.93)(Sec 2).

1 Testing the CAF features within Fortran2008 specification

1.1 Categories of the Test-codes

This section outlines the different categories of tests within the suite that can be used to evaluate a CAF compiler implementation. The primary goal is to determine the extent to which it supports the coarray-features of the Fortran 2008 standard in accordance with ISO/IEC 1539-1:2010 (E)[1].

There are three main categories of tests in the test suite. Each category is located in a different subdirectory within \$SUITE_ROOT, and all the tests within the same category can be executed using the makefile.

Feature Tests These tests can be found under:

\$SUITE_ROOT/feature_tests. The tests under this category verify the support and correctness of the implementations of the basic constructs/semantics of CAF. The tests concentrate on the verification of the correctness of contiguous and strided remote read/write operations, the coarray syntax, the use of strided co-subscript notation, coarrays of different data types and image-query intrinsics.

Cross Checked Feature Tests These tests can be found under:

\$SUITE_ROOT/crosscheck_feature_tests. All tests in this category verify CAF constructs that aid in maintaining consistency and synchronization among images. The tests intentionally compute intensive loops and forced CPU - idling (using calls to the sleep() intrinsic) for simulating delays in progress of certain images. This enforces an increase in the likelihood of inconsistent states (and races) in case of incorrect implementations of the constructs being tested.

Due to the nondeterministic nature of unsynchronized images, configuration parameters(as defined under \$SUITE_ROOT/config/CONFIG*) can be modified to determine the number of times the experiment passes a cross-check test.

This test-category uses *cross-check*-tests to verify whether the test stands the cross test every time or not. Such *cross-check*- tests include the exact same code like the original version but with certain statements deleted/replaced to identify the change in behavior of the tests.

Note on code design: Most of the time, the modifications to the original code are in the form of the absence of the CAF statements which are being tested in that test case. In order to reduce redundant code, we chose to include the *cross*-test version and the original version all in one file, using conditional `#ifdef`'s and macros (e.g. `CROSS_`).

Detecting/Reporting of errors

- Every test includes a module called 'crosstest'.
- The module 'crosstest' (defined in file `testmofule.f90`) includes the declaration of an integer scalar coarray called 'cross_err' which is modified by image with rank 1 on detecting an error. It also contains two subroutines - `calc_ori` and `calc`. The former returns the test result when the specific construct is being tested. The latter is called by the cross-test version and returns the number of times the cross verification passed out of total trials.

Status Tests These tests can be found under:

`$$SUITE_ROOT/status_tests`. These test the correctness of the implementation of specifiers used for handling normal and error termination. These tests include testing the support of statevariables that flag the execution state of other images. Here's an excerpt describing the 2 states of image execution-termination [from Page 23, sec. 13 of "ISO/IEC JTC1/SC22/WG5 N1824 "2]]:

" ... It seems natural to allow all images to continue executing until they have all executed a stop or end program statement, provided none of them encounters an error condition that may be expected to terminate its execution. This is called normal termination. On the other hand, if such an error condition occurs on one image, the computation is flawed and it is desirable to stop the other images as soon as is practicable. This is called error termination.

Normal termination occurs in three steps: initiation, synchronization, and completion. An image initiates normal termination if it executes a stop or end program statement. All images synchronize execution at the second step so that no image starts the completion step until all images have finished the initiation step. The synchronization step allows its data to remain accessible to the other images until they all reach the synchronization step. Normal termination may also be initiated during execution of a procedure defined by a C companion processor[a.k.a. C compiler]

An image initiates error termination if it executes a statement that would cause the termination of a single-image program but is not a stop or end program statement. This causes all other images that have not already initiated error termination to initiate error termination. Within the performance limits of the processor's ability to send signals to other images, this propagation of error termination should be immediate. The exact details are intentionally left processor dependent.... "

Specific Tests If the user wants to evaluate a CAF implementation in terms of the support to specific types of tests, the names of the tests can be specified in the file "*test_file*" in the directory `$$SUITE_ROOT/few_tests`.

1.2 List of Test-codes

The tests are listed in Tables 1,2, and 3. The test-files are named using the following convention:

“<construction_type>.<section_number>.f90”, where,

- *construction_type* is the semantic-target of the test.
- *section_number* is the section number in the standard to which the check belongs. This allows or a quick look-up of the exact point to which a correct CAF implementation must adhere to.

Table 1. Feature Test files in the UH - CAF Validation Tests suite

File	Description
character_test.f90	CHARACTER coarrays
coarray_2.4.7.6.f90	similar translation of co-subscripts and subscripts
coarray_4.8.R468.f90	reference of coarray without [] implies local object
coarray_5.3.6.1.f90	attribute CODIMENSION + remote accesses at single integer/real boundary
dummyargs_12.3.2.2c.f90	explicit shape, assumed size, assumed shape, allocatable dummy args
intrin_13.7.126.f90	NUM_IMAGES() returns the number of images launched
intrin_13.7.165.f90	THIS_IMAGE(), THIS_IMAGE(coarray), THIS_IMAGE(coarray, dim)
intrin_13.7.172.f90	LCOBOUND(coarray) and LCOBOUND(coarray,dim)
intrin_13.7.79.f90	IMAGE_INDEX(coarray, subs)
intrin_13.7.91.f90	UCOBOUND(COARRAY[, DIM, KIND])
intrin_6.7.3.2.11.f90	ALLOCATE and DEALLOCATE act as barriers
item_4.8.a.f90	Subobjects of a coarray is also a coarray
pointer_4.5.4.6b.f90	association of pointer components of coarrays with local objects
intrin_8.5.7d.f90	STOP and LOCK construct with STAT=STAT_LOCKED specifier
intrin_8.5.7e.f90	STOP and LOCK construct with STAT=STAT_LOCKED_OTHER_IMAGE specifier
intrin_8.5.7f.f90	STOP and LOCK construct with STAT=STAT_UNLOCKED specifier
derived_4.5.4.f90	(non-)coarray COMPONENTS of (non-)coarray derived types

2 Validation Results of CAF Compilers

Tables 4,5, and 6 list the extent of support of coarrays in different CAF compiler implementations as detected by the UH CAF validation test suite:

Table 2. Cross-checked Feature test files in the UH - CAF Validation Tests suite

File	Description
atomic_8.5.2.f90	Atomic subroutines
critical_8.1.5.f90	CRITICAL - END CRITICAL sections
intrin_8.5.6.f90	LOCK & UNLOCK without STAT specifier
sync_8.5.3.f90	SYNC ALL without STAT specifier
sync_8.5.4a.f90	SYNC IMAGES(arr) paired with SYNC IMAGES(*)
sync_8.5.4b.f90	call to SYNC IMAGES(arr), should not behave like SYNC ALL

Table 3. Status Test files in the UH - CAF Validation Tests suite

File	Description
sync_8.5.7a.f90	STOP and SYNC ALL with STAT=STAT_STOPPED_IMAGE specifier
sync_8.5.7b.f90	STOP and SYNC IMAGES(arr) with STAT=STAT_STOPPED_IMAGE specifier
sync_8.5.7c.f90	STOP and SYNC IMAGES(*) with STAT=STAT_STOPPED_IMAGE specifier

Table 4. Results of Feature tests

DESCRIPTION	OpenUH	Intel	G95	Cray
CHARACTER coarrays	YES	YES	YES	YES
similar translation of co-subscripts and subscripts	YES	YES	YES	YES
reference of coarray without [] implies local object	YES	YES	YES	YES
attribute CODIMENSION + remote accesses at single integer/real boundary	YES	Exec times out	Exec fails	YES
(non-)coarray COMPONENTS of (non-)coarray derived types	YES	YES	YES	YES
explicit shape, assumed size, assumed shape, allocatable dummy arguments	YES	YES	comp fails	YES
NUM_IMAGES() returns the number of images launched	YES	YES	YES	YES
THIS_IMAGE(), THIS_IMAGE(coarray), THIS_IMAGE(coarray, dim)	YES	YES	YES	YES
LCOBOUND(coarray) and LCOBOUND(coarray,dim)	YES	YES	YES	YES
IMAGE_INDEX(coarray, subs)	YES	YES	YES	YES
UCOBOUND(COARRAY[, DIM, KIND])	YES	YES	YES	YES
ALLOCATE and DEALLOCATE act as barriers	YES	YES	YES	YES
STOP and LOCK construct with STAT=STAT_LOCKED specifier	YES	YES	comp fails	Exec fails
STOP and LOCK construct with STAT=STAT_LOCKED_OTHER_IMAGE specifier	Exec times out	Exec times out	comp fails	Exec times out
STOP and LOCK construct with STAT=STAT_UNLOCKED specifier	YES	Exec times out	comp fails	Exec fails
subobjects if a coarray is also a coarray	YES	YES	YES	YES
association of pointer components of coarrays with local objects	YES	Exec times out	YES	YES

Table 5. Results of Cross-Checked Feature tests

DESCRIPTION	OpenUH	Intel	G95	Cray
Atomic subroutines	YES	Fails compilation	Fails compilation	YES
CRITICAL - END CRITICAL sections	YES	YES	YES	Exec fails
LOCK & UNLOCK without STAT specifier	YES	Fails compilation	Fails compilation	YES
SYNC ALL without STAT specifier	YES	YES	YES	YES
SYNC IMAGES(arr) paired with SYNC IMAGES(*)	YES	Exec fails	YES	YES
call to SYNC IMAGES(arr), should not behave like SYNC ALL	YES	Exec fails	YES	YES

Table 6. Results of Status tests

DESCRIPTION	OpenUH	Intel	G95	Cray
STOP and SYNC ALL with STAT=STAT.STOPPED.IMAGE speci- fier	YES	Exec fails	Exec fails	Exec fails
STOP and SYNC IMAGES(arr) with STAT=STAT.STOPPED.IMAGE speci- fier	YES	YES	Exec fails	YES
STOP and SYNC IMAGES(*) with STAT=STAT.STOPPED.IMAGE speci- fier	YES	Exec fails	Exec fails	YES

References

1. ISO: "international standard ISO/IEC 1539-1:2010 (E) - Draft (for Ballot)", Third edition (June)
2. Numrich, R.W., Reid, J.: Co-arrays in the next fortran standard. SIGPLAN Fortran Forum 24(2), 4–17 (August 2005), <http://doi.acm.org/10.1145/1080399.1080400>