

Ivan Valbusa

The
biblatex-philosophy
bundle

v1.9 – 2016/11/26

Copyright © 2009-2016 Ivan Valbusa.

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c or later (<http://latex-project.org/lpp1>). This software is provided "as is", without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

If you have any questions, feedback or requests please email me at `ivan dot valbusa at univr dot it`. If you need specific features not already implemented, remember to attach the example files.

User's Guide to biblatex-philosophy

Bibliography styles for (Italian) users of biblatex

v1.9 – 2016/11/26

Ivan Valbusa

Dipartimento di Filologia, Letteratura e Linguistica
Università degli Studi di Verona
ivan dot valbusa at univr dot it

Abstract

This package provides a small collection of bibliography and citation styles for use with Philipp Lehman's `biblatex` package. These styles aim to match the needs of the Italian writers, particularly those concerned in the humanities (for example the comma is used to distinguish the units of the entry). They offer some useful features to compose detailed bibliographic entries including the translation data of foreign texts, annotations etc. Many options allow you to change the style defaults. Only the Italian, English and Spanish localization is available for now but you can use the styles with all the languages supported by `babel` (or `polyglossia`) adding simple redefinitions.

Contents

1	Use	4	4.2.1	philosophy-classic																																																													
				and philosophy-modern	12																																																												
2	The styles	5	4.2.2	philosophy-verbose	12																																																												
2.1	philosophy-classic	5																																																															
2.2	philosophy-modern	5	5	Customizations	13																																																												
2.3	philosophy-verbose	6	3	Specialities	6	5.1	Fonts	13	3.1	Related entries	6	5.2	Punctuation	13	3.2	Classical works	7	5.3	Lengths	13	3.3	Crossreferences	8	5.4	Languages	14	3.4	Annotated entries	8	5.5	Date and page ranges	14	3.5	Citation commands	9	6	Backward compatibility	14	4	Options	9	4.1	Global	9	6.1	Deprecated fields	14	4.2	Style-specific	12	6.2	Deprecated options	15	7	The Code	16	7.1	philosophy-standard.bbx	16				7.1.1	Global options	16
3	Specialities	6	5.1	Fonts	13																																																												
3.1	Related entries	6	5.2	Punctuation	13																																																												
3.2	Classical works	7	5.3	Lengths	13																																																												
3.3	Crossreferences	8	5.4	Languages	14																																																												
3.4	Annotated entries	8	5.5	Date and page ranges	14																																																												
3.5	Citation commands	9	6	Backward compatibility	14																																																												
4	Options	9	4.1	Global	9	6.1	Deprecated fields	14	4.2	Style-specific	12	6.2	Deprecated options	15	7	The Code	16	7.1	philosophy-standard.bbx	16				7.1.1	Global options	16																																							
4.1	Global	9	6.1	Deprecated fields	14																																																												
4.2	Style-specific	12	6.2	Deprecated options	15																																																												
7	The Code	16	7.1	philosophy-standard.bbx	16																																																												
			7.1.1	Global options	16																																																												

7.1.2	Name format	18	7.3.5	Internal commands for crossreferences	55
7.1.3	New internal commands	19	7.3.6	The <code>restoreclassic</code> option	56
7.1.4	Fields formats	20	7.4	<code>philosophy-verbose.bbx</code> .	57
7.1.5	The <code>orig-</code> macros (deprecated)	21	7.4.1	Initial settings	57
7.1.6	New macros	24	7.4.2	Internal commands for crossreferences	59
7.1.7	The <code>related</code> field mechanism	29	7.5	<code>philosophy-classic.cbx</code> .	67
7.1.8	Bibliography drivers .	30	7.5.1	Initial settings	67
7.2	<code>philosophy-classic.bbx</code> .	48	7.5.2	Author-title macros . .	68
7.2.1	Initial settings	48	7.5.3	Author-year macros .	70
7.2.2	New macros	51	7.5.4	Citation commands . .	73
7.2.3	Internal commands for crossreferences	52	7.6	<code>philosophy-modern.cbx</code> .	74
7.2.4	The <code>nodate</code> option . .	53	7.7	<code>philosophy-verbose.cbx</code> .	74
7.3	<code>philosophy-modern.bbx</code> .	53	7.7.1	Initial settings	74
7.3.1	Initial settings	53	7.7.2	New macros	77
7.3.2	New lengths	53	7.7.3	Citation commands . .	78
7.3.3	New commands	53	7.8	<code>italian-philosophy.lbx</code> .	79
7.3.4	New macros	54	7.9	<code>english-philosophy.lbx</code> .	80
			7.10	<code>spanish-philosophy.lbx</code> .	80

A brief history

The first step toward the creation of the `philosophy-modern` style was the request of Lorenzo Pantieri in the G_{IT} Forum: <http://www.guit.sssup.it/phpbb/viewtopic.php?t=6472> (See the discussion on <http://www.guit.sssup.it/phpbb/viewtopic.php?t=6717>.) Now this is the bibliography style of *L’arte di scrivere con L^AT_EX*, the most popular Italian guide to L^AT_EX (Pantieri and Gordini 2011).

I would like to thank who took part in the debate on G_{IT} Web site and the authors of the styles which inspired `biblatex-philosophy`, specifically: Dominik Waßenhoven (2011), James Clawson (2010) and Sander Gliboff (2010).

1 Use

The styles can be loaded as usual, but to ensure Italian-style quotation marks, you need to call the `babel` and `csquotes` packages in the preamble of your L^AT_EX document:

```
\usepackage[italian]{babel}
\usepackage[style=italian]{csquotes}
\usepackage[style=philosophy-<style>,backend=biber]{biblatex}
\addbibresource{<bibfile>.bib}
```

Replace `<style>` with `classic`, `modern` or `verbose`, and `<bibfile>` with the name of your bibliography file (“.bib” must be declared). See the example files in the `texmf-dist/doc/latex/biblatex-philosophy/examples.zip` folder.

To uniform the style of quotation marks in multilingual bibliographies typeset using the `babel=other` package option, you can use the `\DeclareQuoteAlias` command:

```
\DeclareQuoteAlias{italian}{german}
```

Warning! Since version 1.6 the package requires Biber (see Kime and Charette 2016) as backend bibliography processor so you have to set it properly in the preferences of the editor.

2 The styles

2.1 philosophy-classic

The `classic` style is a standard author-year style associated to a compact citation scheme which allows to cite multiple entries of the same author and/or published in the same year, omitting some redundant informations:

Knuth (1984, 1986a,b,c,d)

- Donald E. Knuth (1984–1986), *Computers & Typesetting*, 5 vols., Addison-Wesley, Reading, Mass.
- (1984) *Computers & Typesetting*, vol. A: *The TeXbook*, Addison-Wesley, Reading, Mass.
 - (1986a) *Computers & Typesetting*, vol. B: *TeX: The Program*, Addison-Wesley, Reading, Mass.
 - (1986b) *Computers & Typesetting*, vol. C: *The METAFONTbook*, Addison-Wesley, Reading, Mass.
 - (1986c) *Computers & Typesetting*, vol. D: *METAFONT: The Program*, Addison-Wesley, Reading, Mass.
 - (1986d) *Computers & Typesetting*, vol. E: *Computer Modern Typefaces*, Addison-Wesley, Reading, Mass.

2.2 philosophy-modern

The `philosophy-modern` style uses the `philosophy-classic` style for the citations but produces a fancy bibliography divided into blocks, which is particularly suited for bibliographies with many entries for the same author:

Donald E. Knuth

- 1984/1986 *Computers & Typesetting*, 5 vols., Addison-Wesley, Reading, Mass.
- 1984 *Computers & Typesetting*, vol. A: *The TeXbook*, Addison-Wesley, Reading, Mass.
- 1986a *Computers & Typesetting*, vol. B: *TeX: The Program*, Addison-Wesley, Reading, Mass.
- 1986b *Computers & Typesetting*, vol. C: *The METAFONTbook*, Addison-Wesley, Reading, Mass.
- 1986c *Computers & Typesetting*, vol. D: *METAFONT: The Program*, Addison-Wesley, Reading, Mass.

2.3 philosophy-verbose

This style is aimed for citations given in the footnotes and follows the most popular scheme used in the Italian humanities.

It prints a full citation similar to a bibliography entry when an item is cited for the first time, and a short citation afterwards, using the title (possibly shortened in the `shorttitle` field), followed by the string “cit.”. Citing the same entry two times, in the second one the string “Ivi” is used; citing the same place of the previous citation you will have “*Ibidem*”:

¹ Cfr. Cartesio, *Discorso sul metodo*, trad. e introd. di Lucia Urbani Ulivi, 1^a ed., testo francese a fronte, Bompiani, Milano 2002, p. 43.

² Ivi, p. 26.

³ *Ibidem*.

⁴ Settimo Termini, «Vita morte e miracoli di Alan Mathison Turing», in *Vite matematiche. Protagonisti del '900 da Hilbert a Wiles*, a cura di Claudio Bartocci *et al.*, Springer-Verlag Italia, Milano 2007, pp. 59–61.

⁵ Cartesio, *Discorso sul metodo* cit., p. 35.

When there is only one entry for the same author, with the `singletitle=true` option the string “op. cit.” is used instead of the (short) title followed by “cit.”:

⁶ Cartesio, op. cit., p. 35.

All the scholarly abbreviations (*latinitates*) but “cit.” are printed by default in normal font. With the `latinemph` option (section 4.2.2) you can get them in italic shape.

3 Specialities

The first simple and trivial characteristic of these style is that they use commas instead of dots to separate the parts of the entry, according to the most common Italian tradition. But they do much more, of course.

3.1 Related entries

The philosophy styles use the mechanism provided by the `related` field to typeset complex entries comprising both the original publication data and the translation data (see Poincaré 1968). Previous versions of the styles provided a different mechanism to manage translations. This feature is now deprecated and it is still supported only for backward compatibility. See section 6.1 for details.

Jules-Henri Poincaré (1968), *La science et l'hypothèse*, Flammarion, Paris; trans. as *La scienza e l'ipotesi*, ed. by Corrado Sinigaglia, Bompiani, Milano 2003.

```
@book{Poincare:1968-ORIG,
author      = {Jules-Henri Poincaré},
title       = {La science et l'hypothèse},
publisher   = {Flammarion},
location    = {Paris},
date        = {1968},
related     = {Poincare:1968-ITA}}
```

```
@book{Poincare:1968-ITA,
  author    = {Jules-Henri Poincaré},
  editor    = {Corrado Sinigaglia},
  title     = {La scienza e l'ipotesi},
  publisher = {Bompiani},
  location  = {Milano}}
```

Since Biber 1.6 you can have cascading relations too (see Popper 1934).

```
@Book{key1,
  ...
  related = {key2},
  ...
}

@Book{key2,
  ...
  related = {key3},

}

@Book{key3,
  ...
}
```

The related entry is preceded by the `translationas` string which defaults to “trad. it.” for Italian documents and “trans. as” for English documents. If you want to change it, use the `relatedstring` field. For example:

```
@book{Poincare:1968-ORIG,
  author      = {Jules-Henri Poincaré},
  ...
  related     = {Poincare:1968-ITA},
  relatedstring = {ed.~it.}}
```

3.2 Classical works

The treatment of the classical works and other writings with uncertain or omitted date is particularly difficult and inevitably imposes some choices.

If a critical edition exists you should cite it directly, such as Heidegger (2001). If you do not like this anachronistic label you may use the `shorthand` field, such as Kant (1968b [henceforth cited as KpV]). Note that a “shorthand intro” is automatically printed when the entry is cited for the first time and omitted afterwards. To turn off this capability load the option `shorthandintro=false`. In this case you will need a list of shorthands (`\printshorthands` command). If you do not like these solutions you can use the `entrysubtype` field with `classic` value (see section 3.2) or the `\sdcite` command (section 3.5).

`nameaddon` field (literal)

An addon to be printed immediately after the author name in the bibliography. It is useful for those author known with alias, Latinized names, etc. (see Komensky 1969).

entrysubtype field (literal)

This feature is active only for the `classic` and `modern` styles. With the `classic` value the citation commands will produce an author-title label. This is useful for citing works from classical antiquity, such as Aristotle, *Physics*:

```
@book{aristotle:physics,
  entrysubtype = {classic},
  author       = {Aristotle},
  title        = {Physics},
  ...
}
```

In the bibliography the entry is printed with the author-year label, but with the `skipbib` option in the `options` field you can exclude it from the bibliography.

3.3 Crossreferences

The `philosophy` styles allow you to manage entries referring to other entries through the `crossref` fields. This is very useful when you have to cite two or more `@incollection` of the same `@collection` (see Corrocher 2009; Federspil and Vettor 2009). In this way the `@collection` is printed in the bibliography and is cross-referenced inside the `@incollection`, using the corresponding author-year label (the mechanism is the same for `@inbook` items).

When you have to cite only one `@incollection` of a single `@collection` you have three choices:

1. use the `crossref` field (see Rossitto 1977; Termini 2007). In this case all the `@collection` data are automatically printed inside the `@incollection` entry;
2. put the `@collection` data in the fields of the `@incollection` entry (see Valbusa 2007). In this case the `@incollection` is self-contained;
3. put the `@collection` data in the fields of the `@incollection` entry and put the `@collection` label in the `xref` field of the `@incollection` (see Kant 1968c,d).

With the `verbose` style, when citing `@incollections` entries, the data of the `@collection` are printed entirely in the first citation and shortened afterwards. Anyway in the final bibliography the `@incollection` is always complete of all the informations about the corresponding `@collection`.

3.4 Annotated entries

library field (literal)

This field is printed at the end of the entry, in a new period. It is aimed for secondary informations such as the location of the texts, historical notes, etc. (see Heidegger 2001).

annotation/annotate field (literal)

This field is printed in a new paragraph at the very end of the entry. It requires the `annotation` package option. The default font can be changed redefining the `\annotationfont` command (section 5.1). See the examples in the references of this documentation.

3.5 Citation commands

`\sdcite{<key>}`

Uses an author-title label instead of an author-year label (defined only for the `classic` and `modern` styles). It is useful for some classical or undated works (see section 3.2). Writing `\sdcite[15]{guzman:sd}` you will obtain: Guzmán de Rojas, *Problemática*. This command is deprecated. Use the `entrysubtype` field instead (see section 3.2).

`\footcitet{<key>}`

Same as `\footcite`,^a but with the `\textcite` style.^b (defined only for the `classic` and `modern` styles).

^aCorrocher 2009, pp. 12–13.

^bCorrocher (2009, pp. 12–13).

`\ccite{<key>}`

The same as `\cite`, but omits the author’s (editor’s) name (defined only for the `verbose` style). Here is an example:

This topic is discussed in `\cite{Rossi:2007}` and in the recent
`\ccite{Rossi:2008}`.

This topic is discussed in P. Rossi, *History of Types*, La TeXnica, Verona 2007 and in the recent *Types of History*, Typographica, Milano 2008.

4 Options

4.1 Global

`relatedformat=semicolon, parens, brackets`

default: `semicolon`

semicolon The “related” entry is preceded by a semicolon.

Poincaré, Jules-Henri (1968), *La science et l’hypothèse*, Paris, Flammarion; trad. it. *La scienza e l’ipotesi*, Milano, Bompiani 2003.

parens Puts the “related” entry in parentheses.

Poincaré, Jules-Henri (1968), *La science et l’hypothèse*, Paris, Flammarion (trad. it. *La scienza e l’ipotesi*, Milano, Bompiani 2003).

brackets Same as the previous option but with brackets.

Poincaré, Jules-Henri (1968), *La science et l'hypothèse*, Paris, Flammarion [trad. it. *La scienza e l'ipotesi*, Milano, Bompiani 2003].

shorthandintro=true, false default: true

true Prints a language-specific expression such as “hence- forth cited as [<shorthand>]” to introduce shorthands on the first citation. You can overwrite the default expression using the `shorthandintro` field. Note that the alternative expression must include the shorthand.

Kant (1968a [henceforth cited as KpV])

false Does not print the intro to the shorthand. Obviously, this option requires a list of shorthands (`\printshorthand` command).

scauthors=true, false default: false

Prints the names (author, editor, etc.) at the beginning of the entry in small caps shape, both in citations and in bibliography:

If you want *all* the names (translator, commentator, etc.) in small caps, you have to redefine the `\mkbibname...` commands (see `biblatex` documentation for details).

scauthorsbib=true, false default: false

Same as the previous, but only for the bibliography.

scauthorscite=true, false default: false

Same as the previous, but only for the citations.

lowcauthors=true, false default: false

Prints the initials of the names in lowercase small capitals. For example you will obtain DONALD E. KNUTH instead of DONALD E. KNUTH. If you need the uppercase for some specific entries use the `\MakeUppercase` command.

publocformat=publocyear, locpubyear, loccolonpub default: publocyear

This option provides three styles for typesetting the “publisher/location/date” block. It is active also for the related entry (see above) and for the `orig`-fields (see section 6.1).

publocyear Oxford University Press, Oxford 2007

locpubyear Oxford, Oxford University Press, 2007

loccolonpub Oxford: Oxford University Press, 2007

volnumformat=strings, parens, plain default: plain

This option provides three styles for typesetting the “volume/number” block in `@article` entries.

- plain** ... *Journal Title*, 5, 8, ...
- strings** ... *Journal Title*, vol. 5, n. 8, ...
- parens** ... *Journal Title* (5, 8), ...

You can combine this option with `volumeformat` options and re-defining the `\volnumpunct` command you can get other styles (see section 5.3):

```
... Journal Title, 5/8, ...
... Journal Title, V/8, ...
... Journal Title (5/8), ...
... Journal Title (V/8), ...
```

volumeformat=arabic, roman, romansc, Roman default: arabic

This option provides three styles for typesetting the `volume` field:

- arabic** ... *Book Title*, vol. 12, ...
- roman** ... *Book Title*, vol. xii, ...
- romansc** ... *Book Title*, vol. XII, ...
- Roman** ... *Book Title*, vol. XII, ...

With the command

```
\DeclareFieldFormat{volume}{\bibstring{volume}~#1}
```

you can restore the default format for all but `@article` entries.

editionformat=arabic, roman, romansc, Roman, superscript default: arabic

This option provides three styles for typesetting the `edition` field:

- arabic** ... *Book Title*, 3^a ed., ...
- roman** ... *Book Title*, iii ed., ...
- romansc** ... *Book Title*, III ed., ...
- Roman** ... *Book Title*, III ed., ...
- superscript** ... *Book Title*, Publisher, Location 2010³. Available only for philosophy-verbose style.

inbeforejournal=true, false default: false

Prints the string “in” before the `journaltitle` in the `@article` entries.

<code>annotation=true, false</code>	default: false
Shows the <code>annotation</code> field, only in the bibliography (see also section 3.4).	
<code>library=true, false</code>	default: true
Shows the <code>library</code> field, both in the bibliography and in the citations (see also section 3.4).	
<code>classical=true, false</code>	default: false
[only for Italian and Spanish documents] It requires <code>babel</code> or <code>polyglossia</code> . If <code>true</code> it doubles the last consonant of the abbreviations such as “p.”, “vol.”, “col.” etc. when used in the plural form. For example you will have “p.” for “page” and “pp.” for “pages”. This habit is very common in Italian writings even if it remains useless.	

4.2 Style-specific

4.2.1 philosophy-classic and philosophy-modern

<code>square=true, false</code>	default: false
Uses brackets instead of parentheses in the citations and in the author-year label used in the bibliography.	
<code>nodate=true, false</code>	default: true
Prints the <code>nodate</code> string when <code>year</code> or <code>date</code> is missing.	
<code>yearleft=true, false</code>	default: false
[philosophy-modern only] Prints the date flushed left in the bibliography.	

<code>restoreclassic=true, false</code>	default: true
[philosophy-modern only]	
This option can be given as an optional argument of <code>\printbibliography</code> :	

```
\printbibliography [restoreclassic]
```

It restores the `classic` style in a document typeset using the `modern` style. It is useful to compose a “Web List” like that at the end of this document (active only for the `philosophy-modern`).

4.2.2 philosophy-verbose

<code>latinemph=true, false</code>	default: false
Prints the <i>latinitates</i> “ <i>ivi</i> ” and “ <i>ibidem</i> ” in italic shape.	
<code>commacit=true, false</code>	default: false
Adds a comma at the end of the <code>shorttitle</code> field when this is followed by the string <code>cit.</code> : “ <i>Descartes, Discours de la méthode, cit.</i> ”.	

5 Customizations

5.1 Fonts

`\annotationfont{<code>}` default: `\footnotesize`

The font of the annotation field. It can be redefined with:

```
\renewcommand*\annotationfont{\normalsize\sffamily}
```

`\libraryfont{<code>}` default: `\normalfont`

The font of the library field. It can be redefined with:

```
\renewcommand*\libraryfont{\sffamily}
```

5.2 Punctuation

`\volumpunct{<code>}` default: `\addcomma\space`

The separator between volume and number in `@article` entries. It can be redefined with:

```
\renewcommand*\volumpunct{/}
```

5.3 Lengths

The new lengths described in this section are defined only for the `modern` style. For the other customizable lengths see the `biblatex` documentation (Lehman 2011).

`\postnamesep` The space between author (or editor) and the first entry relating to him.

`\yeartitle` The space between year and title.

The `modern` style redefines also the following `biblatex` lengths:

`\bibnamesep` The vertical space between two blocks of authors.

`\bibitemsep` The vertical space between the individual entries in the bibliography.

`\bibhang` The hanging indentation of the bibliography.

These are the default values for the lengths used by the `modern` style:

```
\setlength{\yeartitle}{0.8em}
\setlength{\postnamesep}{0.5ex plus 2pt minus 1pt}
\setlength{\bibitemsep}{\postnamesep}
\setlength{\bibnamesep}{1.5ex plus 2pt minus 1pt}
\setlength{\bibhang}{4\parindent}
```

If you want to change them past these codes in the preamble of your document and modify the values according to your needs.

5.4 Using the styles with other languages

The languages currently supported by this package are Italian, English and Spanish.

In order to use the styles with different languages, you have to define in the preamble of your document all the string not defined in the localization file of the language loaded. This is a sample code for using the styles in german documents:

```
\NewBibliographyString{edorig,cit}
\DefineBibliographyStrings{german}{%
  inherit      = {german},
  translationas = {deut\addotspace \"Ubers\adddot},
  edorig       = {...},
  cit          = {...},
  reviewof     = {...}}
```

Another approach is to use the \DeclareLanguageMapping command. See the documentation of the biblatex package for details.

5.5 Date and page ranges

These style redefines the \bibrangedash and \bibdatedash commands in order to get a simple hyphen (-) instead of an en dash (–) in the page and date ranges. If you prefer the en dash use the following code:

```
\DefineBibliographyExtras{<language>}{%
  \protected\def\bibrangedash{%
    \textendash\penalty\hyphenpenalty}%
  \protected\def\bibdatedash{\bibrangedash}}%
```

For a consistent result you probably have to do this for all the languages loaded by babel or polyglossia.

6 Backward compatibility

This section explain a different mechanism (now deprecated) to manage entries comprising both the original publication data and the translation data. This mechanism uses some special fields.

6.1 Deprecated fields

The following fields can hold the translation or the original edition data. They are precede by the string “trans.” or “orig. ed.”, respectively according to the `origfields=trans` (default) or `origfields=origed` option (see below). Note that the `origdate/transdate` field is needed in order to print these fields. Contrarily they will be ignored.

`origtitle` field (literal)

`transtitle` field (literal biber only)

The title of the translation/original edition.

`origpublisher` field (list)

transpublisher field (list biber only)

The publisher of the translation/original edition.

origlocation field (list)

translocation field (list biber only)

The location of the translation/original edition.

origdate field (range)

transdate field (range biber only)

The publication date of the translation/original edition.

usera field (literal)

origbooktitle field (literal biber only)

transbooktitle field (literal biber only)

The title of the @collection/@book/@mvbook in which the translation/original edition of an @article (@inbook or @incollection) is published.

The field is printed after the `origtitle/transtitle`.

userb field (literal)

orignote field (literal biber only)

transnote field (literal biber only)

This field is printed after the `origtitle/transtitle`. It is meant for secondary informations about the translation/original edition, such as the name of editors, translators, etc.:

userc field (literal)

origpages field (literal biber only)

transpages field (literal biber only)

This field is printed at the end of the entry, after the `origdate/transdate` field. It is meant for the page range of the translation/original edition or other useful informations. In the first case string “p.” is omitted.

6.2 Deprecated options

origfields=trans, none, edorig

default: trans

true Prints the `orig-` fields.

none Omits the `orig-` fields.

origed This option cites the translation data first and adds the original publication data at the end of the entry, preceded by the string “orig. ed” (or “ed. orig.” for Italian documents).

origed=true, false default: true

Same as the previous but can be set on a per-entry basis in the options field. (see Lobačevskij 1994).

origfieldsformat=semicolon, parens, brackets default: semicolon

Deprecated. Use the `relatedformat` option instead.

semicolon The translation/original publication data are preceded by a semicolon.

parens Puts the translation or the original publication data in parentheses.

brackets Same as the previous option but with brackets instead of parentheses.

References

The bibliography style of the document is `philosophy-modern`, but in this list of references we use `philosophy-classic` through the `restoreclassic` option. This is particularly useful for typesetting Web lists which.

Clawson, James (2010), *biblatex-mla*. *MLA Style Using biblatex*, version 0.95, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-mla/doc/biblatex-mla.pdf>.

The `biblatex-mla` files provide support to `biblatex`, `bibtex`, and `latex` for citations and Works Cited lists in the style established by the Modern Language Association (MLA).

Gliboff, Sander (2010), *User's Guide to Historian. A Footnotes-and-Bibliography Style, Following Turabian/Chicago Guidelines: For Use with the Biblatex System of Programmable Bibliographies and Citations*, version 0.4, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-historian/historian.pdf>.

`Historian` follows the conventions of The Chicago Manual of Style, as presented in Turabian's Manual for Writers.

Kime, Philip and François Charette (2016), *biber*. *A backend bibliography processor for biblatex*, version 2.5, <http://biblatex-biber.sourceforge.net>.

Lehman, Philipp (2011), *The biblatex package. Programmable Bibliographies and Citations*, version 1.7, <http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.pdf>.

This document is a systematic reference manual for the `biblatex` package. Look at the sample documents which ship with `biblatex` to get a first impression.

Pantieri, Lorenzo and Tommaso Gordini (2011), *L'arte di scrivere con L^AT_EX. Un'introduzione a L^AT_EX*, with a forew. by Enrico Gregorio, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.

The most popular Italian guide to L^AT_EX. A little masterpiece of style and typesetting.

Waßenhoven, Dominik (2011), *biblatex-dw*, version 1.4, <http://mirrors.ctan.org/macros/latex/contrib/biblatex-contrib/biblatex-dw/doc/biblatex-dw.pdf>.

A small collection of styles for the `biblatex` package. It was designed for citations in the Humanities and offers some features that are not provided by the standard `biblatex` styles.

Examples

Aristotle

- 1929 *Physics*, trans. by P. H. Wicksteed and F. M. Cornford, G. P. Putnam, New York.
 A book entry with a `translator` field.

Corrocher, Roberto

- 2009 “Riflessioni sull’uomo di fronte a nuove sfide”, in Giaretta et al. (2009), pp. 27–42.
 An `@incollection` entry. The `@collection` is automatically printed in the bibliography because another `@incollection` has been cited.

Federspil, Giovanni and Roberto Vettor

- 2009 “Medicina: un unico metodo e una sola argomentazione?”, in Giaretta et al. (2009), pp. 43–74.
 An `@incollection` entry. The `@collection` is automatically printed in the bibliography because another `@incollection` has been cited.

Giaretta, Pierdaniele, Antonio Moretto, Gian Franco Gensini, and Marco Trabucchi

- 2009 (eds.), *Filosofia delle medicina. Metodo, modelli, cura ed errori*, 2 vols., il Mulino, Bologna.
 A collection with four editors. The list is automatically truncated in the citations.

Guzmán de Rojas, Iván

- s.d. *Problemática logico-lingüística de la comunicación social con el pueblo Aymara*, mimeo,
 Con los auspicios del Centro internacional de Investigaciones para el Desarrollo de
 Canada.
 A work without a publication date. The string `nodate` (localized) is automatically printed.

Heidegger, Martin

- 2001 *Sein und Zeit*, 18th ed., Max Niemeyer Verlag, Tübingen. Apparso originariamente nel
 1927 nell’annuario diretto da H. Husserl *Jahrbuch für Philosophie und phänomenologische Forschung* (vol. VIII).
 Note the `library` field, use for some details about the first edition.

Kant, Immanuel

- 1968a *Kants Werke. Akademie Textausgabe*, 9 vols., Walter de Gruyter, Berlin.
 1968b *Kritik der praktischen Vernunft*, in *Kants Werke. Akademie Textausgabe*, vol. 5: *Kritik der praktischen Vernunft. Kritik der Urtheilskraft*, Walter de Gruyter, Berlin, pp. 1–163.
 An edition of Kant’s *Collected Works*, volume five. This is an `inbook` entry which explicitly refers to the *Critique of Practical Reason* only, not to the entire fifth volume. Note the `author` and `bookauthor` fields in the database file. By default, the `bookauthor` is omitted if the values of the `author` and `bookauthor` fields are identical.
 1968c *Kritik der praktischen Vernunft*, in Kant (1968a), vol. 5, pp. 1–163.
 1968d *Kritik der Urtheilskraft*, in Kant (1968a), vol. 5, pp. 165–485.

Komensky, Jan Amos [Comenio]

- 1969 *Opera Omnia*, Praga.

This author is known with his Latin name, given in the `nameaddon` field.

Lobačevskij, Nikolaj Ivanovič

- 1994 *Nuovi principi della geometria. Con una teoria completa delle parallele*, ed. by Lucio Lombardo Radice, with a forew. by Evandro Agazzi, Bollati Boringhieri, Torino; orig. ed. 1835.

An entry typeset using the depreciated `orig-` fields mechanism.

Pantieri, Lorenzo and Tommaso Gordini

- 2011 *L’arte di scrivere con L^AT_EX. Un’introduzione a L^AT_EX*, with a forew. by Enrico Gregorio, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.
The most popular Italian guide to L^AT_EX. A little masterpiece of style and typesetting.

Poincaré, Jules-Henri

- 1968 *La science et l’hypothèse*, Flammarion, Paris; trans. *La scienza e l’ipotesi*, ed. by Corrado Sinigaglia, testo greco a fronte, Bompiani, Milano 2003.
A book entry followed by its translation, cross-referenced in the `related` field.

Popper, Karl R.

- 1934 *Logik der Forschung*, Springer, Wien; trans. *The Logic of Scientific Discovery*, 3rd ed., Hutchinson, London 1959; it. trans. *Logica della scoperta scientifica*, 3rd ed., Einaudi, Torino 1998.
A book entry followed by two different translations, cross-referenced in the `related` (biber 1.6 required).

Rossitto, Cristina

- 1977 “Opposizione e non contraddizione nella *Metafisica* di Aristotele”, in *La contraddizione*, ed. by Enrico Berti, Città Nuova, Roma, pp. 43–69.
Note that the `@collection` data (inherited from the `crossref` field) are printed inside the `@incollection` entry because this is the the only `@incollection` cited from that `@collection`.

Termini, Settimò

- 2007 “Vita morte e miracoli di Alan Mathison Turing”, in *Vite matematiche. Protagonisti del ’900 da Hilbert a Wiles*, ed. by Claudio Bartocci, Renato Betti, Angelo Guerraggio, and Roberto Lucchetti, Springer-Verlag Italia, Milano.

Valbusa, Ivan

- 2007 “Psicologia e sistema in Alsted e in Wolff”, in *Christian Wolff tra psicologia empirica e psicologia razionale*, ed. by Ferdinando Luigi Marcolungo, Georg Olms Verlag, Hildesheim, Zürich, and London.

Web List

Here we have a list of Web sites typeset with the `philosophy-classic` style through the `restoreclassic` option.

CTAN (2006), *CTAN. The Comprehensive TeX Archive Network*, <http://www.ctan.org> (visited on 10/01/2006).

Note the `urldate` field and the `label` field, used for the citations.

GUIT. *Gruppo degli Utilizzatori Italiani di T_EX* (2012), <http://www.guitex.org> (visited on 01/15/2012).

A Web site.

7 The Code

7.1 philosophy-standard.bbx

```
1 \RequireBiber[3]
2 \RequireBibliographyStyle{standard}
```

Load the localization modules:

```
3 \DeclareLanguageMapping{italian}{italian-philosophy}
4 \DeclareLanguageMapping{english}{english-philosophy}
5 \DeclareLanguageMapping{spanish}{spanish-philosophy}
```

7.1.1 Global options

```
6 \newtoggle{bbx:annotation}
7 \newtoggle{bbx:library}
8 \newtoggle{bbx:scauthors}
9 \newtoggle{bbx:scauthorsbib}
10 \newtoggle{bbx:inbeforejournal}
11 \newtoggle{bbx:classical}
12 \newtoggle{bbx:lowscauthors}

13
14 \newtoggle{cbx:shorthandintro}

15
16 \DeclareBibliographyOption{annotation}[true]{%
17   \settoggle{bbx:annotation}{#1}}
18 \DeclareBibliographyOption{library}[true]{%
19   \settoggle{bbx:library}{#1}}
20 \DeclareBibliographyOption{scauthors}[true]{%
21   \settoggle{bbx:scauthors}{#1}}
22 \DeclareBibliographyOption{scauthorsbib}[true]{%
23   \settoggle{bbx:scauthorsbib}{#1}}
24 \DeclareBibliographyOption{inbeforejournal}[true]{%
25   \settoggle{bbx:inbeforejournal}{#1}}
26 \DeclareBibliographyOption{classical}[true]{%
27   \settoggle{bbx:classical}{#1}}
28 \DeclareBibliographyOption{lowscauthors}[true]{%
29   \settoggle{bbx:lowscauthors}{#1}}

30
31 \DeclareBibliographyOption{shorthandintro}[true]{%
32   \settoggle{cbx:shorthandintro}{#1}}

33
34
35 \newcommand{\bbx@publocformat}{}%
36 \newcommand{\bbx@volnumformat}{}%
37 \newcommand{\bbx@relatedformat}{}%
38 \newcommand{\bbx@origfields}{}%
39 \newcommand{\bbx@editionformat}{}%
40 \newcommand{\bbx@volumeformat}{}%

41
42 \DeclareBibliographyOption{publocformat}[publocyear]{%
43   \renewcommand{\bbx@publocformat}{#1}}
44 \DeclareBibliographyOption{volnumformat}[plain]{%
45   \renewcommand{\bbx@volnumformat}{#1}}
```

```

46 \DeclareBibliographyOption{origfieldsformat}[semicolon]{%
47   \renewcommand{\bbx@relatedformat}{#1}}
48 \DeclareBibliographyOption{relatedformat}[semicolon]{%
49   \renewcommand{\bbx@relatedformat}{#1}}
50 \DeclareBibliographyOption{origfields}[true]{%
51   \renewcommand{\bbx@origfields}{#1}}
52 \DeclareBibliographyOption{editionformat}[arabic]{%
53   \renewcommand{\bbx@editionformat}{#1}}
54 \DeclareBibliographyOption{volumeformat}[arabic]{%
55   \renewcommand{\bbx@volumeformat}{#1}}
56
57 \DeclareEntryOption{origed}[true]{%
58   \renewcommand{\bbx@origfields}{origed}}
59
60 \ExecuteBibliographyOptions{%
61   lowscauthors      = false,
62   publocformat     = publocyear,
63   annotation       = false,
64   library          = true,
65   scauthors        = false,
66   scauthorsbib    = false,
67   origfieldsformat = semicolon,
68   inbeforejournal  = false,
69   volnumformat     = plain,
70   editionformat    = arabic,
71   volumeformat     = arabic,
72   classical        = false,
73   useprefix         = true,
74   maxcitenames    = 2,
75   mincitenames    = 1,
76   maxbibnames     = 999,
77   minbibnames     = 999,
78   shorthandintro  = true}

```

Changing the penalty of the urls will prevent many overfull boxes.

```

79 \setcounter{biburlnumpenalty}{9000}
80 \setcounter{biburlucpenalty}{9000}
81 \setcounter{biburllcpenalty}{9000}

```

These counters control the list of names of cross-referenced entries:

```

82 \newcounter{maxnamesincross}
83 \newcounter{minnamesincross}

```

7.1.2 Name format

```

84 \AtBeginDocument{%
85   \iftoggle{bbx:lowscauthors}{%
86     {\newrobustcmd*{\mkbibsc}[1]{\textsc{\MakeLowercase{#1}}}}{%
87     {\newrobustcmd*{\mkbibsc}[1]{\textsc{#1}}}}{%
88   \iftoggle{bbx:scauthors}{%
89     \toggletrue{bbx:scauthorsbib}{%
90     \toggletrue{cbx:scauthorscite}{%
91   {}}}{%
92 \AtBeginBibliography{%

```

```
93 \iftoggle{bbx:scauthorsbib}{%
94 %\DeclareNameFormat{family-given/given-family}{%
95 %  \let\mkbibnamefamily\mkbibsc%
96 %  \let\mkbibnamegiven\mkbibsc%
97 %  \let\mkbibnameprefix\mkbibsc%
98 %  \let\mkbibnameaffix\mkbibsc%
99 % \ifnumequal{\value{listcount}}{1}%
100 %  {\liffirstinits
101 %   {\usebibmacro{name:family-given}{#1}{#4}{#5}{#7}}%
102 %   {\usebibmacro{name:family-given}{#1}{#3}{#5}{#7}}%
103 %  \ifblank{#3#5}
104 %   {}
105 %   {\usebibmacro{name:revsdelim}}}
106 %  {\liffirstinits
107 %   {\usebibmacro{name:given-family}{#1}{#4}{#5}{#7}}%
108 %   {\usebibmacro{name:given-family}{#1}{#3}{#5}{#7}}}}
109 % \usebibmacro{name:andothers}}%
110 \DeclareNameFormat{sortname}{%
111  \let\mkbibnamefamily\mkbibsc%
112  \let\mkbibnamegiven\mkbibsc%
113  \let\mkbibnameprefix\mkbibsc%
114  \let\mkbibnameaffix\mkbibsc%
115  \nameparts{#1}%
116 \ifnumequal{\value{listcount}}{1}%
117  {\lifgiveninits
118   {\usebibmacro{name:family-given}
119    {\namepartfamily}
120    {\namepartgiveni}
121    {\namepartprefix}
122    {\namepartsuffix}}
123   {\usebibmacro{name:family-given}
124    {\namepartfamily}
125    {\namepartgiven}
126    {\namepartprefix}
127    {\namepartsuffix}}}}
128 \ifboolexpe{%
129  test {\ifdefvoid\namepartgiven}
130  and
131  test {\ifdefvoid\namepartprefix}}
132  {}
133  {\usebibmacro{name:revsdelim}}}
134 {\lifgiveninits
135  {\usebibmacro{name:given-family}
136   {\namepartfamily}
137   {\namepartgiveni}
138   {\namepartprefix}
139   {\namepartsuffix}}
140  {\usebibmacro{name:given-family}
141   {\namepartfamily}
142   {\namepartgiven}
143   {\namepartprefix}
144   {\namepartsuffix}}}}%
```

```
145 \usebibmacro{name:andothers}}}}%
146 {}}}
```

7.1.3 New internal commands

```
147 \renewcommand*{\newunitpunct}{\addcomma\space}
148 \renewcommand*{\subtitlepunct}{\addperiod\space}
149 \renewcommand*{\intitlepunct}{\nopunct\addspace}
150 \newcommand*{\volnumpunct}{\addcomma\space}
```

We have to define a new internal command in order to get pure parenthese for some specific fields when using the square option:

```
151 \newrobustcmd*{\mkpureparens}[1]{%
152   \begingroup
153   \blx@blxinit
154   \blx@setsfcodes
155   \blx@postpunct(#1\blx@postpunct)\midsentence%
156   \endgroup}
```

Indexing

```
157 \renewbibmacro*citeindex}{%
158 \ifciteindex{\indexnames{labelname}}{}}
159 \renewbibmacro*bibindex}{%
160 \ifbibindex{\indexnames{author}}%
161 \indexnames{editor}%
162 \indexnames{editora}%
163 \indexnames{editorb}%
164 \indexnames{editorc}}%
165 {}}}
```

Font selection

```
166 \newcommand*{\annotationfont}{\footnotesize}
167 \newcommand*{\libraryfont}{}
168 \newcommand*{\editionfont}{%
169   \ifdefstring{\bbx@editionformat}{Roman}%
170     {\uppercase}%
171     {\ifdefstring{\bbx@editionformat}{romansc}%
172       {\scshape}%
173       {\relax}}%
174   }%
175 \newrobustcmd*{\edfnt}[1]{%
176   \begingroup
177   \expandafter\editionfont
178   \expandafter{\romannumeral#1}%
179   \endgroup}
```

7.1.4 Fields formats

```
180 \DeclareFieldFormat[bookinbook,thesis]{title}{\mkbibemph{#1}}
181 \DeclareFieldFormat[review]{title}{\bibstring{reviewof}\addspace#1}
182 \DeclareFieldFormat[review]{citetitle}{\bibstring{reviewof}\addspace#1}
183 \DeclareFieldFormat[inreference,article]{title}{\mkbibquote{#1}}
184 \DeclareFieldFormat[bookinbook,thesis]{citetitle}{\mkbibemph{#1}}
```

```
185 \DeclareFieldFormat{origtitle}{\mkbibemph{#1}}
186 \DeclareFieldFormat[article]{origtitle}{\mkbibquote{#1}}
187 \DeclareFieldFormat{usera}{\mkbibemph{#1}}
188 \DeclareFieldFormat[bookinbook,inbook]{usera}{\mkbibemph{#1}}
189 \DeclareFieldFormat[incollection]{usera}{\mkbibquote{#1}}
190 \DeclareFieldFormat{userc}{\mkpageprefix[bookpagination]{#1}}
191 \DeclareFieldFormat{url}{\url{#1}}
192 \DeclareFieldFormat{annotation}{\annotationfont #1}
193 \DeclareFieldFormat{library}{\libraryfont #1}
194 \DeclareFieldFormat{backrefparens}{\mkpureparens{#1}}
195 \DeclareFieldFormat{pureparens}{\mkpureparens{#1}}
196
197 \def\optionerror#1{%
198 \ClassError{biblatex-philosophy}%
199     {\MessageBreak**** Unknown value for '#1' option}%
200     {\MessageBreak**** Unknown value for '#1' option}%
201 }
202
203 \DeclareFieldFormat{volume}{%
204     \bibstring{volume}%
205     \ifinteger{#1}{%
206         \ifdefstring{\bbx@volumeformat}{arabic}{%
207             {#1}%
208             \ifdefstring{\bbx@volumeformat}{Roman}{%
209                 {\RNN{#1}}%
210                 \ifdefstring{\bbx@volumeformat}{romansc}{%
211                     {\textsc{\Rn{#1}}}%
212                     \ifdefstring{\bbx@volumeformat}{roman}{%
213                         {\Rn{#1}}{\optionerror{volumeformat}}}}}}}}{#1}%
214
215 \DeclareFieldFormat[article]{volume}{%
216     \ifdefstring{\bbx@volnumformat}{strings}{%
217         \bibstring{volume}%
218         {}%
219         \ifinteger{#1}{%
220             \ifdefstring{\bbx@volumeformat}{arabic}{%
221                 {#1}%
222                 \ifdefstring{\bbx@volumeformat}{Roman}{%
223                     {\RNN{#1}}%
224                     \ifdefstring{\bbx@volumeformat}{romansc}{%
225                         {\textsc{\Rn{#1}}}%
226                         \ifdefstring{\bbx@volumeformat}{roman}{%
227                             {\Rn{#1}}{\optionerror{volumeformat}}}}}}}}{#1}%
228
229 \DeclareFieldFormat*[number]{%
230     \ifdefstring{\bbx@volnumformat}{strings}{%
231         \bibstring{number}~#1{#1}%
232     \DeclareFieldFormat*[series]{%
233         \ifinteger{#1}{%
234             {\mkbibordseries{#1}\bibstring{jourser}}%
235             {\lfbibstring{#1}\bibstring{#1}{#1}}%
236     \DeclareFieldFormat{edition}{%
```

```

237 \ifinteger{#1}{%
238   \ifdefstring{\bbx@editionformat}{arabic}{%
239     {\mkbibordedition{#1}\bibstring{edition}}%
240     {\ifdefstring{\bbx@editionformat}{Roman}{%
241       {\RN{#1}\bibstring{edition}}%}
242       {\ifdefstring{\bbx@editionformat}{romansc}{%
243         {\textsc{\Rn{#1}}\bibstring{edition}}%}
244         {\ifdefstring{\bbx@editionformat}{roman}{%
245           {\Rn{#1}\bibstring{edition}}%
246           {\ifdefstring{\bbx@editionformat}{superscript}{%
247             {\ClassError{biblatex-philosophy}{%
248               {\MessageBreak**** Option 'editionformat=superscript',%
249               available only for philosophy-verbose style}}%
250             {\MessageBreak**** Option 'editionformat=superscript',%
251               available only for philosophy-verbose style}}%
252           }}}}{}{#1}}%}\isdot??
253 \DeclareFieldFormat{related}{%
254   \ifdefstring{\bbx@relatedformat}{parens}{%
255     {\mkpureparens{#1}}%}
256     {\ifdefstring{\bbx@relatedformat}{brackets}{%
257       {\mkbibbrackets{#1}}%}
258       {\ifdefstring{\bbx@relatedformat}{semicolon}{%
259         {#1}{\optionerror{relatedformat}}}}}}%}

```

7.1.5 The orig- macros (deprecated)

These macros are provided for backward compatibility. The new `related` field mechanism now directly support also this feature.

```

260 \newbibmacro*[origpublisher+origlocation+origdate]{%
261   \ifdefstring{\bbx@publocformat}{loccolonpub}{%
262     {\usebibmacro{origloccolonpub}\setunit{\bibpagespunct}}%
263       \printfield{userc}{\ifdefstring{\bbx@publocformat}{locpubyear}{%
264         {\usebibmacro{origlocpubyear}\setunit{\bibpagespunct}}%
265           \printfield{userc}}%
266         {\usebibmacro{origpublicyear}\setunit{\bibpagespunct}}%
267           \printfield{userc}}}}%
268 
269 \newbibmacro*[origpublicyear]{%
270   \iflistundef{origpublisher}{%
271     {\printlist{origlocation}}%
272     \setunit*{\addspace}%
273     \printorigdate}%
274   {\printlist{origpublisher}}%
275     \setunit*{\addcomma\space}%
276   \printlist{origlocation}%
277   \setunit*{\addspace}%
278     \printorigdate}%
279   \newunit}%
280 
281 \newbibmacro*[origloccolonpub]{%
282   \iflistundef{origlocation}{%
283     {\printlist{origlocation}}%}

```

```
284 \iflistundef{origpublisher}%
285     {\setunit*{\addspace}%
286 \printorigdate}%
287     {\setunit*{\addcolon\space}%
288 \printlist{origpublisher}%
289 \setunit*{\addcomma\space}%
290 \printorigdate}%
291 \newunit
292
293 \newbibmacro*{origlocpubyear}{%
294 \iflistundef{origlocation}{}{%
295     {\printlist{origlocation}}{%
296 \iflistundef{origpublisher}%
297     {\setunit*{\addspace}%
298 \printorigdate}%
299     {\setunit*{\addcomma\space}%
300 \printlist{origpublisher}%
301 \setunit*{\addcomma\space}%
302 \printorigdate}%
303 \newunit
304
305 \newbibmacro*{reprinttitle}{%
306 \iffieldundef{reprinttitle}{}{%
307 \iffieldsequal{reprinttitle}{title}{}{%
308     \printfield[title]{reprinttitle}%
309     \setunit{\addcomma\space}}{}}%
310 \iffieldundef{userb}{}{%
311     \printfield{userb}}{}}%
312
313 \newbibmacro*{transorigstring}{%
314 \iffieldundef{reprinttitle}%
315 {\printtext{\ifdefstring{\bbx@origfields}{origed}%
316 {\bibstring{origed}}}}{%
317 {\bibstring{translationas}}}\nopunct}%
318 {\printtext{\bibstring{reprint}}}\nopunct}
319
320 \newbibmacro*{origtitle:book}{%
321 \iffieldundef{origtitle}{}{%
322     \printfield[origtitle]{origtitle}%
323     \setunit{\addcomma\space}}{}}%
324 \iffieldundef{userb}{}{%
325     \printfield{userb}}{}}%
326
327 \newbibmacro*{origtitledata:book}{%
328 \usebibmacro{transorigstring}%
329 \iffieldundef{reprinttitle}%
330 {\usebibmacro{origtitle:book}}{%
331 {\usebibmacro{reprinttitle}}{}}%
332 \newunit\newblock
333 \usebibmacro{origpublisher+origlocation+origdate}}%
334
335 \newbibmacro*{origdata:book}{%
```

```

336 \ifboolexpr{%
337   test {\iffieldundef{origtitle}}
338   and
339   test {\iffieldundef{origlocation}}
340   and
341   test {\iffieldundef{origpublisher}}
342   and
343   test {\iffieldundef{origyear}}
344 }%
345 {}%
346   {\ifdefstring{\bbx@relatedformat}{parens}
347     {\nopunct\printtext[pureparens]{\usebibmacro{origtitledata:book}}}
348     {\ifdefstring{\bbx@relatedformat}{brackets}
349       {\nopunct\printtext[brackets]{\usebibmacro{origtitledata:book}}}
350       {\setunit{\addsemicolon\space}%
351         \printtext{\usebibmacro{origtitledata:book}}}}}}
352
353 \newbibmacro*[origtitle:article-inbook-incoll]{%
354   \iffieldundef{origtitle}{}{%
355     \printfield[origtitle]{origtitle}%
356     \setunit{\addcomma\space}%
357     \iffieldundef{usera}{}{%
358       \usebibmacro{in:}%
359       \printfield{usera}%
360         \setunit{\addcomma\space}%
361     \iffieldundef{userb}{}{%
362       \printfield{userb}%
363       \newunit}%
364   }
365 \newbibmacro*[origtitledata:article-inbook-incoll]{%
366   \usebibmacro{transorigstring}%
367   \setunit{\addspace}%
368   \usebibmacro{origtitle:article-inbook-incoll}%
369   \usebibmacro{origpublisher+origlocation+origdate}%
370
371 \newbibmacro*[origdata:article-inbook]{}%
372   \iflistundef{origlocation}{}{%
373     \ifdefstring{\bbx@relatedformat}{parens}
374       {\nopunct\printtext[pureparens]{%
375         \usebibmacro{origtitledata:article-inbook-incoll}}}
376       {\ifdefstring{\bbx@relatedformat}{brackets}
377         {\nopunct\printtext[brackets]{%
378           \usebibmacro{origtitledata:article-inbook-incoll}}}
379         \setunit{\addsemicolon\space}%
380       \printtext{%
381     \usebibmacro{origtitledata:article-inbook-incoll}}}}}

```

7.1.6 New macros

```

382 \renewbibmacro*[addendum+pubstate]{%
383   \printfield{addendum}%
384   \newunit\newblock

```

```
385 \printfield{pubstate}%
386 \ifdefstring{\bbx@origfields}{none}{}{%
387   \newunit\newblock
388   \usebibmacro{origdata:book}}%
389   \newunit\newblock
390   \usebibmacro{library}}
391
392 \newbibmacro*{addendum+pubstate:article-inbook-incoll}{%
393   \printfield{addendum}%
394   \newunit\newblock
395   \printfield{pubstate}%
396   \ifdefstring{\bbx@origfields}{none}{}{%
397     \newunit\newblock
398     \usebibmacro{origdata:article-inbook}}%
399     \newunit\newblock
400     \usebibmacro{library}}
401
402 \newbibmacro*{volnumdefault}{%
403   \printfield{volume}%
404   \setunit*{\volumpunct}%
405   \printfield{number}}
406
407 \newbibmacro*{volnumparens}{%
408   \nopunct%
409   \printtext[pureparens]{%
410     \printfield{volume}%
411     \setunit*{\volumpunct}%
412     \printfield{number}}}
413
414 \newbibmacro*{volnumstrings}{%
415   \iffieldundef{volume}{}{%
416     \printfield{volume}\setunit*{\volumpunct}}%
417   \iffieldundef{number}{}{%
418     \printfield{number}}}
419
420 \renewbibmacro*{journal}{%
421   \iffieldundef{journaltitle}%
422   {}
423   {\printtext[journaltitle]{%
424     \printfield[titlecase]{journaltitle}%
425     \midsentence%MOD#####
426     \setunit{\subtitlepunct}%
427     \printfield[titlecase]{journalsubtitle}}}}
428
429 \renewbibmacro*{periodical}{%
430   \iffieldundef{title}%
431   {}
432   {\printtext[title]{%
433     \printfield[titlecase]{title}%
434     \midsentence%MOD#####
435     \setunit{\subtitlepunct}%
436     \printfield[titlecase]{subtitle}}}}
```

```
437
438 \renewbibmacro*{journal+issuetitle}{%
439   \usebibmacro{journal}%
440   \setunit*{\addspace}%
441   \iffieldundef{series}
442     {}
443     {\newunit%
444      \printfield{series}\setunit{\addspace}\midsentence}%
445     \newunit%
446   \usebibmacro{volume+number+eid}%
447   \setunit{\addspace}%
448   \usebibmacro{issue+date}%
449   \setunit{\addcolon\space}%
450   \usebibmacro{issue}%
451   \newunit}
452
453 \renewbibmacro*{title+issuetitle}{%
454   \usebibmacro{periodical}%
455   \setunit*{\addspace}%
456   \iffieldundef{series}
457     {}
458     {\newunit%
459      \printfield{series}%
460      \setunit{\addspace}\midsentence}%
461     \newunit%
462     \usebibmacro{volume+number+eid}%
463     \setunit{\addcomma\space}%
464     \printfield{eid}%
465     \setunit{\addspace}%
466     \usebibmacro{issue+date}%
467     \setunit{\addcolon\space}%
468     \usebibmacro{issue}%
469     \newunit}
470
471 \renewbibmacro*{volume+number+eid}{%
472   \ifdefstring{\bbx@volnumformat}{strings}
473     {\usebibmacro{volnumstrings}}%
474   \ifdefstring{\bbx@volnumformat}{parens}
475     {\usebibmacro{volnumparens}}%
476   \ifdefstring{\bbx@volnumformat}{plain}
477     {\usebibmacro{volnumdefault}}%
478     {\optionerror{volnumformat}}}%
479   \setunit{\addcomma\space}%
480   \printfield{eid}}
481
482 \renewbibmacro*{issue+date}{%
483   \printtext[pureparens]{%
484     \iffieldundef{issue}
485       {\usebibmacro{date}}
486       {\printfield{issue}}%
487       \setunit*{\addspace}%
488       \usebibmacro{date}}}}
```

```
489 \newunit}
490
491 \renewbibmacro*{event+venue+date}{%v0.8
492   \printfield{eventtitle}%
493   \ifboolexpr{%
494     test {\iffieldundef{venue}}
495     and
496     test {\iffieldundef{eventyear}}}
497 }%
498 {}
499 {\setunit*{\addspace}%
500 \printtext{%
501   \printfield{venue}%
502   \setunit*{\addcomma\space}%
503   \printeventdate}%
504 \newunit}
505
506 \renewbibmacro*{series+number}{%
507   \printfield{series}%
508   \setunit*{\addcomma\space}%
509   \printfield{number}%
510   \newunit}
511
512 \renewbibmacro*{publisher+location+date}{%
513   \ifdefstring{\bbx@publocformat}{loccolonpub}
514     {\usebibmacro{loccolonpub}}
515     {\ifdefstring{\bbx@publocformat}{locpubyear}
516       {\usebibmacro{locpubyear}}
517       {\ifdefstring{\bbx@publocformat}{publocyear}%
518         {\usebibmacro{publocyear}}{\optionerror{publocformat}}}}}
519
520 \renewbibmacro*{institution+location+date}{%
521   \ifdefstring{\bbx@publocformat}{loccolonpub}
522     {\usebibmacro{inloccolonpub}}
523     {\ifdefstring{\bbx@publocformat}{locpubyear}
524       {\usebibmacro{inlocpubyear}}
525       {\ifdefstring{\bbx@publocformat}{publocyear}%
526         {\usebibmacro{inpublocyear}}{\optionerror{publocformat}}}}}
527
528 \renewbibmacro*{organization+location+date}{%
529   \ifdefstring{\bbx@publocformat}{loccolonpub}
530     {\usebibmacro{orgloccolonpub}}
531     {\ifdefstring{\bbx@publocformat}{locpubyear}
532       {\usebibmacro{orglocpubyear}}
533       {\ifdefstring{\bbx@publocformat}{publocyear}%
534         {\usebibmacro{orgpublocyear}}{\optionerror{publocformat}}}}}
535
536 \newbibmacro*{library}{%
537   \iftoggle{bbx:library}{%
538     \iffieldundef{library}%
539   {}%
540     {\setunit{\addperiod\space}}%
```

```
541     {\printfield{library}}}}}%  
542 }
```

In this macro the `\nopunct` command is needed to avoid the dot after the parentheses.

```
543 \renewbibmacro*{pageref}{%  
544   \iflistundef{pageref}  
545     {}%  
546     {\setunit{\addperiod\space}%  
547      \printtext[backrefparens]{%  
548        \ifnumgreater{\value{pageref}}{1}  
549          {\bibstring{backrefpages}\ppspace}%  
550        {\bibstring{backrefpage}\ppspace}%  
551        \printlist[pageref][-{\value{listtotal}}]{pageref}\adddot\nopunct}}}%  
552  
553 \renewbibmacro*{finentry}{%  
554   \iftoggle{bbx:annotation}{%  
555     {\iffieldundef{annotation}{%  
556       {\finentry}{%  
557         {\setunit{\addperiod\par\nobreak\vspace{.5ex}}}%  
558         \printtext[annotation]{\printfield{annotation}\finentry\par}}}}}%  
559   {\finentry}}}  
560  
561 \newbibmacro*{publocyear}{%  
562   \iflistundef{publisher}{%  
563     {}%  
564   {\printlist[publisher]}  
565     \setunit*{\addcomma\space}%  
566     \printlist[location]{%  
567       \usebibmacro{relateddate}}%  
568   \newunit}  
569  
570 \newbibmacro*{inpublocyear}{%  
571   \iflistundef{institution}{%  
572     {}%  
573   {\printlist[institution]}  
574     \setunit*{\addcomma\space}%  
575     \printlist[location]{%  
576       \usebibmacro{relateddate}}%  
577   \newunit}  
578  
579 \newbibmacro*{orgpublocyear}{%  
580   \iflistundef{organization}{%  
581     {}%  
582   {\printlist[organization]}  
583     \setunit*{\addcomma\space}%  
584     \printlist[location]{%  
585       \usebibmacro{relateddate}}%  
586   \newunit}  
587  
588 \newbibmacro*{loccolonpub}{%  
589   \printlist[location]{%  
590   \iflistundef{publisher}{%
```

```
591  {\setunit*{\addspace}}%
592  {\setunit*{\addcolon\space}}%
593  \printlist{publisher}%
594  \usebibmacro{commarelateddate}%
595 \newunit
596
597 \newbibmacro*{inloccolonpub}{%
598  \printlist{location}%
599  \iflistundef{institution}
600  {\setunit*{\addspace}}%
601  {\setunit*{\addcolon\space}}%
602  \printlist{institution}%
603  \usebibmacro{commarelateddate}%
604  \newunit
605
606 \newbibmacro*{orgloccolonpub}{%
607  \printlist{location}%
608  \iflistundef{organization}
609  {\setunit*{\addspace}}%
610  {\setunit*{\addcolon\space}}%
611  \printlist{organization}%
612  \usebibmacro{commarelateddate}%
613  \newunit
614
615 \newbibmacro*{locpubyear}{%
616  \printlist{location}%
617  \iflistundef{publisher}%
618  {\setunit*{\addspace}}%
619  {\setunit*{\addcomma\space}}%
620  \printlist{publisher}%
621  \usebibmacro{commarelateddate}%
622 \newunit
623
624 \newbibmacro*{inlocpubyear}{%
625  \printlist{location}%
626  \iflistundef{institution}
627  {\setunit*{\addspace}}%
628  {\setunit*{\addcomma\space}}%
629  \printlist{institution}%
630  \usebibmacro{commarelateddate}%
631  \newunit
632
633 \newbibmacro*{orglocpubyear}{%
634  \printlist{location}%
635  \iflistundef{organization}
636  {\setunit*{\addspace}}%
637  {\setunit*{\addcomma\space}}%
638  \printlist{organization}%
639  \usebibmacro{commarelateddate}%
640  \newunit}
```

7.1.7 The related field mechanism

```

641 \newbibmacro*[relateddate]{%
642   \setunit{\addspace}%
643   \printdate}
644 \newbibmacro*[commarelateddate]{%
645   \setunit{\addcomma\space}%
646   \printdate}
```

A trick to delete the author/editor list for related entries and \ccite command:

```

647 \newbibmacro*[related:clearauthors]{%
648   \renewbibmacro*[author/translator+others]{\usebibmacro{bbx:savehash}}%
649   \renewbibmacro*[author/editor+others/translator+others]{%
650     \usebibmacro{bbx:savehash}}%
651   \renewbibmacro*[editor+others]{\usebibmacro{bbx:savehash}}%
652   \renewbibmacro*[author/translator+others]{\usebibmacro{bbx:savehash}}%
653   \renewbibmacro*[author/editor]{\usebibmacro{bbx:savehash}}%
654   \renewbibmacro*[author]{\usebibmacro{bbx:savehash}}%
655   \renewbibmacro*[editor]{\usebibmacro{bbx:savehash}}%
656   \renewcommand*{\labelnamepunct}{}}}%
657
658 \DeclareCiteCommand{\relatedcite}
659   {}%
660   {\usedriver
661     {\DeclareNameAlias{sortname}{default}}%
662     \usebibmacro{related:clearauthors}%
663     \renewbibmacro*[relateddate]{%
664       \setunit{\addspace}\printdate}%
665     \renewbibmacro*[commarelateddate]{%
666       \setunit{\addcomma\space}\printdate}%
667       {\thefield{entrytype}}}%
668   {}%
669   {}%
670
671 \renewbibmacro*[related:default][1]{%
672   \togglefalse{cbx:sauthorscite}%
673   \togglefalse{bbx:annotation}%
674 \iffieldundef{relatedstring}%
675   {\bibstring{translationas}\space}%
676   {\printtext{\addspace}}%
677   \ifentrytype{article}{}{\%horrible trick
678   \renewcommand*{\mkpureparens}{\unspace\addsemicolon\space}%
679   \renewcommand*{\mkbibbrackets}{\unspace\addsemicolon\space}%
680   \relatedcite{\thefield{related}}}}
```

7.1.8 Bibliography drivers

```

681 \DeclareBibliographyDriver{article}{%
682 \renewbibmacro*[related:default][1]{%
683   \togglefalse{cbx:sauthorscite}%
684   \togglefalse{bbx:annotation}%
685 \iffieldundef{relatedstring}%
686   {\bibstring{translationas}\space}%
687   {\setunit{\bibstring{translationas}\space}}%
688   \relatedcite{\thefield{related}}}%
689 \usebibmacro{bibindex}}
```

```
690 \usebibmacro{begentry}%
691 \usebibmacro{author+translator+others}%
692 \setunit{\labelnamepunct}\newblock
693 \usebibmacro{title}%
694 \newunit
695 \printlist{language}%
696 \newunit\newblock
697 \usebibmacro{byauthor}%
698 \newunit\newblock
699 \usebibmacro{bytranslator+others}%
700 \newunit\newblock
701 \printfield{version}%
702 \newunit\newblock
703 \iftoggle{bbx:inbeforejournal}{\usebibmacro{in:}}{}%
704 \usebibmacro{journal+issuetitle}%
705 \newunit\newblock
706 \usebibmacro{byeditor+others}%
707 \newunit\newblock
708 \usebibmacro{note+pages}%
709 \newunit\newblock
710 \iftoggle{bbx:isbn}
711   {\printfield{issn}}
712   {}%
713 \newunit\newblock
714 \usebibmacro{doi+eprint+url}%
715 \newunit\newblock
716 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
717 \newblock
718 \iftoggle{bbx:related}
719   {\ifdefstring{\bbx@relatedformat}{semicolon}{\setunit{\addsemicolon\space}}%
720   {\setunit{\unspace\space}}%horrible trick
721   \usebibmacro{related:init}%
722   \usebibmacro{related}{}%
723   {}%
724 \newunit\newblock
725 \usebibmacro{pageref}%
726 \usebibmacro{finentry}%
727
728 \DeclareBibliographyDriver{book}%
729   \usebibmacro{bibindex}%
730   \usebibmacro{begentry}%
731   \usebibmacro{author+editor+others+translator+others}%
732   \setunit{\labelnamepunct}\newblock
733   \usebibmacro{maintitle+title}%
734   \newunit
735   \printlist{language}%
736   \newunit\newblock
737   \usebibmacro{byauthor}%
738   \newunit\newblock
739   \usebibmacro{byeditor+others}%
740   \newunit\newblock
741   \printfield{edition}%
```

```
742 \newunit
743 \printfield{volumes}%
744 \newunit\newblock
745 \usebibmacro{series+number}%
746 \newunit\newblock
747 \printfield{note}%
748 \newunit\newblock
749 \usebibmacro{publisher+location+date}%
750 \newunit
751 \iffieldundef{maintitle}
752   {\printfield{volume}%
753    \printfield{part}%
754   {}%
755 \newunit\newblock
756 \usebibmacro{chapter+pages}%
757 \newunit
758 \printfield{pagetotal}%
759 \newunit\newblock
760 \iftoggle{bbx:isbn}
761   {\printfield{isbn}%
762   {}%
763 \newunit\newblock
764 \usebibmacro{doi+eprint+url}%
765 \newunit\newblock
766 \usebibmacro{addendum+pubstate}%
767 \newblock
768 \iftoggle{bbx:related}
769   {\ifdefstring{\bbx@relatedformat}{semicolon}%
770    {\setunit{\addsemicolon\space}}%
771    {\setunit{\unspace\space}}%horrible trick
772    \usebibmacro{related:init}%
773    \usebibmacro{related}{}%
774   {}%
775 \newunit\newblock
776 \usebibmacro{pageref}%
777 \usebibmacro{finentry}%
778
779 \DeclareBibliographyDriver{booklet}{%
780   \usebibmacro{bibindex}%
781   \usebibmacro{begentry}%
782   \usebibmacro{author/editor+others/translator+others}%
783   \setunit{\labelnamepunct}\newblock
784   \usebibmacro{title}%
785   \newunit
786   \printlist{language}%
787   \newunit\newblock
788   \usebibmacro{byauthor}%
789   \newunit\newblock
790   \usebibmacro{byeditor+others}%
791   \newunit\newblock
792   \printfield{howpublished}%
793   \newunit\newblock
```

```
794 \printfield{type}%
795 \newunit\newblock
796 \printfield{note}%
797 \newunit\newblock
798 \usebibmacro{location+date}%
799 \newunit\newblock
800 \usebibmacro{chapter+pages}%
801 \newunit
802 \printfield{pagetotal}%
803 \newunit\newblock
804 \usebibmacro{doi+eprint+url}%
805 \newunit\newblock
806 \usebibmacro{addendum+pubstate}%
807 \newblock
808 \iftoggle{bbx:related}
809   {\ifdefstring{\bbx@relatedformat}{semicolon}%
810    {\setunit{\addsemicolon\space}}%
811    {\setunit{\unspace\space}}%horrible trick
812    \usebibmacro{related:init}%
813    \usebibmacro{related}}%
814  {}%
815 \newunit\newblock
816 \usebibmacro{pageref}%
817 \usebibmacro{finentry}%
818
819 \DeclareBibliographyDriver{collection}%
820   \usebibmacro{bibindex}%
821   \usebibmacro{begentry}%
822   \usebibmacro{editor+others}%
823   \setunit{\labelnamepunct}\newblock
824   \usebibmacro{maintitle+title}%
825   \newunit
826   \printlist{language}%
827   \newunit\newblock
828   \usebibmacro{byeditor+others}%
829   \newunit\newblock
830   \printfield{edition}%
831   \newunit
832   \iffieldundef{maintitle}
833     {\printfield{volume}%
834      \printfield{part}}
835   {}%
836   \newunit
837   \printfield{volumes}%
838   \newunit\newblock
839   \usebibmacro{series+number}%
840   \newunit\newblock
841   \printfield{note}%
842   \newunit\newblock
843   \usebibmacro{publisher+location+date}%
844   \newunit\newblock
845   \usebibmacro{chapter+pages}%
```

```
846 \newunit
847 \printfield{pagetotal}%
848 \newunit\newblock
849 \iftoggle{bbx:isbn}
850   {\printfield{isbn}}
851   {}%
852 \newunit\newblock
853 \usebibmacro{doi+eprint+url}%
854 \newunit\newblock
855 \usebibmacro{addendum+pubstate}%
856 \newblock
857 \iftoggle{bbx:related}
858   {\ifdefstring{\bbx@relatedformat}{semicolon}%
859     {\setunit{\addsemicolon\space}}%
860     {\setunit{\unspace\space}}%horrible trick
861   \usebibmacro{related:init}%
862   \usebibmacro{related}}%
863 {}%
864 \newunit\newblock
865 \usebibmacro{pageref}%
866 \usebibmacro{finentry}%
867
868 \DeclareBibliographyDriver{inbook}{%
869 \togglefalse{cbx:scauthorscite}%
870   \usebibmacro{bibindex}%
871   \usebibmacro{begentry}%
872   \usebibmacro{author/translator+others}%
873   \setunit{\labelnamepunct}\newblock
874   \usebibmacro{title}%
875   \newunit
876   \printlist{language}%
877   \newunit\newblock
878   \usebibmacro{byauthor}%
879   \newunit\newblock
880   \usebibmacro{in:}%
881   \iffieldundef{xref}%
882     {\iffieldundef{crossref}{\usebibmacro{inbook:full}}%
883       {\bbx@crossref@inbook{\thefield{crossref}}}%
884     \newunit\newblock
885     \usebibmacro{crossrefdata}}%
886     {\bbx@crossref@inbook{\thefield{xref}}}%
887     \newunit\newblock
888     \usebibmacro{xrefdata}}%
889
890 \newbibmacro*{inbook:full}{%
891   \usebibmacro{bybookauthor}%
892   \newunit\newblock
893   \usebibmacro{maintitle+booktitle}%
894   \newunit\newblock
895   \usebibmacro{byeditor+others}%
896   \newunit\newblock
897   \printfield{edition}%
898 }
```

```
898 \newunit
899 \printfield{volumes}%
900 \newunit\newblock
901 \usebibmacro{series+number}%
902 \newunit\newblock
903 \printfield{note}%
904 \newunit\newblock
905 \usebibmacro{publisher+location+date}%
906 \newunit
907 \iffieldundef{maintitle}
908   {\printfield{volume}%
909     \printfield{part}%
910   {}%
911 \newunit\newblock
912 \usebibmacro{chapter+pages}%
913 \newunit\newblock
914 \iftoggle{bbx:isbn}
915   {\printfield{isbn}%
916   {}%
917 \newunit\newblock
918 \usebibmacro{doi+eprint+url}%
919 \newunit\newblock
920 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
921 \newblock
922 \iftoggle{bbx:related}
923   {\ifdefstring{\bbx@relatedformat}{semicolon}%
924     {\setunit{\addsemicolon\space}}%
925     {\setunit{\unspace\space}}%horrible trick
926     \usebibmacro{related:init}%
927       \usebibmacro{related}{}%
928   {}%
929 \newunit\newblock
930 \usebibmacro{pageref}%
931 \usebibmacro{finentry}%
932
933 \DeclareBibliographyDriver{incollection}{%
934   \togglefalse{cbx:sauthorscite}%
935   \usebibmacro{bibindex}%
936   \usebibmacro{begentry}%
937   \usebibmacro{author/translator+others}%
938   \setunit{\labelnamepunct}\newblock
939   \usebibmacro{title}%
940   \newunit
941   \printlist{language}%
942   \newunit\newblock
943   \usebibmacro{byauthor}%
944   \newunit\newblock
945   \usebibmacro{in:}%
946   \iffieldundef{xref}%
947     {\iffieldundef{crossref}{\usebibmacro{incollection:full}}%
948     {\bbx@crossref@incollection{\thefield{crossref}}}%
949   \newunit\newblock}
```

```
950 \usebibmacro{crossrefdata}}}}%
951 {\bbx@crossref@incollection{\thefield{xref}}}}%
952 \newunit\newblock
953 \usebibmacro{xrefdata}}}

954 \newbibmacro*{incollection:full}{%
955 \usebibmacro{maintitle+booktitle}}%
956 \newunit\newblock
957 \usebibmacro{byeditor+others}}%
958 \newunit\newblock
959 \printfield{edition}}%
960 \newunit
961 \printfield{volumes}}%
962 \newunit\newblock
963 \usebibmacro{series+number}}%
964 \newunit\newblock
965 \printfield{note}}%
966 \newunit\newblock
967 \usebibmacro{publisher+location+date}}%
968 \newunit
969 \iffieldundef{maintitle}
970   {\printfield{volume}}%
971     \printfield{part}}%
972   {}}}%
973 \newunit\newblock
974 \usebibmacro{chapter+pages}}%
975 \newunit\newblock
976 \iftoggle{bbx:isbn}
977   {\printfield{isbn}}%
978   {}}}%
979 \newunit\newblock
980 \usebibmacro{doi+eprint+url}}%
981 \newunit\newblock
982 \usebibmacro{addendum+pubstate:article-inbook-incoll}}%
983 \newblock
984 \iftoggle{bbx:related}
985   {\ifdefstring{\bbx@relatedformat}{semicolon}}%
986     {\setunit{\addsemicolon\space}}}}%
987   {\setunit{\unspace\space}}%horrible trick
988 \usebibmacro{related:init}}%
989   \usebibmacro{related}}}}%
990   {}}}%
991 \newunit\newblock
992 \usebibmacro{pageref}}%
993 \usebibmacro{finentry}}}

995 \DeclareBibliographyDriver{inproceedings}{%
996 \togglefalse{cbx:scauthorscite}}%
997 \usebibmacro{bibindex}}%
998 \usebibmacro{begentry}}%
999 \usebibmacro{author/translator+others}}%
1000 \setunit{\labelnamepunct}\newblock
```

```
1002 \usebibmacro{title}%
1003 \newunit
1004 \printlist{language}%
1005 \newunit\newblock
1006 \usebibmacro{byauthor}%
1007 \newunit\newblock
1008 \usebibmacro{in:}%
1009 \iffieldundef{xref}%
1010 {\iffieldundef{crossref}{\usebibmacro{inproceedings:full}}%
1011 {\bbx@crossref@incollection{\thefield{crossref}}}}
1012 \newunit\newblock
1013 \usebibmacro{crossrefdata}%
1014 {\bbx@crossref@incollection{\thefield{xref}}}
1015 \newunit\newblock
1016 \usebibmacro{xrefdata}%
1017
1018 \newbibmacro*[inproceedings:full]{%
1019   \usebibmacro{maintitle+booktitle}%
1020   \newunit\newblock
1021   \usebibmacro{event+venue+date}%
1022   \newunit\newblock
1023   \usebibmacro{byeditor+others}%
1024   \newunit
1025   \printfield{volumes}%
1026   \newunit\newblock
1027   \usebibmacro{series+number}%
1028   \newunit\newblock
1029   \printfield{note}%
1030   \newunit\newblock
1031   \printlist{organization}%
1032   \newunit
1033   \usebibmacro{publisher+location+date}%
1034   \newunit
1035   \iffieldundef{maintitle}%
1036     {\printfield{volume}%
1037      \printfield{part}}
1038   {}%
1039   \newunit\newblock
1040   \usebibmacro{chapter+pages}%
1041   \newunit\newblock
1042   \iftoggle{bbx:isbn}%
1043     {\printfield{isbn}}
1044   {}%
1045   \newunit\newblock
1046   \usebibmacro{doi+eprint+url}%
1047   \newunit\newblock
1048   \usebibmacro{addendum+pubstate:article-inbook-incoll}%
1049   \newblock
1050   \iftoggle{bbx:related}%
1051     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1052       {\setunit{\addsemicolon\space}}%
1053       {\setunit{\unspace\space}}%horrible trick
```

```
1054     \usebibmacro{related:init}%
1055     \usebibmacro{related}{}%
1056     {}%
1057     \newunit\newblock
1058     \usebibmacro{pageref}%
1059     \usebibmacro{finentry}%
1060
1061 \DeclareBibliographyDriver{manual}{%
1062     \usebibmacro{bibindex}%
1063     \usebibmacro{begentry}%
1064     \usebibmacro{author/editor}%
1065     \setunit{\labelnamepunct}\newblock
1066     \usebibmacro{title}%
1067     \newunit
1068     \printlist{language}%
1069     \newunit\newblock
1070     \usebibmacro{byauthor}%
1071     \newunit\newblock
1072     \usebibmacro{byeditor}%
1073     \newunit\newblock
1074     \printfield{edition}%
1075     \newunit\newblock
1076     \usebibmacro{series+number}%
1077     \newunit\newblock
1078     \printfield{type}%
1079     \newunit
1080     \printfield{version}%
1081     \newunit
1082     \printfield{note}%
1083     \newunit\newblock
1084     \printlist{organization}%
1085     \newunit
1086     \usebibmacro{publisher+location+date}%
1087     \newunit\newblock
1088     \usebibmacro{chapter+pages}%
1089     \newunit
1090     \printfield{pagetotal}%
1091     \newunit\newblock
1092     \iftoggle{bbx:isbn}%
1093         {\printfield{isbn}}%
1094         {}%
1095     \newunit\newblock
1096     \usebibmacro{doi+eprint+url}%
1097     \newunit\newblock
1098     \usebibmacro{addendum+pubstate}%
1099     \newblock
1100     \iftoggle{bbx:related}%
1101         {\ifdefstring{\bbx@relatedformat}{semicolon}%
1102             {\setunit{\addsemicolon\space}}%
1103             {\setunit{\unspace\space}}%horrible trick
1104         \usebibmacro{related:init}%
1105         \usebibmacro{related}{}%
```

```
1106      {}%
1107  \newunit\newblock
1108  \usebibmacro{pageref}%
1109  \usebibmacro{finentry}%
1110
1111 \DeclareBibliographyDriver{misc}{%
1112  \usebibmacro{bibindex}%
1113  \usebibmacro{begentry}%
1114  \usebibmacro{author/editor+others/translator+others}%
1115  \setunit{\labelnamepunct}\newblock
1116  \usebibmacro{title}%
1117  \newunit
1118  \printlist{language}%
1119  \newunit\newblock
1120  \usebibmacro{byauthor}%
1121  \newunit\newblock
1122  \usebibmacro{byeditor+others}%
1123  \newunit\newblock
1124  \printfield{howpublished}%
1125  \newunit\newblock
1126  \printfield{type}%
1127  \newunit
1128  \printfield{version}%
1129  \newunit
1130  \printfield{note}%
1131  \newunit\newblock
1132  \usebibmacro{organization+location+date}%
1133  \newunit\newblock
1134  \usebibmacro{doi+eprint+url}%
1135  \newunit\newblock
1136  \usebibmacro{addendum+pubstate}%
1137  \newblock
1138  \iftoggle{bbx:related}%
1139    {\ifdefstring{\bbx@relatedformat}{semicolon}%
1140     {\setunit{\addsemicolon\space}}%
1141     {\setunit{\unspace\space}}%horrible trick
1142     \usebibmacro{related:init}%
1143     \usebibmacro{related}%
1144   }%
1145  \newunit\newblock
1146  \usebibmacro{pageref}%
1147  \usebibmacro{finentry}%
1148
1149 \DeclareBibliographyDriver{online}{%
1150  \usebibmacro{bibindex}%
1151  \usebibmacro{begentry}%
1152  \usebibmacro{author/editor+others/translator+others}%
1153  \setunit{\labelnamepunct}\newblock
1154  \usebibmacro{title}%
1155  \newunit
1156  \printlist{language}%
1157  \newunit\newblock
```

```
1158 \usebibmacro{byauthor}%
1159 \newunit\newblock
1160 \usebibmacro{byeditor+others}%
1161 \newunit\newblock
1162 \printfield{version}%
1163 \newunit
1164 \printfield{note}%
1165 \newunit\newblock
1166 \printlist{organization}%
1167 \newunit\newblock
1168 \usebibmacro{date}%
1169 \newunit\newblock
1170 \iftoggle{bbx:eprint}
1171   {\usebibmacro{eprint}}
1172   {}%
1173 \newunit\newblock
1174 \usebibmacro{url+urldate}%
1175 \newunit\newblock
1176 \usebibmacro{addendum+pubstate}%
1177 \newblock
1178 \iftoggle{bbx:related}
1179   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1180     {\setunit{\addsemicolon\space}}%
1181     {\setunit{\unspace\space}}%horrible trick
1182   \usebibmacro{related:init}%
1183   \usebibmacro{related}%
1184   {}%
1185 \newunit\newblock
1186 \usebibmacro{pageref}%
1187 \usebibmacro{finentry}%
1188
1189 \DeclareBibliographyDriver{patent}{%
1190   \usebibmacro{bibindex}%
1191   \usebibmacro{begentry}%
1192   \usebibmacro{author}%
1193   \setunit{\labelnamepunct}\newblock
1194   \usebibmacro{title}%
1195   \newunit
1196   \printlist{language}%
1197   \newunit\newblock
1198   \usebibmacro{byauthor}%
1199   \newunit\newblock
1200   \printfield{type}%
1201   \setunit*\{\addspace}%
1202   \printfield{number}%
1203   \iflistundef{location}
1204     {}
1205     {\setunit*\{\addspace}%
1206      \printtext[parens]{%
1207        \printlist[][-\value{listtotal}]{location}}}%
1208   \newunit\newblock
1209   \usebibmacro{byholder}%
```

```
1210 \newunit\newblock
1211 \printfield{note}%
1212 \newunit\newblock
1213 \usebibmacro{date}%
1214 \newunit\newblock
1215 \usebibmacro{doi+eprint+url}%
1216 \newunit\newblock
1217 \usebibmacro{addendum+pubstate}%
1218 \newblock
1219 \iftoggle{bbx:related}
1220   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1221    {\setunit{\addsemicolon\space}}%
1222    {\setunit{\unspace\space}}%horrible trick
1223   \usebibmacro{related:init}%
1224     \usebibmacro{related}%
1225   {}%
1226 \newunit\newblock
1227 \usebibmacro{pageref}%
1228 \usebibmacro{finentry}%

1229
1230 \DeclareBibliographyDriver{periodical}{%
1231   \usebibmacro{bibindex}%
1232   \usebibmacro{begentry}%
1233   \usebibmacro{editor}%
1234   \setunit{\labelnamepunct}\newblock
1235   \usebibmacro{title+issuetitle}%
1236   \newunit
1237   \printlist{language}%
1238   \newunit\newblock
1239   \usebibmacro{byeditor}%
1240   \newunit\newblock
1241   \printfield{note}%
1242   \newunit\newblock
1243   \iftoggle{bbx:isbn}
1244     {\printfield{issn}}
1245   {}%
1246   \newunit\newblock
1247   \usebibmacro{doi+eprint+url}%
1248   \newunit\newblock
1249   \usebibmacro{addendum+pubstate}%
1250   \newblock
1251   \iftoggle{bbx:related}
1252     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1253      {\setunit{\addsemicolon\space}}%
1254      {\setunit{\unspace\space}}%horrible trick
1255     \usebibmacro{related:init}%
1256       \usebibmacro{related}%
1257     {}%
1258   \newunit\newblock
1259   \usebibmacro{pageref}%
1260   \usebibmacro{finentry}%
1261 }
```

```
1262 \DeclareBibliographyDriver{proceedings}{%
1263   \usebibmacro{bibindex}%
1264   \usebibmacro{begentry}%
1265   \usebibmacro{editor+others}%
1266   \setunit{\labelnamepunct}\newblock
1267   \usebibmacro{maintitle+title}%
1268   \newunit
1269   \printlist{language}%
1270   \newunit\newblock
1271   \usebibmacro{event+venue+date}%
1272   \newunit\newblock
1273   \usebibmacro{byeditor+others}%
1274   \newunit\newblock
1275   \iffieldundef{maintitle}%
1276     {\printfield{volume}%
1277      \printfield{part}%
1278    {}%
1279   \newunit
1280   \printfield{volumes}%
1281   \newunit\newblock
1282   \usebibmacro{series+number}%
1283   \newunit\newblock
1284   \printfield{note}%
1285   \newunit\newblock
1286   \printlist{organization}%
1287   \newunit
1288   \usebibmacro{publisher+location+date}%
1289   \newunit\newblock
1290   \usebibmacro{chapter+pages}%
1291   \newunit
1292   \printfield{pagetotal}%
1293   \newunit\newblock
1294   \iftoggle{bbx:isbn}%
1295     {\printfield{isbn}%
1296    {}%
1297   \newunit\newblock
1298   \usebibmacro{doi+eprint+url}%
1299   \newunit\newblock
1300   \usebibmacro{addendum+pubstate}%
1301   \newblock
1302   \iftoggle{bbx:related}%
1303     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1304      {\setunit{\addsemicolon\space}}%
1305      {\setunit{\unspace\space}}%\horrible trick
1306      \usebibmacro{related:init}%
1307      \usebibmacro{related}%
1308    {}%
1309   \newunit\newblock
1310   \usebibmacro{pageref}%
1311   \usebibmacro{finentry}%
1312 \DeclareBibliographyDriver{report}{%
```

```
1314 \usebibmacro{bibindex}%
1315 \usebibmacro{begentry}%
1316 \usebibmacro{author}%
1317 \setunit{\labelnamepunct}\newblock
1318 \usebibmacro{title}%
1319 \newunit
1320 \printlist{language}%
1321 \newunit\newblock
1322 \usebibmacro{byauthor}%
1323 \newunit\newblock
1324 \printfield{type}%
1325 \setunit*{\addspace}%
1326 \printfield{number}%
1327 \newunit\newblock
1328 \printfield{version}%
1329 \newunit
1330 \printfield{note}%
1331 \newunit\newblock
1332 \usebibmacro{institution+location+date}%
1333 \newunit\newblock
1334 \usebibmacro{chapter+pages}%
1335 \newunit
1336 \printfield{pagetotal}%
1337 \newunit\newblock
1338 \iftoggle{bbx:isbn}
1339   {\printfield{isrn}}
1340   {}%
1341 \newunit\newblock
1342 \usebibmacro{doi+eprint+url}%
1343 \newunit\newblock
1344 \usebibmacro{addendum+pubstate}%
1345 \newblock
1346 \iftoggle{bbx:related}
1347   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1348     {\setunit{\addsemicolon\space}}%
1349     {\setunit{\unspace\space}}%horrible trick
1350   \usebibmacro{related:init}%
1351   \usebibmacro{related}%
1352   {}%
1353 \newunit\newblock
1354 \usebibmacro{pageref}%
1355 \usebibmacro{finentry}%
1356
1357 \DeclareBibliographyDriver{thesis}%
1358   \usebibmacro{bibindex}%
1359   \usebibmacro{begentry}%
1360   \usebibmacro{author}%
1361   \setunit{\labelnamepunct}\newblock
1362   \usebibmacro{title}%
1363   \newunit
1364   \printlist{language}%
1365   \newunit\newblock
```

```
1366 \usebibmacro{byauthor}%
1367 \newunit\newblock
1368 \printfield{note}%
1369 \newunit\newblock
1370 \printfield{type}%
1371 \newunit
1372 \usebibmacro{institution+location+date}%
1373 \newunit\newblock
1374 \usebibmacro{chapter+pages}%
1375 \newunit
1376 \printfield{pagetotal}%
1377 \newunit\newblock
1378 \iftoggle{bbx:isbn}
1379   {\printfield{isbn}}
1380   {}%
1381 \newunit\newblock
1382 \usebibmacro{doi+eprint+url}%
1383 \newunit\newblock
1384 \usebibmacro{addendum+pubstate}%
1385 \newblock
1386 \iftoggle{bbx:related}
1387   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1388     {\setunit{\addsemicolon\space}}%
1389     {\setunit{\unspace\space}}%\horrible trick
1390   \usebibmacro{related:init}%
1391   \usebibmacro{related}%
1392   {}%
1393 \newunit\newblock
1394 \usebibmacro{pageref}%
1395 \usebibmacro{finentry}%
1396
1397 \DeclareBibliographyDriver{unpublished}{%
1398   \usebibmacro{bibindex}%
1399   \usebibmacro{begentry}%
1400   \usebibmacro{author}%
1401   \setunit{\labelnamepunct}\newblock
1402   \usebibmacro{title}%
1403   \newunit
1404   \printlist{language}%
1405   \newunit\newblock
1406   \usebibmacro{byauthor}%
1407   \newunit\newblock
1408   \printfield{howpublished}%
1409   \newunit\newblock
1410   \printfield{note}%
1411   \newunit\newblock
1412   \usebibmacro{location+date}%
1413   \newunit\newblock
1414   \iftoggle{bbx:url}
1415     {\usebibmacro{url+urldate}%
1416     {}%
1417 \newunit\newblock
```

```
1418 \usebibmacro{addendum+pubstate}%
1419 \newblock
1420 \iftoggle{bbx:related}{%
1421   {\ifdefstring{\bbx@relatedformat}{semicolon}{%
1422     {\setunit{\addsemicolon\space}}%
1423     {\setunit{\unspace\space}}%horrible trick
1424   \usebibmacro{related:init}%
1425   \usebibmacro{related}{}%
1426   {}%
1427 }%
1428 \newunit\newblock
1429 \usebibmacro{pageref}%
1430 \usebibmacro{finentry}%
1431 \DeclareBibliographyDriver{set}{%
1432   \protect\PackageWarningNoLine{biblatex-philosophy}{%
1433     \MessageBreak
1434     Entry type @set is not supported\MessageBreak
1435     by the 'biblatex-philosophy' styles.\MessageBreak
1436     All the @set entries will be ignored}%
1437 %
1438 % ripristina ordine nome cognome nelle voci inbook:full
1439 \renewbibmacro*{bybookauthor}{%
1440   \ifnamesequal{author}{bookauthor}{%
1441     {}%
1442     {\printnames[default]{bookauthor}}}%
1443 %
1444 \newbibmacro*{cross:maintitle+booktitle}{%
1445   \iffieldundef{volume}{%
1446     {}%
1447     {\printfield{volume}}%
1448     {\printfield{part}}%
1449     {\setunit{\addcolon\space}}%
1450     {\printfield{booktitle}}}}%
1451 %
1452 \newbibmacro*{xrefdata}{%
1453   \usebibmacro{cross:maintitle+booktitle}%
1454   \newunit\newblock
1455   \usebibmacro{byeditor+others}%
1456   \newunit\newblock
1457   \printfield{edition}%
1458 %
1459   \newunit
1460   \iffieldundef{maintitle}{%
1461     {\printfield{volume}}%
1462     {\printfield{part}}%
1463     {}%
1464   \newunit
1465   \printfield{volumes}%
1466   \newunit\newblock
1467   \usebibmacro{series+number}%
1468   \newunit\newblock
1469   \printfield{note}%
1470   \newunit\newblock
```

```

1470 \usebibmacro{publisher+location+date}%
1471 \newunit\newblock
1472 \usebibmacro{chapter+pages}%
1473 \newunit\newblock
1474 \iftoggle{bbx:isbn}
1475   {\printfield{isbn}}
1476   {}%
1477 \newunit\newblock
1478 \usebibmacro{doi+eprint+url}%
1479 \newunit\newblock
1480 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
1481 \newblock
1482 \iftoggle{bbx:related}
1483   {\ifdefstring{\bbx@relatedformat}{semicolon}%
1484    {\setunit{\addsemicolon\space}}%
1485    {\setunit{\unspace\space}}%horrible trick
1486    \usebibmacro{related:init}%
1487    \usebibmacro{related}%
1488    {}%
1489 \newunit\newblock
1490 \usebibmacro{pageref}%
1491 \usebibmacro{finentry}%
1492 \newbibmacro*[crossrefdata]{%
1493   \iffieldundef{maintitle}
1494     {\printfield{volume}%
1495      \printfield{part}}
1496     {}%
1497   \newunit\newblock
1498   \usebibmacro{chapter+pages}%
1499   \newunit\newblock
1500   \iftoggle{bbx:isbn}
1501     {\printfield{isbn}}
1502     {}%
1503   \newunit\newblock
1504   \usebibmacro{doi+eprint+url}%
1505   \newblock
1506   \iftoggle{bbx:related}
1507     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1508      {\setunit{\addsemicolon\space}}%
1509      {\setunit{\unspace\space}}%horrible trick
1510      \usebibmacro{related:init}%
1511      \usebibmacro{related}%
1512      {}%
1513   \newunit\newblock
1514   \usebibmacro{pageref}%
1515   \usebibmacro{finentry}%

```

Experimental drivers for jurisprudence This feature is available for now only for Italian documents.

```

1517 \%DeclareFieldFormat[jurisprudence]{title}{#1}
1518 \%DeclareFieldFormat[jurisprudence]{pages}{#1}

```

```

1519 \%ExecuteBibliographyOptions[jurisprudence]{skipbib=true}%
1520 \DeclareFieldFormat[jurisdiction]{volume}{\RN{\#1}}
1521 \DeclareFieldFormat[jurisdiction]{number}{\bibsstring{number}^{\#1}}
1522 \DeclareFieldFormat[jurisdiction]{nameaddon}{%
1523   \ifinteger{\#1}{\bibcpsstring{section}^{\RN{\#1}}{\#1}}}
1524 \DeclareFieldFormat[jurisdiction]{pages}{%
1525   \iffieldundef{bookpagination}{\mkpageprefix[bookpagination]{\#1}}}
1526 \DeclareFieldFormat[jurisdiction]{title}{%
1527   \iffieldequalstr{entrysubtype}{international}{\emph{\#1}}{\#1}}
1528 \DeclareFieldFormat[jurisdiction]{notacomm}{\nt\adddotspace{\#1}}

```

A new macro to manage authors of @jurisdiction entries.

```
1529 \newbibmacro*[juris:author]{%
```

Use the default name format: “name surname”

```

1530 \DeclareNameAlias{sortname}{default}%
1531   \ifboolexpr{%
1532     test \ifuseauthor
1533     and
1534     not test {\ifnameundef{author}}}
1535   }%
1536   {%
1537     \iffieldequalstr{type}{conclusions}{%
1538       \printtext{Conclusioni dell'Avv\adddotspace generale}%
1539       \setunit{\addspace}}{%
1540       \printnames{author}%
1541         \iffieldundef{authortype}{%
1542           {}%
1543           {\setunit{\addcomma\space}}%
1544           \usebibmacro{authorstrg}}{%
1545             {}%
1546             \iffieldequalstr{type}{conclusions}{%
1547               \setunit{\addspace}}{%
1548                 \printtext{presentate il}%
1549                 \setunit{\addspace}}{%
1550               }{%
1551                 \setunit{\addcomma\space}}%
1552               \iffieldundef{nameaddon}{%
1553                 \printtext{\printfield{nameaddon}}%
1554                 \setunit{\addcomma\space}}{%
1555                   }{%
1556                     \printeventdate}%
1557               }%
1558             \newbibmacro*[addendum+pubstate:juris]{%
1559               \printfield{usera}{notacomm}%
1560               \newunit\newblock
1561               \printfield{addendum}%
1562               \newunit\newblock
1563               \printfield{pubstate}%
1564               \ifdefstring{\bbx@origfields}{none}{}{%
1565                 \newunit\newblock
1566                 \usebibmacro{origdata:article-inbook}}%
1567                 \newunit\newblock

```

```
1568 \usebibmacro{library}%
1569
1570 \DeclareBibliographyDriver{jurisdiction}{%
1571   \usebibmacro{bibindex}%
1572   \usebibmacro{begentry}%
1573   \usebibmacro{juris:author}%
1574   \setunit{\labelnamepunct}\newblock
1575   \usebibmacro{title}%
1576   \newunit\newblock
1577   \usebibmacro{series+number}%
1578   \printlist{language}%
1579   \newunit\newblock
1580   \usebibmacro{byauthor}%
1581   \newunit\newblock
1582   \iffieldundef{booktitle}{}{%
1583     \usebibmacro{in:}%
1584     \usebibmacro{maintitle+booktitle}%
1585     \newunit\newblock
1586   \printtext{%
1587     \printfield{labelyear}%
1588     \printfield{extrayear}%
1589     \usebibmacro{byeditor+others}%
1590     \newunit\newblock
1591     \printfield{edition}%
1592     \newunit
1593     \iffieldundef{maintitle}%
1594       {\printfield{volume}%
1595        \printfield{part}}%
1596     {}%
1597   \newunit
1598   \printfield{volumes}%
1599   \newunit\newblock
1600   \printfield{note}%
1601   \newunit\newblock
1602   \usebibmacro{publisher+location+date}%
1603   \newunit\newblock
1604   \usebibmacro{chapter+pages}%
1605   \newunit\newblock
1606   \iftoggle{bbx:isbn}%
1607     {\printfield{isbn}}%
1608   {}%
1609   \newunit\newblock
1610   \usebibmacro{doi+eprint+url}%
1611   \newunit\newblock
1612   \usebibmacro{addendum+pubstate:juris}%
1613   \newblock
1614   \iftoggle{bbx:related}%
1615     {\ifdefstring{\bbx@relatedformat}{semicolon}%
1616       {\setunit{\addsemicolon\space}}%
1617       {\setunit{\unspace\space}}%horrible trick
1618     \usebibmacro{related:init}%
1619     \usebibmacro{related}}%
```

```

1620      {}%
1621      \newunit\newblock
1622      \usebibmacro{pageref}%
1623      \usebibmacro{finentry}%
Define new fields for @jurisdiction entry types and orig- fields mechanism:
1624 \DeclareStyleSource{map{
1625 \maps[datatype=bibtex]{
1626     \map{
1627         \step[fieldsource=court      , fieldtarget=author]
1628         \step[fieldsource=notacomm   , fieldtarget=usera]
1629         \step[fieldsource=section    , fieldtarget=nameaddon]
1630         \step[fieldsource=transdate  , fieldtarget=origdate]
1631         \step[fieldsource=transtitle , fieldtarget=origtitle]
1632         \step[fieldsource=tranpublisher, fieldtarget=origpublisher]
1633         \step[fieldsource=translocation, fieldtarget=origlocation]
1634         \step[fieldsource=transbooktitle, fieldtarget=usera]
1635         \step[fieldsource=transnote   , fieldtarget=userb]
1636         \step[fieldsource=transpages  , fieldtarget=userc]
1637         \step[fieldsource=origbooktitle, fieldtarget=usera]
1638         \step[fieldsource=orignote   , fieldtarget=userb]
1639         \step[fieldsource=origpages  , fieldtarget=userc]
1640     }
1641 }
1642 }
1643 \DeclareDataInheritance{}{*}{\noinherit{annotation}}
1644
1645 \DeclareFieldAlias{jurisdiction}{usera}[jurisdiction]{notacomm}
1646 \DeclareFieldAlias{jurisdiction}{nameaddon}[jurisdiction]{section}
1647 \DeclareFieldAlias{jurisdiction}{author}[jurisdiction]{court}
1648

```

7.2 philosophy-classic.bbx

7.2.1 Initial settings

```

1649 \RequireBibliographyStyle{authoryear}
1650 \RequireBibliographyStyle{philosophy-standard}
1651
1652 \newtoggle{bbx:square}
1653 \newtoggle{bbx:nodate}
1654
1655 \DeclareBibliographyOption{square}[true]{%
1656     \settoggle{bbx:square}{#1}}
1657 \DeclareBibliographyOption{nodate}[true]{%
1658     \settoggle{bbx:nodate}{#1}}
1659
1660 \ExecuteBibliographyOptions{%
1661     nodate      = true,
1662     uniquename  = false,
1663     pagetracker = true,
1664     singletitle = false,
1665     square      = false,

```

```
1666 mergedate = basic,
1667 dashed = true,
1668 }
```

The classic and modern styles redefine the `relateddate` and `commarelateddate` macros because the date have to be printed after the name of the author/editor. In the list of shorthands we need a standard entry, with the date at the end and no date after the name of the author/editor so we overwrite these macros locally:

```
1669 \AtBeginShorthands{%
1670 \togglefalse{bbx:annotation}%
1671 \renewcommand{\labelnamepunct}{\addcomma\space}%
1672 \renewbibmacro*[relateddate]{%
1673   \setunit*{\addspace}%
1674   \printdate}%
1675 \renewbibmacro*[commarelateddate]{%
1676   \setunit*{\addcomma\space}%
1677   \printdate}%
1678 \DeclareCiteCommand{\bbx@crossref@inbook}%
1679   {}%
1680   {\iffieldundef{shorthand}{%
1681     \usebibmacro{citeindex}%
1682     \ifuseeditor{%
1683       \ifthenelse{\value{listtotal}=2}{%
1684         {\printnames[][-\value{maxnamesincross}]\labelname}%
1685         {\printnames[][-\value{minnamesincross}]\labelname}%
1686         {\usebibmacro{labeltitle}}%
1687       \setunit*{\addspace}%
1688       \usebibmacro{date+extrayear:crossref}%
1689       {\usebibmacro{cite:shorthand}}}%
1690     {}%
1691     {}%
1692   \DeclareCiteCommand{\bbx@crossref@incollection}%
1693     {}%
1694     {\iffieldundef{shorthand}{%
1695       \usebibmacro{citeindex}%
1696       \ifuseeditor{%
1697         \ifthenelse{\value{listtotal}=2}{%
1698           {\printnames[][-\value{maxnamesincross}]\labelname}%
1699           {\printnames[][-\value{minnamesincross}]\labelname}%
1700           {\usebibmacro{labeltitle}}%
1701         \setunit*{\addspace}%
1702         \usebibmacro{date+extrayear:crossref}%
1703         {\usebibmacro{cite:shorthand}}}%
1704       {}%
1705       {}%
1706     \newbibmacro*[date+extrayear:crossref]{%
1707       \begingroup%
1708         \clearfield{month}%
1709         \clearfield{day}%
1710       \ifboolexpr{%
1711         test {\iffieldundef{date}}%
1712         and
```

```

1713     test {\iffieldundef{year}}
1714   }%
1715     {\iftoggle{bbx:nodate}{\printtext[parens]{%
1716       \midsentence\bibstring{nodate}}}{}}%
1717     {\printtext[parens]{\printdateextra}}%
1718   \endgroup}%
1719 \newbibmacro*[date+extrayear}{}
1720 % for article entries:
1721 \renewbibmacro*[date]{\printdate}%
1722 \renewbibmacro*[issue+date]{%
1723   \printtext[pureparens]{%
1724     \iffieldundef{issue}%
1725       {\usebibmacro{date}}%
1726       {\printfield{issue}}%
1727         \setunit{\addspace}%
1728         \usebibmacro{date}}}}%
1729 \newunit
1730 }%
1731 \AtBeginDocument{%
1732   \iftoggle{bbx:square}{%
1733     {\renewcommand{\bibopenparen}{\bibopenbracket}%
1734      \renewcommand{\bibcloseparen}{\bibclosebracket}}{}%
1735   }%
1736   \setcounter{maxnamesincross}{\value{maxnames}}%
1737   \setcounter{minnamesincross}{\value{minnames}}%
1738 }%
1739 }%
1740 \AtEveryBibitem{%
1741   \iffieldequalstr{entrysubtype}{classic}{%
1742     \togglefalse{bbx:nodate}}}%
1743 }%
1744

```

7.2.2 New macros

Renew the bibliography macro 'relateddate' to delete the date at the end of the entry:

```

1745 \renewbibmacro*[relateddate]{}
1746 \renewbibmacro*[commarelateddate]{}

```

Dates

```

1747   \renewbibmacro*[issue+date]{%
1748     \ifboolexpr{%
1749       test {\iffieldundef{issue}}%
1750       and%
1751       test {\iffieldundef{month}}%
1752     }%
1753       {}%
1754       {\ifdefstring{\bbx@volnumformat}{parens}{%
1755         \printtext{%
1756           \printfield{issue}\setunit{\addspace}%
1757           \printdate}}{}}%
1758     \printtext[pureparens]{%

```

```

1759      \printfield{issue}\setunit*{\addspace}%
1760      \printdate}}}}%
1761      \newunit}%

```

Delete “month” from \printdateextra to print open ranges such as: “1968-”:

```

1762 \renewbibmacro*{date+extrayear}{%
1763     \begingroup%
1764         \clearfield{month}%
1765         \clearfield{day}%
1766     \ifboolexpr{%
1767         test {\iffieldundef{date}}
1768         and
1769         test {\iffieldundef{year}}
1770     }{%
1771         {\iftoggle{bbx:nodate}{\printtext[parens]{%
1772             \midsentence\bibstring{nodate}}}{}}%
1773         {\printtext[parens]{\printdateextra}}%
1774     }\endgroup}%

```

Authors and editors

```

1775 \renewbibmacro*{author}{%
1776     \ifboolexpr{%
1777         test \ifuseauthor
1778         and
1779         not test {\ifnameundef{author}}}
1780     }{%
1781         {\usebibmacro{bbx:dashcheck}%
1782             {\bibnamedash}%
1783             {\usebibmacro{bbx:savehash}%
1784                 \printnames{author}%
1785                 \iffieldundef{nameaddon}{%
1786                     {\setunit{\addspace}%
1787                         \printtext[brackets]{\printfield{nameaddon}}}}%
1788                 \iffieldundef{authortype}{%
1789                     {\setunit{\addspace}}%
1790                     {\setunit{\addcomma\space}}%
1791                     \iffieldundef{authortype}{%
1792                         {}%
1793                         {\usebibmacro{authorstrg}}%
1794                     \setunit{\addspace}}%
1795                     {\global\undef\bbx@lasthash}%
1796                     \usebibmacro{labeltitle}%
1797                     \setunit*{\addspace}}%
1798                 \usebibmacro{date+extrayear}}}}%
1799 \renewbibmacro*{editor}{%
1800     \usebibmacro{bbx:editor}{editorstrg}}%
1801 \renewbibmacro*{editor+others}{%
1802     \usebibmacro{bbx:editor}{editor+othersstrg}}%
1803 \renewbibmacro*{bbx:editor}[1]{%
1804     \ifboolexpr{%
1805         test \ifuseeditor

```

```

1807     and
1808     not test {\ifnameundef{editor}}
1809 }%
1810     {\usebibmacro{bbx:dashcheck}%
1811      {\bibnamedash}%
1812      {\printnames{editor}}%
1813 \setunit{\addspace}%
1814 \usebibmacro{bbx:savehash}%
1815     \usebibmacro{\#1}%
1816     \clearname{editor}%
1817     \setunit{\addspace}%
1818     {\global\edef\bbx@lasthash{%
1819       \usebibmacro{labeltitle}%
1820     \setunit*{\addspace}%
1821     \usebibmacro{date+extrayear}}}%

```

7.2.3 Internal commands for crossreferences

```

1822 \DeclareCiteCommand{\bbx@crossref@inbook}%
1823 {}%
1824 {\usebibmacro{citeindex}%
1825 \ifuseeditor{%
1826   \ifthenelse{\value{listtotal}=2}{%
1827     {\printnames[][-\value{maxnamesincross}]{\labelname}}%
1828     {\printnames[][-\value{minnamesincross}]{\labelname}}%
1829     {\usebibmacro{labeltitle}}%
1830   \setunit*{\addspace}%
1831   \usebibmacro{date+extrayear}}}%
1832 {}%
1833 {}%
1834
1835 \DeclareCiteCommand{\bbx@crossref@incollection}%
1836 {}%
1837 {\usebibmacro{citeindex}%
1838 \ifuseeditor{%
1839   \ifthenelse{\value{listtotal}=2}{%
1840     {\printnames[][-\value{maxnamesincross}]{\labelname}}%
1841     {\printnames[][-\value{minnamesincross}]{\labelname}}%
1842     {\usebibmacro{labeltitle}}%
1843   \setunit*{\addspace}%
1844   \usebibmacro{date+extrayear}}}%
1845 {}%
1846 {}%

```

The `restoreclassic` option is redundant for the philosophy-classic style. Anyway it is defined to avoid error messages:

```

1847 \define@key{blx@bib1}{restoreclassic}{}{}%
1848 \define@key{blx@bib2}{restoreclassic}[true]{}%

```

7.2.4 The `nodate` option for `\printbibliography`

```

1849 \define@key{blx@bib1}{nodate}{}{}%
1850 \define@key{blx@bib2}{nodate}[true]{}%

```

```
1851 \ifstrequal{#1}{false}{%
1852   \togglefalse{bbx:nodate}%
1853 }{}}%
```

7.3 philosophy-modern.bbx

7.3.1 Initial settings

```
1854 \RequireBibliographyStyle{philosophy-classic}
```

The modern style has only one specific option which is turned off by default:

```
1855 \newtoggle{bbx:yearleft}%
1856 \DeclareBibliographyOption{yearleft}[true]{%
1857   \settoggle{bbx:yearleft}{#1}%
1858 \ExecuteBibliographyOptions{%
1859   yearleft=false}}
```

7.3.2 New lengths

```
1860 \newlength{\yeartitle}%
1861 \newlength{\postnamesep}%
1862 \setlength{\yeartitle}{0.8em}%
1863 \setlength{\postnamesep}{0.5ex plus 2pt minus 1pt}%
1864 \setlength{\bibitemsep}{\postnamesep}%
1865 \setlength{\bibnamesep}{1.5ex plus 2pt minus 1pt}%
1866 \setlength{\bibhang}{4\parindent}%
1867 %
1868 \AtBeginBibliography{%
1869   \iftoggle{bbx:yearleft}{%
1870     \setlength{\yeartitle}{\fill}%
1871   }{}}%
```

7.3.3 New commands

```
1872 \newcommand{\postsep}{\par\nobreak\vskip\postnamesep%
1873   \hskip-\bibhang\ignorespaces}%
1874 \renewcommand{\labelnamepunct}{}
1875 %
1876 \AtBeginShorthands{%
1877 \renewcommand{\postsep}{\addspace}%
1878 \renewcommand{\labelnamepunct}{\newunitpunct}}}
```

7.3.4 New macros

Dates

```
1879 \renewbibmacro*[date+extrayear]{%
1880   \begingroup%
1881   \clearfield{month}%
1882   \clearfield{day}%
1883   \makebox[\bibhang][r]{\printtext{%
1884     \ifboolexpr{%
1885       test {\iffieldundef{date}}%
1886       and%
1887       test {\iffieldundef{year}}%
1888     }{%
1889       \iftoggle{bbx:nodate}{\printtext{%
```

```

1890      \midsentence\bibstring{nodate}{}{}%
1891      {\printtext{\printdateextra}}%
1892      \hskip\yeartitle}%
1893      \endgroup}%
1894
1895 \renewbibmacro*{labeltitle}{%
1896     \iffieldundef{label}%
1897     {\iffieldundef{shorttitle}%
1898      {\printfield{title}\clearfield{title}}%
1899      {\printfield[title]{shorttitle}}}}%
1900     {\printtext{\printfield{label}}}%
1901 \postsep}%

```

Authors and editors

```

1902 \renewbibmacro*{author}{%
1903     \ifboolexpr{%
1904         test \ifuseauthor
1905         and
1906         not test {\ifnameundef{author}}}
1907     }%
1908     {\usebibmacro{bbx:dashcheck}%
1909         {}%
1910         {\usebibmacro{bbx:savehash}%
1911             \printnames{author}%
1912             \iffieldundef{nameaddon}{}%
1913             {\setunit{\addspace}%
1914                 \printtext[brackets]{\printfield{nameaddon}}%
1915                 \iffieldundef{authortype}%
1916                 {}%
1917                 {\setunit{\addcomma\space}}%
1918                 \usebibmacro{authorstrg}%
1919             \postsep}%
1920             {\global\undef\bbx@lasthash%
1921                 \usebibmacro{labeltitle}%
1922                 \setunit*\addspace}%
1923             \usebibmacro{date+extrayear}}%
1924
1925 \renewbibmacro*{editor}{%
1926     \usebibmacro{bbx:editor}{editorstrg}}%
1927 \renewbibmacro*{editor+others}{%
1928     \usebibmacro{bbx:editor}{editor+othersstrg}}%
1929 \renewbibmacro*{bbx:editor}[1]{%
1930     \ifboolexpr{%
1931         test \ifuseeditor
1932         and
1933         not test {\ifnameundef{editor}}}
1934     }%
1935     {\usebibmacro{bbx:dashcheck}%
1936         {}%
1937         {\printnames{editor}}%
1938     \postsep%ADD

```

```

1939  \usebibmacro{bbx:savehash}}}}%
1940  {\global\undef\bbx@lasthash%
1941  \usebibmacro{labeltitle}}}}%
1942 \usebibmacro{date+extrayear}}}}%
1943  \iffieldundef{label}{%
1944  {\usebibmacro{#1}}%
1945  \clearname{editor}}%
1946  \printtext{\addcomma\space}}}}}}%

```

7.3.5 Internal commands for crossreferences

```

1947 \DeclareCiteCommand{\bbx@crossref@inbook}}%
1948  {}%
1949  {\usebibmacro{citeindex}}%
1950  \ifuseeditor{%
1951  \ifthenelse{\value{listtotal}=2}{%
1952  {\printnames[][-\value{maxnamesincross}]{labelname}}}}%
1953  {\printnames[][-\value{minnamesincross}]{labelname}}}}}}%
1954  \usebibmacro{labeltitle}}}}%
1955  \setunit*{\addspace}}%
1956  \usebibmacro{classic:date+extrayear}}}}%
1957  {}%
1958  {}%
1959
1960 \DeclareCiteCommand{\bbx@crossref@incollection}}%
1961  {}%
1962  {\usebibmacro{citeindex}}%
1963  \ifuseeditor{%
1964  \ifthenelse{\value{listtotal}=2}{%
1965  {\printnames[][-\value{maxnamesincross}]{labelname}}}}%
1966  {\printnames[][-\value{minnamesincross}]{labelname}}}}}}%
1967  \usebibmacro{labeltitle}}}}%
1968  \setunit*{\addspace}}%
1969  \usebibmacro{classic:date+extrayear}}}}%
1970  {}%
1971  {}%
1972
1973 \newbibmacro*{classic:date+extrayear}}{%
1974  \begingroup%
1975  \clearfield{month}}%
1976  \clearfield{day}}%
1977  \ifboolexpr{%
1978  \test{\iffieldundef{date}}%
1979  \and%
1980  \test{\iffieldundef{year}}%
1981 }%
1982  {\iftoggle{bbx:nodate}{\printtext[parens]}{%
1983  \midsentence\bibstring{nodate}}}}}}}}%
1984  {\printtext[parens]}%
1985  \printfield{labelyear}}}}%
1986  \printfield{extrayear}}}}}}%
1987  \endgroup}}%

```

7.3.6 The restoreclassic option

```

1988 \define@key{blx@bib1}{restoreclassic}{}{}%
1989 \define@key{blx@bib2}{restoreclassic}[true]{%
1990   \ifstreq{\#1}{true}{%
1991     \setlength{\bibhang}{\parindent}%
1992     \renewcommand{\labelnamepunct}{\newunitpunct}%
1993 \renewbibmacro*{date+extrayear}{%
1994   \begingroup%
1995     \clearfield{month}%
1996     \clearfield{day}%
1997   \ifboolexpr{%
1998     test {\iffieldundef{date}}%
1999     and%
2000     test {\iffieldundef{year}}%
2001   }%
2002   {\iftoggle{bbx:nodate}{\printtext[parens]{%
2003     \midsentence\bibstring{nodate}\}}{\}}%
2004   {\printtext[parens]{\printdateextra}}%
2005   \endgroup}%
2006 \renewbibmacro*{author}{%
2007   \ifboolexpr{%
2008     test \ifuseauthor
2009     and%
2010     not test {\ifnameundef{author}}%
2011   }%
2012   {\usebibmacro{bbx:dashcheck}%
2013     {\bibnamedash}%
2014     {\usebibmacro{bbx:savehash}%
2015       \printnames{author}%
2016       \iffieldundef{nameaddon}{%
2017         \setunit{\addspace}%
2018         \printtext[brackets]{\printfield{nameaddon}}}}%
2019 \iffieldundef{authortype}{%
2020   {\setunit{\addspace}}%
2021   {\setunit{\addcomma\space}}}}%
2022   \iffieldundef{authortype}{%
2023     {}%
2024     {\usebibmacro{authorstrg}}%
2025 \setunit{\addspace}}}}%
2026   {\global\undef\bbx@lasthash}%
2027   \usebibmacro{labeltitle}%
2028   \setunit{\addspace}}%
2029   \usebibmacro{date+extrayear}}%
2030 \renewbibmacro*{editor}{%
2031   \usebibmacro{bbx:editor}{editorstrg}}%
2032 \renewbibmacro*{editor+others}{%
2033   \usebibmacro{bbx:editor}{editor+othersstrg}}%
2034 \renewbibmacro*{bbx:editor}[1]{%
2035   \ifboolexpr{%
2036     test \ifuseeditor
2037     and%

```

```

2038     not test {\ifnameundef{editor}}
2039   }%
2040   {\usebibmacro{bbx: dashcheck}%
2041     {\bibnamedash}%
2042     {\printnames{editor}}%
2043 \setunit{\addspace}%
2044 \usebibmacro{bbx: savehash}%
2045   \usebibmacro{#1}%
2046   \clearname{editor}%
2047   \setunit{\addspace}%
2048   {\global\undef\bbx@lasthash%
2049     \usebibmacro{labeltitle}%
2050     \setunit*{\addspace}%
2051   \usebibmacro{date+extrayear}%
2052 \renewbibmacro*{labeltitle}{%
2053   \iffieldundef{label}%
2054     {\iffieldundef{shorttitle}%
2055       {\printfield{title}%
2056         \clearfield{title}}%
2057       {\printfield[title]{shorttitle}}%
2058     {\printfield{label}}}%
2059   }{}%
2059 }{}%

```

7.4 philosophy-verbose.bbx

7.4.1 Initial settings

```

2060 \RequireBibliographyStyle{authortitle}
2061 \RequireBibliographyStyle{philosophy-standard}
2062
2063 \DeclareFieldFormat{edition}{%
2064   \ifinteger{#1}{%
2065     \ifdefstring{\bbx@editionformat}{arabic}%
2066       {\mkbibordition{#1}\~\bibstring{edition}}%
2067     \ifdefstring{\bbx@editionformat}{Roman}%
2068       {\RN{#1}\~\bibstring{edition}}%
2069     \ifdefstring{\bbx@editionformat}{romansc}%
2070       {\textsc{\Rn{#1}}\~\bibstring{edition}}%
2071     \ifdefstring{\bbx@editionformat}{roman}%
2072       {\Rn{#1}\~\bibstring{edition}}%
2073     \ifdefstring{\bbx@editionformat}{superscript}%
2074       {\mkbibsuperscript{#1}}%
2075     {\optionerror{editionformat}}}}}}{#1}\isdot??
2076
2077 \AtBeginShorthands{%

```

The annotation field is omitted in the list of shorthands:

```
2078 \togglefalse{bbx:annotation}%

```

In the list of shorthands we always use the shorthand for the cross-referenced entries:

```

2079 \DeclareCiteCommand{\bbx@crossref@inbook}%
2080 {}%
2081 {\iffieldundef{shorthand}%
2082   {\usebibmacro{inbook:full}}%
```

```

2083     {\usebibmacro{cite:shorthand}}%
2084     {}%
2085     {}%
2086 \DeclareCiteCommand{\bbx@crossref@incollection}%
2087   {}%
2088   {\iffieldundef{shorthand}%
2089     {\usebibmacro{incollection:full}}%
2090     {\usebibmacro{cite:shorthand}}%
2091   {}%
2092   {}%
2093 }
```

Authors and editors

```

2094 \renewbibmacro*{author}{%
2095   \ifboolexpr{%
2096     test \ifuseauthor
2097     and
2098     not test {\ifnameundef{author}}}
2099 }%
2100   {\usebibmacro{bbx:dashcheck}}%
2101     {\bibnamedash}%
2102     {\printnames{author}}%
2103     \iffieldundef{nameaddon}{}%
2104     {\setunit{\addspace}}%
2105     \printtext[brackets]{\printfield{nameaddon}}%
2106 \setunit{\addcomma\space}%
2107 \usebibmacro{bbx:savehash}}%
2108   {\usebibmacro{authorstrg}}%
2109   {\global\undef\bbx@lasthash}}%
2110
2111 \renewbibmacro*{editor}{%
2112   \usebibmacro{bbx:editor}{editorstrg}}%
2113 \renewbibmacro*{editor+others}{%
2114   \usebibmacro{bbx:editor}{editor+othersstrg}}%
2115 \renewbibmacro*{bbx:editor}[1]{%
2116   \ifboolexpr{%
2117     test \ifuseeditor
2118     and
2119     not test {\ifnameundef{editor}}}
2120 }%
2121   {\usebibmacro{bbx:dashcheck}}%
2122     {\bibnamedash}%
2123     {\printnames{editor}}%
2124 \setunit{\addspace} #MOD#
2125   {\usebibmacro{bbx:savehash}}%
2126   {\usebibmacro{#1}}%
2127   {\clearname{editor}}%
2128   {\global\undef\bbx@lasthash}}%
```

7.4.2 Internal commands for crossreferences

```

2129 \newbibmacro*{nodash:author}{%
```

```
2130 \ifboolexpr{%
2131   test \ifuseauthor
2132   and
2133   not test {\ifnameundef{author}}
2134 }%
2135   {\printnames{author}%
2136     \iffieldundefined{nameaddon}{}%
2137     {\setunit{\addspace}%
2138      \printtext[brackets]{\printfield{nameaddon}}%
2139 \setunit{\addcomma\space}%
2140     \usebibmacro{authorstrg}%
2141     {\global\edef\bbx@lasthash}%
2142
2143 \newbibmacro*[nodash:editor+others]{%
2144   \usebibmacro{nodash:bbx:editor}{editor+othersstrg}%
2145 \newbibmacro*[nodash:bbx:editor][1]{%
2146   \ifboolexpr{%
2147     test \ifuseeditor
2148     and
2149     not test {\ifnameundef{editor}}
2150   }%
2151   {\printnames{editor}%
2152 \setunit{\addspace}%
2153   \usebibmacro{#1}%
2154   \clearname{editor}%
2155   {\global\edef\bbx@lasthash}%
2156
2157 \newbibmacro*[nodash:author/editor+others/translator+others]{%
2158   \ifboolexpr{
2159     test \ifuseauthor
2160     and
2161     not test {\ifnameundef{author}}
2162   }%
2163   {\usebibmacro{nodash:author}%
2164   \ifboolexpr{
2165     test \ifuseeditor
2166     and
2167     not test {\ifnameundef{editor}}
2168   }%
2169   {\usebibmacro{nodash:editor+others}%
2170   {\usebibmacro{translator+others}}}%
2171
2172 \renewbibmacro*[relateddate]{%
2173   \setunit*{\addspace}%
2174   \printdate\ifdefstring{\bbx@editionformat}{superscript}{\printfield{edition}}{}%
2175 \renewbibmacro*[commarelateddate]{%
2176   \setunit*{\addcomma\space}%
2177   \printdate\ifdefstring{\bbx@editionformat}{superscript}{\printfield{edition}}{}%
2178
2179 \DeclareBibliographyDriver{book}{%
2180   \usebibmacro{bibindex}%
2181   \usebibmacro{begentry}%
2182 }
```

```
2182 \usebibmacro{author+editor+others+translator+others}%
2183 \setunit{\labelnamepunct}\newblock
2184 \usebibmacro{maintitle+title}%
2185 \newunit
2186 \printlist{language}%
2187 \newunit\newblock
2188 \usebibmacro{byauthor}%
2189 \newunit\newblock
2190 \usebibmacro{byeditor+others}%
2191 \newunit\newblock
2192 \ifdefstring{\bbx@editionformat}{superscript}{}%
2193 {\printfield{edition}%
2194 \newunit}%
2195 \printfield{volumes}%
2196 \newunit\newblock
2197 \usebibmacro{series+number}%
2198 \newunit\newblock
2199 \printfield{note}%
2200 \newunit\newblock
2201 \usebibmacro{publisher+location+date}%
2202 \newunit
2203 \iffieldundef{maintitle}%
2204 {\printfield{volume}%
2205 \printfield{part}%
2206 {}}%
2207 \newunit\newblock
2208 \usebibmacro{chapter+pages}%
2209 \newunit
2210 \printfield{pagetotal}%
2211 \newunit\newblock
2212 \iftoggle{bbx:isbn}%
2213 {\printfield{isbn}%
2214 {}}%
2215 \newunit\newblock
2216 \usebibmacro{doi+eprint+url}%
2217 \newunit\newblock
2218 \usebibmacro{addendum+pubstate}%
2219 \newblock
2220 \iftoggle{bbx:related}%
2221 {\ifdefstring{\bbx@relatedformat}{semicolon}%
2222 {\setunit{\addsemicolon\space}}%
2223 {\setunit{\unspace\space}}%\horrible trick
2224 \usebibmacro{related:init}%
2225 \usebibmacro{related}{}%
2226 {}}%
2227 \newunit\newblock
2228 \usebibmacro{pageref}%
2229 \usebibmacro{finentry}%
2230
2231 \DeclareBibliographyDriver{collection}{%
2232 \usebibmacro{bibindex}%
2233 \usebibmacro{begentry}%

```

```
2234 \usebibmacro{editor+others}%
2235 \setunit{\labelnamepunct}\newblock
2236 \usebibmacro{maintitle+title}%
2237 \newunit
2238 \printlist{language}%
2239 \newunit\newblock
2240 \usebibmacro{byeditor+others}%
2241 \newunit\newblock
2242 \ifdefstring{\bbx@editionformat}{superscript}{}%
2243 {\printfield{edition}%
2244 \newunit}%
2245 \iffieldundef{maintitle}%
2246 {\printfield{volume}%
2247 \printfield{part}%
2248 {}%
2249 \newunit
2250 \printfield{volumes}%
2251 \newunit\newblock
2252 \usebibmacro{series+number}%
2253 \newunit\newblock
2254 \printfield{note}%
2255 \newunit\newblock
2256 \usebibmacro{publisher+location+date}%
2257 \newunit\newblock
2258 \usebibmacro{chapter+pages}%
2259 \newunit
2260 \printfield{pagetotal}%
2261 \newunit\newblock
2262 \iftoggle{bbx:isbn}%
2263 {\printfield{isbn}%
2264 {}%
2265 \newunit\newblock
2266 \usebibmacro{doi+eprint+url}%
2267 \newunit\newblock
2268 \usebibmacro{addendum+pubstate}%
2269 \newblock
2270 \iftoggle{bbx:related}%
2271 {\ifdefstring{\bbx@relatedformat}{semicolon}%
2272 {\setunit{\addsemicolon\space}}%
2273 {\setunit{\unspace\space}}%horrible trick
2274 \usebibmacro{related:init}%
2275 \usebibmacro{related}{}%
2276 {}%
2277 \newunit\newblock
2278 \usebibmacro{pageref}%
2279 \usebibmacro{finentry}%
2280
2281 \renewbibmacro*[inbook:full]{%
2282 \usebibmacro{bybookauthor}%
2283 \newunit\newblock
2284 \usebibmacro{maintitle+booktitle}%
2285 \newunit\newblock
```

```
2286 \usebibmacro{byeditor+others}%
2287 \newunit\newblock
2288 \ifdefstring{\bbx@editionformat}{superscript}{}%
2289 {\printfield{edition}%
2290 \newunit}%
2291 \printfield{volumes}%
2292 \newunit\newblock
2293 \usebibmacro{series+number}%
2294 \newunit\newblock
2295 \printfield{note}%
2296 \newunit\newblock
2297 \usebibmacro{publisher+location+date}%
2298 \newunit
2299 \iffieldundef{maintitle}%
2300 {\printfield{volume}%
2301 \printfield{part}%
2302 }%
2303 \newunit\newblock
2304 \usebibmacro{chapter+pages}%
2305 \newunit\newblock
2306 \iftoggle{bbx:isbn}%
2307 {\printfield{isbn}%
2308 }%
2309 \newunit\newblock
2310 \usebibmacro{doi+eprint+url}%
2311 \newunit\newblock
2312 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
2313 \newblock
2314 \iftoggle{bbx:related}%
2315 {\ifdefstring{\bbx@relatedformat}{semicolon}%
2316 {\setunit{\addsemicolon\space}}%
2317 {\setunit{\unspace\space}}%horrible trick
2318 \usebibmacro{related:init}%
2319 \usebibmacro{related}%
2320 }%
2321 \newunit\newblock
2322 \usebibmacro{pageref}%
2323 \usebibmacro{finentry}%

2324 \renewbibmacro*{incollection:full}{%
2325 \usebibmacro{maintitle+booktitle}%
2326 \newunit\newblock
2327 \usebibmacro{byeditor+others}%
2328 \newunit\newblock
2329 \ifdefstring{\bbx@editionformat}{superscript}{}%
2330 {\printfield{edition}%
2331 \newunit}%
2332 \printfield{volumes}%
2333 \newunit\newblock
2334 \usebibmacro{series+number}%
2335 \newunit\newblock
2336 \printfield{note}%
2337 }
```

```
2338 \newunit\newblock
2339 \usebibmacro{publisher+location+date}%
2340 \newunit
2341 \iffieldundef{maintitle}
2342   {\printfield{volume}%
2343    \printfield{part}}
2344  {}%
2345 \newunit\newblock
2346 \usebibmacro{chapter+pages}%
2347 \newunit\newblock
2348 \iftoggle{bbx:isbn}
2349   {\printfield{isbn}}
2350  {}%
2351 \newunit\newblock
2352 \usebibmacro{doi+eprint+url}%
2353 \newunit\newblock
2354 \usebibmacro{addendum+pubstate:article-inbook-incoll}%
2355 \newblock
2356 \iftoggle{bbx:related}
2357   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2358    {\setunit{\addsemicolon\space}}%
2359    {\setunit{\unspace\space}}%horrible trick
2360    \usebibmacro{related:init}%
2361    \usebibmacro{related}{}%
2362  {}%
2363 \newunit\newblock
2364 \usebibmacro{pageref}%
2365 \usebibmacro{finentry}

2366

2367
2368 \DeclareBibliographyDriver{manual}{%
2369   \usebibmacro{bibindex}%
2370   \usebibmacro{begentry}%
2371   \usebibmacro{author/editor}%
2372   \setunit{\labelnamepunct}\newblock
2373   \usebibmacro{title}%
2374   \newunit
2375   \printlist{language}%
2376   \newunit\newblock
2377   \usebibmacro{byauthor}%
2378   \newunit\newblock
2379   \usebibmacro{byeditor}%
2380   \newunit\newblock
2381   \ifdefstring{\bbx@editionformat}{superscript}{}%
2382   {\printfield{edition}%
2383   \newunit\newblock}
2384   \usebibmacro{series+number}%
2385   \newunit\newblock
2386   \printfield{type}%
2387   \newunit
2388   \printfield{version}%
2389   \newunit
```

```
2390 \printfield{note}%
2391 \newunit\newblock
2392 \printlist{organization}%
2393 \newunit
2394 \usebibmacro{publisher+location+date}%
2395 \newunit\newblock
2396 \usebibmacro{chapter+pages}%
2397 \newunit
2398 \printfield{pagetotal}%
2399 \newunit\newblock
2400 \iftoggle{bbx:isbn}
2401   {\printfield{isbn}}
2402   {}%
2403 \newunit\newblock
2404 \usebibmacro{doi+eprint+url}%
2405 \newunit\newblock
2406 \usebibmacro{addendum+pubstate}%
2407 \newblock
2408 \iftoggle{bbx:related}
2409   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2410    {\setunit{\addsemicolon\space}}%
2411    {\setunit{\unspace\space}}%horrible trick
2412    \usebibmacro{related:init}%
2413    \usebibmacro{related}{}%
2414   {}%
2415 \newunit\newblock
2416 \usebibmacro{pageref}%
2417 \usebibmacro{finentry}%
2418
2419 \newbibmacro*{usedriver:book}{%
2420   \usebibmacro{bibindex}%
2421   \usebibmacro{begentry}%
2422   \usebibmacro{nodash:author/editor+others/translator+others}%
2423   \setunit{\labelnamepunct}\newblock
2424   \usebibmacro{maintitle+title}%
2425 \newunit
2426   \printlist{language}%
2427 \newunit\newblock
2428   \usebibmacro{byauthor}%
2429 \newunit\newblock
2430   \usebibmacro{byeditor+others}%
2431 \newunit\newblock
2432   \ifdefstring{\bbx@editionformat}{superscript}{}%
2433   {\printfield{edition}%
2434   \newunit}%
2435   \printfield{volumes}%
2436 \newunit\newblock
2437   \usebibmacro{series+number}%
2438 \newunit\newblock
2439   \printfield{note}%
2440 \newunit\newblock
2441   \usebibmacro{publisher+location+date}%

```

```
2442 \newunit
2443 \iffieldundef{maintitle}
2444   {\printfield{volume}%
2445     \printfield{part}%
2446   }%
2447 \newunit\newblock
2448 \usebibmacro{chapter+pages}%
2449 \newunit
2450 \printfield{pagetotal}%
2451 \newunit\newblock
2452 \iftoggle{bbx:isbn}
2453   {\printfield{isbn}%
2454   }%
2455 \newunit\newblock
2456 \usebibmacro{doi+eprint+url}%
2457 \newunit\newblock
2458 \usebibmacro{addendum+pubstate}%
2459 \newblock
2460 \iftoggle{bbx:related}
2461   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2462    {\setunit{\addsemicolon\space}}%
2463    {\setunit{\unspace\space}}%horrible trick
2464    \usebibmacro{related:init}%
2465    \usebibmacro{related}%
2466   }%
2467 \newunit\newblock
2468 \usebibmacro{pageref}%
2469 }
2470 \newbibmacro*{usedriver:collection}{%
2471   \usebibmacro{bibindex}%
2472   \usebibmacro{begentry}%
2473   \usebibmacro{nodash:editor+others}%
2474   \setunit{\labelnamepunct}\newblock
2475   \usebibmacro{maintitle+title}%
2476   \newunit
2477   \printlist{language}%
2478   \newunit\newblock
2479   \usebibmacro{byeditor+others}%
2480   \newunit\newblock
2481   \ifdefstring{\bbx@editionformat}{superscript}{}%
2482   {\printfield{edition}%
2483   }%
2484   \iffieldundef{maintitle}
2485     {\printfield{volume}%
2486       \printfield{part}%
2487     }%
2488   \newunit
2489   \printfield{volumes}%
2490   \newunit\newblock
2491   \usebibmacro{series+number}%
2492   \newunit\newblock
2493   \printfield{note}%
```

```
2494 \newunit\newblock
2495 \usebibmacro{publisher+location+date}%
2496 \newunit\newblock
2497 \usebibmacro{chapter+pages}%
2498 \newunit
2499 \printfield{pagetotal}%
2500 \newunit\newblock
2501 \iftoggle{bbx:isbn}
2502   {\printfield{isbn}}
2503   {}%
2504 \newunit\newblock
2505 \usebibmacro{doi+eprint+url}%
2506 \newunit\newblock
2507 \usebibmacro{addendum+pubstate}%
2508 \newblock
2509 \iftoggle{bbx:related}
2510   {\ifdefstring{\bbx@relatedformat}{semicolon}%
2511     {\setunit{\addsemicolon\space}}%
2512     {\setunit{\unspace\space}}%horrible trick
2513     \usebibmacro{related:init}%
2514     \usebibmacro{related}{}%
2515   {}%
2516 \newunit\newblock
2517 \usebibmacro{pageref}%
2518 }
2519 \DeclareCiteCommand{\bbx@crossref@inbook}%
2520   {}%
2521   {\ifciteseen{%
2522     \ifthenelse{\value{listtotal}=2}%
2523       {\printnames[][-\value{maxnamesincross}]{labelname}}%
2524       {\printnames[][-\value{minnamesincross}]{labelname}}%
2525     \setunit*{\addcomma\space}\printtext{%
2526       \printfield[citetitle]{labeltitle}%
2527       \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}%
2528     {\setunit{\addspace\midsentence}}%
2529       \bibstring{cited}}%
2530     {\DeclareNameAlias{sortname}{default}}%
2531     \usebibmacro{usedriver:book}}{}%
2532   {}%
2533   {}%
2534 \DeclareCiteCommand{\bbx@crossref@incollection}%
2535   {}%
2536   {\ifciteseen{%
2537     \ifthenelse{\value{listtotal}=2}%
2538       {\printnames[][-\value{maxnamesincross}]{labelname}}%
2539       {\printnames[][-\value{minnamesincross}]{labelname}}%
2540       \setunit{\addspace}%
2541       \usebibmacro{editorstrg}}%
2542     \setunit*{\addcomma\space}\printtext{%
2543       \printfield[citetitle]{labeltitle}%
2544       \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}%
2545       {\setunit{\addspace\midsentence}}%
```

```

2546      \bibstring{cited}}}}%
2547      {\DeclareNameAlias{sortname}{default}%
2548      \usebibmacro{usedriver:collection}}}%
2549  {}%
2550  {}%

```

7.5 philosophy-classic.cbx

7.5.1 Initial settings

```

2551 \RequireCitationStyle{authoryear-comp}
2552
2553 \newtoggle{cbx:scauthorscite}
2554
2555 \DeclareBibliographyOption{scauthorscite}[true]{%
2556   \settoggle{cbx:scauthorscite}{#1}}
2557
2558 \ExecuteBibliographyOptions{%
2559   scauthorscite = false,
2560   citetracker = true,
2561 }
2562
2563 \AtEveryCite{%
2564   \iftoggle{cbx:scauthorscite}{%
2565     {\let\mkbibnamefamily\mkbibsc%
2566      \let\mkbibnamegiven\mkbibsc%
2567      \let\mkbibnameprefix\mkbibsc%
2568      \let\mkbibnameaffix\mkbibsc}%
2569   }{}%
2570
2571 %\DeclareNameFormat{labelname}{%
2572 %\bibhyperref{%
2573 %  \ifcase\value{uniquename}%
2574 %    \usebibmacro{name:family}{#1}{#3}{#5}{#7}%
2575 %  \or
2576 %    \ifuseprefix
2577 %      {\usebibmacro{name:given-family}{#1}{#4}{#5}{#8}}%
2578 %      {\usebibmacro{name:given-family}{#1}{#4}{#6}{#8}}%
2579 %  \or
2580 %    \usebibmacro{name:given-family}{#1}{#3}{#5}{#7}%
2581 %  \fi
2582 %  \usebibmacro{name:andothers}}}
2583 \DeclareNameFormat{labelname}{%
2584   \nameparts{#1}%
2585 \bibhyperref{\ifcase\value{uniquename}%
2586   \usebibmacro{name:family}%
2587   {\namepartfamily}%
2588   {\namepartgiven}%
2589   {\namepartprefix}%
2590   {\namepartsuffix}}%
2591 \or
2592   \ifuseprefix
2593   {\usebibmacro{name:given-family}}
```

```

2594     {\namepartfamily}
2595     {\namepartgiveni}
2596     {\namepartprefix}
2597     {\namepartsuffixi}}
2598     {\usebibmacro{name:given-family}}
2599     {\namepartfamily}
2600     {\namepartgiveni}
2601     {\namepartprefixi}
2602     {\namepartsuffixi}}%
2603 \or
2604   \usebibmacro{name:given-family}
2605   {\namepartfamily}
2606   {\namepartgiven}
2607   {\namepartprefix}
2608   {\namepartsuffix}}%
2609 \fi
2610 \usebibmacro{name:andothers}}}
2611
2612 \newcommand{\switchclass}[2]{%
2613   \iffieldequalstr{entrysubtype}{classic}%
2614     {\usebibmacro{#1}}%
2615     {\usebibmacro{#2}}}

```

7.5.2 Author-title macros

Import the :AT macros from the authortitle-comp.cbx file.

```

2616 \newbibmacro*[cite:init:AT]{%
2617   \ifnumless{\value{multicitecount}}{2}
2618     {\global\boolfalse{cbx:parens}%
2619      \global\undef\cbx@lasthash}%
2620     {\iffieldundef{prenote}%
2621       {}%
2622       {\global\undef\cbx@lasthash}}}
2623
2624 \newbibmacro*[cite:reinit:AT]{%
2625   \global\undef\cbx@lasthash}
2626
2627 \newbibmacro*[cite:AT]{%
2628   \iffieldundef{shorthand}
2629     {\iffieldequals{namehash}{\cbx@lasthash}%
2630      {\setunit{\compitedelim}}%
2631      {\ifnameundef{labelname}%
2632        {}%
2633        {\printnames{labelname}}%
2634        {\setunit{\nametitledelim}}%
2635        {\savefield{namehash}{\cbx@lasthash}}%
2636        \usebibmacro{cite:title:AT}}%
2637      {\usebibmacro{cite:shorthand}}%
2638      {\usebibmacro{cite:reinit:AT}}%
2639      \setunit{\multicitedelim}}}
2640
2641 \newbibmacro*[citetitle:AT]{%
2642   \iffieldundef{shorthand}}

```

```
2643     {\usebibmacro{cite:title:AT}}%
2644     {\usebibmacro{cite:shorthand}}%
2645     \setunit{\multicitedelim}%
2646
2647 \newbibmacro*{textcite:AT}{%
2648   \iffieldequals{namehash}{\cbx@lasthash}%
2649     {\setunit{\compcitedelim}}%
2650     {\ifnameundef{labelname}%
2651       {}%
2652       {\printnames{labelname}}%
2653       \setunit{\%}
2654     \global\booltrue{cbx:parens}%
2655     \addspace\bibopenparen}}%
2656     \savefield{namehash}{\cbx@lasthash}}%
2657 \ifnumequal{\value{citecount}}{1}%
2658   {\usebibmacro{prenote}}%
2659   {}%
2660 \iffieldundef{shorthand}%
2661   {\usebibmacro{cite:title:AT}}%
2662   {\iftoggle{cbx:shorthandintro}{%
2663     \ifciteseen{%
2664       \usebibmacro{cite:shorthand}}%
2665       {\usebibmacro{shorthandintro}}}}%
2666     {\usebibmacro{cite:shorthand}}}}%
2667 \setunit{\%}
2668   \ifbool{cbx:parens}%
2669     {\bibcloseparen\global\boolfalse{cbx:parens}}%
2670     {}%
2671   \multicitedelim}%
2672
2673 \newbibmacro*{cite:title:AT}{%
2674   \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}%
2675
2676 \newbibmacro*{textcite:postnote:AT}{%
2677   \ifnameundef{labelname}%
2678     {\setunit{\%}
2679      \global\booltrue{cbx:parens}%
2680      \addspace\bibopenparen}}%
2681     {\setunit{\postnotedelim}}}}%
2682 \printfield{postnote}%
2683 \ifthenelse{\value{multicitecount}=\value{multicitetotal}}%
2684   {\setunit{\%}
2685     \printtext{%
2686       \ifbool{cbx:parens}%
2687         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2688       {}}}%
2689     {\setunit{\%
2690       \ifbool{cbx:parens}%
2691         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2692       {}}}%
2693     \multicitedelim}}
```

7.5.3 Author-year macros

```

2694 \newbibmacro*[cite:init:AY]{%
2695   \ifnumless{\value{multicitecount}}{2}%
2696     {\global\boolfalse{cbx:parens}%
2697      \global\undef\cbx@lasthash
2698      \global\undef\cbx@lastyear}
2699     {\iffieldundef{prenote}%
2700       {}%
2701       {\global\undef\cbx@lasthash
2702 \global\undef\cbx@lastyear}}}
2703
2704 \newbibmacro*[cite:reinit:AY]{%
2705   \global\undef\cbx@lasthash
2706   \global\undef\cbx@lastyear}
2707
2708 \newbibmacro*[cite:AY]{%
2709   \iffieldundef{shorthand}%
2710   {\usebibmacro{cite:noshorthand}%
2711    {\iftoggle{cbx:shorthandintro}%
2712      {%
2713        \ifciteseen{\usebibmacro{cite:shorthand}%
2714          {\usebibmacro{cite:noshorthand}%
2715          \usebibmacro{shorthandintro}%
2716          }%
2717          {\usebibmacro{cite:shorthand}%
2718          \usebibmacro{cite:reinit:AY}%
2719          \setunit{\multicitedelim}}}
2720
2721 \newbibmacro*[textcite:AY]{%
2722   \iffieldequals{namehash}{\cbx@lasthash}%
2723     {\iffieldundef{shorthand}%
2724       {\ifthenelse{\iffieldequals{labelyear}{\cbx@lastyear}\AND
2725         {(\value{multicitecount}=0\OR\iffieldundef{postnote})}}%
2726         {\setunit{\addcomma}%
2727          \usebibmacro{cite:extrayear}%
2728          \setunit{\compcitedelim}%
2729          \usebibmacro{cite:labelyear+extrayear}%
2730          \savefield{labelyear}{\cbx@lastyear}}%
2731       \setunit{\compcitedelim}%
2732       \iftoggle{cbx:shorthandintro}%
2733         {\ifciteseen
2734           {\usebibmacro{cite:shorthand}%
2735            {\ifthenelse{\iffieldequals{labelyear}{\cbx@lastyear}\AND
2736              {(\value{multicitecount}=0\OR\iffieldundef{postnote})}}%
2737              {\setunit{\addcomma}%
2738                \usebibmacro{cite:extrayear}%
2739                \setunit{\compcitedelim}%
2740                \usebibmacro{cite:labelyear+extrayear}%
2741                \savefield{labelyear}{\cbx@lastyear}}%
2742              \usebibmacro{shorthandintro}}%
2743              {\usebibmacro{cite:shorthand}}%
```

```

2744     \global\undef\cbx@lastyear} }%
2745     {\ifnameundef{labelname}%
2746       {\iffieldundef{shorthand}{shorthand}%
2747         {\usebibmacro{cite:label}%
2748           \setunit{%
2749             \global\booltrue{cbx:parens}%
2750             \addspace\bibopenparen}%
2751           \ifnumequal{\value{citecount}}{1}{%
2752             {\usebibmacro{prenote} }%
2753             {\usebibmacro{cite:shorthand} }%
2754             \usebibmacro{cite:labelyear+extrayear} }%
2755               {\iftoggle{cbx:shorthandintro}{%
2756                 {\ifciteseen{shorthand}%
2757                   {\usebibmacro{cite:shorthand} }%
2758                   {\usebibmacro{cite:label} }%
2759                   \setunit{%
2760                     \global\booltrue{cbx:parens}%
2761                     \addspace\bibopenparen}%
2762                     \ifnumequal{\value{citecount}}{1}{%
2763                       {\usebibmacro{prenote} }%
2764                         {\usebibmacro{cite:shorthand} }%
2765                         \usebibmacro{cite:labelyear+extrayear} }%
2766                         \usebibmacro{shorthandintro} } } }%
2767                         {\usebibmacro{cite:shorthand} }%
2768                           {\printnames{labelname} }%
2769           \setunit{%
2770             \global\booltrue{cbx:parens}%
2771             \addspace\bibopenparen}%
2772           \ifnumequal{\value{citecount}}{1}{%
2773             {\usebibmacro{prenote} }%
2774             {} }%
2775               \iffieldundef{shorthand}{noshorthand}%
2776                 {\iffieldundef{labelyear}{%
2777                   {\usebibmacro{cite:label} }%
2778                   {\usebibmacro{cite:labelyear+extrayear} }%
2779                   \savefield{labelyear}{\cbx@lastyear} }%
2780                   {\iftoggle{cbx:shorthandintro}{%
2781                     {\ifciteseen{%
2782                       {\usebibmacro{cite:shorthand} }%
2783                       {\iffieldundef{labelyear}{%
2784                         {\usebibmacro{cite:label} }%
2785                         {\usebibmacro{cite:labelyear+extrayear} }%
2786                         \savefield{labelyear}{\cbx@lastyear} }%
2787                         {\usebibmacro{shorthandintro} }%
2788                         {\global\undef\cbx@lastyear} }%
2789                         {\usebibmacro{cite:shorthand} }%
2790                         \savefield{namehash}{\cbx@lasthash} } } }%
2791           \setunit{%
2792             \ifbool{cbx:parens}{%
2793               {\bibcloseparen\global\boolfalse{cbx:parens}} }%
2794             {} }%
2795             \multicitedelim } }%

```

```

2796 \newbibmacro*{textcite:postnote:AY}{%
2797   \usebibmacro{postnote}%
2798   \ifthenelse{\value{multicitecount}=\value{multicitetotal}}%
2799     {\setunit{}%}
2800     \printtext{%
2801       \ifbool{cbx:parens}%
2802         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2803       {}%
2804     }%
2805     {\setunit{}%
2806       \ifbool{cbx:parens}%
2807         {\bibcloseparen\global\boolfalse{cbx:parens}}%
2808       {}%
2809     \multicitedelim}}}
```

The `cite:shorthand` is the same for both author-title and author-year styles:

```

2810 \renewbibmacro*{cite:shorthand}{%
2811   \printtext[bibhyperref]{\printfield{shorthand}}}
```

If the field `entrysubtype` equals to `classic` the citation commands will use the author-title macros:

```

2812 \renewbibmacro*{cite:init}{%
2813   \switchclass{cite:init:AT}{cite:init:AY}}
2814 \renewbibmacro*{cite:reinit}{%
2815   \switchclass{cite:reinit:AT}{cite:reinit:AY}}
2816 \renewbibmacro*{cite}{%
2817   \switchclass{cite:AT}{cite:AY}}
2818 \renewbibmacro*{textcite}{%
2819   \switchclass{textcite:AT}{textcite:AY}}
2820 \renewbibmacro*{textcite:postnote}{%
2821   \switchclass{textcite:postnote:AT}{textcite:postnote:AY}}
2822
2823 \newbibmacro*{cite:noshorthand}{%
2824   \ifthenelse{\ifnameundef{labelname}\OR\iffieldundef{labelyear}}{%
2825     {\usebibmacro{cite:label}}%
2826     \setunit{\addspace}%
2827     \usebibmacro{cite:labelyear+extrayear}%
2828     \usebibmacro{cite:reinit}%
2829     {\iffieldequals{namehash}{\cbx@lasthash}{%
2830       \ifthenelse{\iffieldequals{labelyear}{\cbx@lastyear}\AND%
2831         (\value{multicitecount}=0\OR\iffieldundef{postnote})}{%
2832         {\setunit{\addcomma}%
2833           \usebibmacro{cite:extrayear}}%
2834         {\setunit{\compcitedelim}}%
2835           \usebibmacro{cite:labelyear+extrayear}%
2836           \savefield{labelyear}{\cbx@lastyear}}}}%
2837     {\printnames{labelname}}%
2838     \setunit{\nameyeardelim}%
2839     \usebibmacro{cite:labelyear+extrayear}%
2840     \savefield{namehash}{\cbx@lasthash}%
2841     \iffieldundef{postnote}{%
2842       {\savefield{labelyear}{\cbx@lastyear}}}}}}
```

7.5.4 Citation commands

```

2843 \DeclareCiteCommand{\cite}
2844   {\usebibmacro{cite:init}%
2845     \usebibmacro{prenote}%
2846   {\usebibmacro{citeindex}%
2847     \switchclass{citetitle:AT}{citeyear}}%
2848   {}%
2849   {\usebibmacro{postnote}}%
2850
2851 \DeclareCiteCommand{\parencite}[\mkbibparens]
2852   {\usebibmacro{cite:init}%
2853     \usebibmacro{prenote}%
2854   {\usebibmacro{citeindex}%
2855     \switchclass{citetitle:AT}{citeyear}}%
2856   {}%
2857   {\usebibmacro{postnote}}%
2858
2859 \DeclareCiteCommand{\citetitle}
2860   {\booleventh{\citetracker}%
2861     \booleventh{\pagetracker}%
2862     \usebibmacro{prenote}%
2863   {\indexfield{inextitle}%
2864     \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}%
2865   {\multicitedelim}%
2866   {\usebibmacro{postnote}}%
2867
2868 \DeclareCiteCommand{\citetitle}
2869   {\booleventh{\citetracker}%
2870     \booleventh{\pagetracker}%
2871     \usebibmacro{prenote}%
2872   {\indexfield{inextitle}%
2873     \printtext[bibhyperref]{\printfield[citetitle]{title}}}%
2874   {\multicitedelim}%
2875   {\usebibmacro{postnote}}%
2876
2877 \DeclareCiteCommand{\citeyear}
2878   {\booleventh{\citetracker}%
2879     \booleventh{\pagetracker}%
2880     \usebibmacro{prenote}%
2881   {\printtext[bibhyperref]{\printfield{year}}}%
2882   {\multicitedelim}%
2883   {\usebibmacro{postnote}}%
2884
2885 \DeclareCiteCommand{\footcitet}[\mkbibfootnote]
2886   {\usebibmacro{cite:init}%
2887   {\usebibmacro{citeindex}%
2888     \usebibmacro{textcite}%
2889   {}%
2890   {\usebibmacro{textcite:postnote}}}

```

This command is now deprecated because it is substituted by the `entrysubtype=classic` mechanism:

```
2891 \DeclareCiteCommand{\sdcite}
```

```

2892 {\boolearn{citetracker}%
2893   \boolearn{pagetracker}%
2894   \usebibmacro{prenote}%
2895 {\indexnames{labelname}%
2896   \printtext[bibhyperref]{\printnames{labelname}}%
2897   \setunit{\addcomma\space}%
2898   \indexfield{indextitle}%
2899   \printtext[bibhyperref]{\printfield[citetitle]{labeltitle}}}%
2900 {\multicitedelim}%
2901 {\usebibmacro{postnote}}}
```

7.6 philosophy-modern.cbx

The modern style uses the classic citation scheme:

```
2902 \RequireCitationStyle{philosophy-classic}
```

The `\fullcite` command simply prints the bibliography entry supplied by the style used. So we have to redefine this command in order to get the same output as that produced in the `philosophy-classic` style:

```

2903 \DeclareCiteCommand{\fullcite}%
2904   {\usebibmacro{prenote}{}%}
2905   {\setkeys{blx@bib2}{restoreclassic}%
2906   \usedriver%
2907     {\DeclareNameAlias{sortname}{default}}%
2908     {\thefield{entrytype}}}%
2909 {\multicitedelim}%
2910 {\usebibmacro{postnote}}%
```

7.7 philosophy-verbose.cbx

7.7.1 Initial settings

```

2911 \RequireCitationStyle{verbose-trad2}
2912
2913 \newtoggle{cbx:scauthorscrite}
2914 \newtoggle{cbx:latinemph}
2915 \newtoggle{cbx:commacit}
2916
2917 \DeclareBibliographyOption{scauthorscrite}[true]{%
2918   \settoggle{cbx:scauthorscrite}{#1}}
2919 \DeclareBibliographyOption{latinemph}[true]{%
2920   \settoggle{cbx:latinemph}{#1}}
2921 \DeclareBibliographyOption{commacit}[true]{%
2922   \settoggle{cbx:commacit}{#1}}
2923
2924 \ExecuteBibliographyOptions{%
2925   idemtracker=false,
2926   loccittracker=strict,
2927   scauthorscrite=false,
2928   latinemph=false,
2929   commacit=false}
2930
2931 \AtEveryCite{%
```

The annotation field is omitted in every citations:

```
2932 \togglefalse{bbx:annotation}%
```

Redefine \mkibid for every citations when using the latinemph option:

```
2933 \iftoggle{cbx:latinemph}{\renewcommand*{\mkibid}{\emph}}{}%
```

Name formats

```
2934 \renewbibmacro*{name:andothers}{%
2935   \ifboolexpr{%
2936     test {\ifnumequal{\value{listcount}}{\value{liststop}}}{%
2937       and
2938       test \ifmorenames
2939     }%
2940     {\ifnumgreater{\value{liststop}}{1}{%
2941       {\finalandcomma}%
2942     }{%
2943       \andothersdelim\bibstring[\mkibid]{andothers}%
2944     }%
2945   }%
2946 \renewbibmacro*{list:andothers}{%
2947   \ifboolexpr{%
2948     test {\ifnumequal{\value{listcount}}{\value{liststop}}}{%
2949       and
2950       test \ifmoreitems
2951     }%
2952     {\ifnumgreater{\value{liststop}}{1}{%
2953       {\finalandcomma}%
2954     }{%
2955       \andmoredelim\bibstring[\mkibid]{andmore}%
2956     }%
2957 \iftoggle{cbx:scauthorscite}{%
2958 \% \DeclarNameFormat{labelname}{%
2959 \% \let\mkbibnamefamily\mkbibsc%
2960 \% \let\mkbibnamegiven\mkbibsc%
2961 \% \let\mkbibnameprefix\mkbibsc%
2962 \% \let\mkbibnameaffix\mkbibsc}{}%
2963 \% \ifcase\value{uniquename}%
2964 \%   \usebibmacro{name:family}{#1}{#3}{#5}{#7}%
2965 \% \or
2966 \%   \ifuseprefix
2967 \%     {\usebibmacro{name:given-family}{#1}{#4}{#5}{#8}}%
2968 \%     {\usebibmacro{name:given-family}{#1}{#4}{#6}{#8}}%
2969 \% \or
2970 \%   \usebibmacro{name:given-family}{#1}{#3}{#5}{#7}%
2971 \% \fi
2972 \%   \usebibmacro{name:andothers}%
2973 \DeclarNameFormat{labelname}{%
2974 \iffootnote{%
2975   \let\mkbibnamefamily\mkbibsc%
2976   \let\mkbibnamegiven\mkbibsc%
2977   \let\mkbibnameprefix\mkbibsc%
2978   \let\mkbibnameaffix\mkbibsc}{}%
2979 \nameparts{#1}%
}
```

```
2980 \ifcase\value{uniquename}%
2981   \usebibmacro{name:family}%
2982   {\namepartfamily}%
2983   {\namepartgiven}%
2984   {\namepartprefix}%
2985   {\namepartsuffix}%
2986 \or
2987   \ifuseprefix
2988     {\usebibmacro{name:given-family}%
2989      {\namepartfamily}%
2990      {\namepartgivendi}%
2991      {\namepartprefix}%
2992      {\namepartsuffix}}%
2993     {\usebibmacro{name:given-family}%
2994      {\namepartfamily}%
2995      {\namepartgivendi}%
2996      {\namepartprefix}%
2997      {\namepartsuffix}}%
2998 \or
2999   \usebibmacro{name:given-family}%
3000   {\namepartfamily}%
3001   {\namepartgiven}%
3002   {\namepartprefix}%
3003   {\namepartsuffix}%
3004 \fi
3005 \usebibmacro{name:andothers}%
3006 }{}%
3007 %\DeclareNameFormat{scdefault}{%
3008 %\iffootnote{%
3009 %  \let\mkbibnamefamily\mkbibsc%
3010 %  \let\mkbibnamegiven\mkbibsc%
3011 %  \let\mkbibnameprefix\mkbibsc%
3012 %  \let\mkbibnameaffix\mkbibsc}{}%
3013 % \iffirstinits
3014 %  {\usebibmacro{name:given-family}{#1}{#4}{#5}{#7}}%
3015 %  {\usebibmacro{name:given-family}{#1}{#3}{#5}{#7}}%
3016 %  \usebibmacro{name:andothers}%
3017 %\DeclareNameFormat{scdefault}{%
3018 \iffootnote{%
3019   \let\mkbibnamefamily\mkbibsc%
3020   \let\mkbibnamegiven\mkbibsc%
3021   \let\mkbibnameprefix\mkbibsc%
3022   \let\mkbibnameaffix\mkbibsc}{}%
3023 \nameparts{#1}%
3024 \ifgiveninits
3025   {\usebibmacro{name:given-family}%
3026     {\namepartfamily}%
3027     {\namepartgivendi}%
3028     {\namepartprefix}%
3029     {\namepartsuffix}}%
3030   {\usebibmacro{name:given-family}%
3031     {\namepartfamily}}
```

```

3032     {\namepartgiven}%
3033     {\namepartprefix}%
3034     {\namepartsuffix}%
3035 \usebibmacro{name:andothers}%

```

7.7.2 New macros

```

3036 \newbibmacro*[cite:opcit]{%
3037   \printtext[bibhyperlink]{\bibstring[\mkibid]{opcit}}}
3038
3039 \newbibmacro*[cite:loccit]{%
3040   \printtext{%
3041     \bibhyperlink{cite\csuse{cbx@lastcite@\thefield{entrykey}}}{%
3042       \bibstring[\mkibid]{loccit}}}}
3043 \global\toggletrue{cbx:loccit}
3044
3045 \renewbibmacro*[cite:ibid]{%
3046   \ifloccit
3047     {\usebibmacro{cite:loccit}}{%
3048       \printtext{%
3049         \bibhyperlink{cite\csuse{cbx@lastcite@\thefield{entrykey}}}{%
3050           \bibstring[\mkibid]{ibidem}}}}{%
3051
3052 \renewbibmacro*[cite:title]{%OK
3053   \ifsingletitle{\usebibmacro{cite:opcit}}{%
3054     \printtext[bibhyperlink]{%
3055       \printfield[citetitle]{labeltitle}}%
3056       \iftoggle{cbx:commacit}{\setunit{\addcomma\space}}{%
3057         \setunit{\addspace\midsentence}}}}{%
3058       \bibstring{cited}}}
3059
3060 % \renewbibmacro*[cite:full]{%OK
3061 %   \usebibmacro{cite:full:citepages}%
3062 %   \global\toggletrue{cbx:fullcite}%
3063 %   \printtext[bibhypertarget]{%
3064 %     \usedriver
3065 %       {\iftoggle{cbx:scauthorscite}{%
3066 %         \DeclareNameAlias{sortname}{scdefault}}{%
3067 %         {\ DeclareNameAlias{sortname}{default}}}}{%
3068 %         {\thefield{entrytype}}}}{%
3069 %   \usebibmacro{shorthandintro}}
3070
3071 \renewbibmacro*[cite:full]{%OK
3072   \iftoggle{cbx:shorthandintro}{%
3073     \usebibmacro{cite:full:citepages}%
3074     \global\toggletrue{cbx:fullcite}%
3075     \printtext[bibhypertarget]{%
3076       \usedriver
3077         {\iftoggle{cbx:scauthorscite}{%
3078           \DeclareNameAlias{sortname}{scdefault}}{%
3079             {\ DeclareNameAlias{sortname}{default}}}}{%
3080               {\thefield{entrytype}}}}{%

```

```

3081 \usebibmacro{shorthandintro}%
3082 {\usebibmacro{cite:shorthand}}%
3083
3084
3085
3086 \renewbibmacro*[cite:idem]{%
3087 \iftoggle{cbx:scauthorscite}{%
3088 \bibstring[\mkibsc]{idem\thefield{gender}}}{%
3089 \bibstring[\mkibid]{idem\thefield{gender}}}}%
3090 \setunit{\nametitledelim}%
3091
3092 \newbibmacro*[ccite:cite]{%
3093 \usebibmacro{related:clearauthors}%
3094 \usebibmacro{cite:citepages}%
3095 \global\togglefalse{cbx:fullcite}%
3096 \global\togglefalse{cbx:loccit}%
3097 \bibhypertarget{cite\the\value{instcount}}{%
3098 \ifcitesseen
3099 {\iffieldundef{shorthand}
3100 {\usebibmacro{cite:title}}%
3101 \usebibmacro{cite:save}%
3102 {\usebibmacro{cite:shorthand}}%
3103 {\usebibmacro{cite:full}}%
3104 \usebibmacro{cite:save}}}%

```

7.7.3 Citation commands

```

3105 \DeclareCiteCommand{\ccite}%
3106 {\usebibmacro{prenote}}%
3107 {\usebibmacro{citeindex}}%
3108 \usebibmacro{ccite:cite}%
3109 {\multicitedelim}%
3110 {\usebibmacro{cite:postnote}}%
3111 \DeclareCiteCommand{\fullcite}%
3112 {\usebibmacro{prenote}}%
3113 {\usedriver
3114 {\iftoggle{cbx:scauthorscite}{%
3115 {\DeclareNameAlias{sortname}{scdefault}}%
3116 {\DeclareNameAlias{sortname}{default}}}}%
3117 {\thefield{entrytype}}%
3118 {\multicitedelim}%
3119 {\usebibmacro{postnote}}}

```

7.8 italian-philosophy.lbx

```

3120 \InheritBibliographyExtras{italian}%
3121
3122 \DeclareBibliographyExtras{}%
3123 \protected\def\bibrangedash{%
3124 -\penalty\hyphenpenalty}%
3125 \protected\def\bibdatedash{\textendash}%
3126
3127 \NewBibliographyString{origned,cited}%
3128

```

```

3129 \DeclareBibliographyStrings{%
3130   inherit          = {italian},
3131   nodate           = {{senza data}{s\addotspace d\adddot}},
3132   cited            = {{cit\adddot}{cit\adddot}},
3133   opcit            = {{op\addotspace cit\adddot}{op\addotspace cit\adddot}},
3134   ibidem           = {{ivi}{ivi}},
3135   loccit           = {{ibidem}{ibidem}},
3136   origed           = {{ed\addotspace orig\adddot}{ed\addotspace orig\adddot}},
3137   langitalian      = {{italiano}{it\adddot}},
3138   editor            = {{\mkpureparens{a cura di}}{\mkpureparens{a cura di}}},
3139   editors           = {{\mkpureparens{a cura di}}{\mkpureparens{a cura di}}},
3140   backrefpage      = {{Citato a pagina}{Citato a \bibstring{page}\adddot}},
3141   backrefpages     = {{Citato alle pagine}{Citato alle \bibstring{pages}\adddot}},
3142   pages             = {{pagine}{\iftoggle{bbx:classical}{pp\adddot}{p\adddot}}},
3143   columns           = {{colonne}{\iftoggle{bbx:classical}{coll\adddot}{col\adddot}}},
3144   lines              = {{righe}{\iftoggle{bbx:classical}{rr\adddot}{r\adddot}}},
3145   verses             = {{versi}{\iftoggle{bbx:classical}{vv\adddot}{v\adddot}}},
3146   section           = {{sezione}{sez\adddot}},
3147   sections          = {{sezioni}{\iftoggle{bbx:classical}{sez\adddot}{sez\adddot}}},
3148   paragraphs         = {{paragrafi}{\iftoggle{bbx:classical}{parr\adddot}{par\adddot}}},
3149   volumes            = {{volumi}{\iftoggle{bbx:classical}{voll\adddot}{vol\adddot}}},
3150   withcommentator    = {{con commenti di}{con comm\adddot\addabbrvspace di}},
3151   withannotator     = {{annotazioni di}{annotazioni di}},
3152   withintroduction   = {{introduzione di}{introduzione di}},
3153   withforeword       = {{prefazione di}{prefazione di}},
3154   withafterword      = {{postfazione di}{postfazione di}},
3155   reprintas          = {{ristampato}{rist\adddot}},
3156 % reprintfrom       = {{}}{}, % FIXME: missing
3157   translationof      = {{traduzione di}{trad\addotspace di}},
3158   translationas      = {{traduzione italiana}{trad\addotspace it\adddot}},
3159 % translationfrom    = {{}}{}, % FIXME: missing
3160   reviewof           = {{Recensione di}{Recensione di}},
3161 % origpubas          = {{}}{}, % FIXME: missing
3162 % origpubin          = {{}}{}, % FIXME: missing
3163 % astitle            = {{}}{}, % FIXME: missing
3164 % bypublisher        = {{}}{}, % FIXME: missing
3165   byreviser          = {{revisione di}{revisione di}}
3166 }

```

7.9 english-philosophy.lbx

```

3167 \InheritBibliographyExtras{english}
3168
3169 \DeclareBibliographyExtras{%
3170   \protected\def\bibrangedash{%
3171     -\penalty\hyphenpenalty}%
3172   \protected\def\bibdatedash{\textendash}}%
3173
3174 \NewBibliographyString{cited,origed}
3175
3176 \DeclareBibliographyStrings{%
3177   inherit          = {english},
3178   nodate           = {{no date}{n\adddot d\adddot}},

```

```

3179 cited = {{cit\adddot}{cit\adddot}},
3180 ibidem = {{ibid\adddot}{ibid\adddot}},
3181 loccit = {{ibid\adddot}{ibid\adddot}},
3182 origed = {{orig\adddotspace ed\adddot}{orig\adddotspace ed\adddot}},
3183 editor = {{\mkpureparens{ed\adddot}}{\mkpureparens{ed\adddot}}},
3184 editors = {{\mkpureparens{eds\adddot}}{\mkpureparens{eds\adddot}}},
3185 reviewof = {{Review of}{Review of}},
3186 translationas = {{trans\adddot}{trans\adddot}},
3187 backrefpage = {{cited on page}{cited on p\adddot}},
3188 backrefpages = {{cited on pages}{cited on pp\adddot}}
3189 }

```

7.10 spanish-philosophy.lbx

Thanks to Eduardo Villegas for these translations.

```

3190 %
3191 %--A Thanks to Eduardo Villegas for these translations.
3192 %
3193 \InheritBibliographyExtras{spanish}
3194
3195 \DeclareBibliographyExtras{%
3196 \protected\def\bibrangedash{%
3197 -\penalty\hyphenpenalty}%
3198 \protected\def\bibdatedash{\textendash}}%
3199
3200 \NewBibliographyString{origed,cited}
3201
3202 \DeclareBibliographyStrings{%
3203 inherit = {spanish},
3204 cited = {{cit\adddot}{cit\adddot}},
3205 opcit = {{op\adddot cit\adddot}{op\adddot cit\adddot}},
3206 ibidem = {{ivi}{ivi}},
3207 loccit = {{ibidem}{ibidem}},
3208 origed = {{edici'\{o}n original}{ed\adddot orig\adddot}},
3209 langspanish = {{espa\~nol}{es\adddot}},
3210 editor = {{\mkpureparens{ed\adddot}}{\mkpureparens{ed\adddot}}},
3211 editors = {{\mkpureparens{ed\adddot}}{\mkpureparens{eds\adddot}}},
3212 backrefpage = {{Citado en la p'\{a}gina}
   {Citado en la \bibstring{page}\adddot}}, %%FIXME: Maiuscola iniziale?
3213 backrefpages = {{Citado en las p'\{a}ginas}
   {Citado en las \bibstring{pages}\adddot}}, %%FIXME: Maiuscola iniziale?
3214 pages = {{p'\{a}ginas}{\iftoggle{bbx:classical}
   {p'\ags\adddot}{p'\ag\adddot}}},
3215 columns = {{columns}{\iftoggle{bbx:classical}{cols\adddot}{col\adddot}}},
3216 lines = {{l'\ineas}{\iftoggle{bbx:classical}{ll\adddot}{l\adddot}}},
3217 verses = {{versos}{\iftoggle{bbx:classical}{vv\adddot}{v\adddot}}},
3218 volumes = {{vol'\uumenes}
   {\iftoggle{bbx:classical}{vols\adddot}{vol\adddot}}},
3219 withcommentator = {{comentario de}{com\adddot\addabrvspace de}},
3220 withannotator = {{notas de}{notas de}},
3221 withintroduction = {{introducci'\{o}n de}{intr\adddotspace de}},
3222 withforeword = {{prefacio de}{pref\adddot space de}},

```

```

3227 withafterword      = {{postfacio de}{postfacio de}},
3228 reprintas          = {{reimpresi'\{o}n}{reimp\adddot}},
3229 translationof      = {{traducci'\{o}n al espa\~nol de}{trad\adddotspace de}},
3230 translationas      = {{traducido al espa\~nol como}{trad\adddotspace es\adddot}},
3231 reviewof            = {{Rese\~na de}{Rese\~na de}}, %FIXME: Maiuscola iniziale?
3232 section             = {{secci'\{o}n}{sec\adddot}},
3233 sections            = {{secciones}{\iftoggle{bbx:classical}
3234     {secs\adddot}{sec\adddot}}},
3235 byreviser           = {{revisi'\{o}n de}{rev\adddotspace de}}
3236 }

```

Change History

vo.4	General: Improved compatibility for biblatex version 0.9 1	documentation 1
vo.5	General: Added new bibliography style <code>philosophy-verbose</code> . Added localization file <code>italian-philosophy.lbx</code> . Added package options <code>origparens</code> , <code>origbrackets</code> , <code>latinemph</code> . Changed package options <code>scauthors</code> , <code>scauthorscite</code> , <code>scauthorsbib</code> . Renamed file <code>biblatex-philosophy-doc.tex</code> to <code>philosophy-authoryear-doc.tex</code> . Added file <code>philosophy-verbose-doc.tex</code> . Updated documentation 1	vo.7a General: Added command <code>volumfont</code> . Added command <code>footcitet</code> . Updated documentation 1
vo.6	General: Added localization file <code>italian-philosophy.lbx</code> . Added file <code>philosophy-standard.bbx</code> . New documentation file <code>biblatex-philosophy</code> . Removed files <code>philosophy-authoryear-doc.tex</code> , <code>philosophy-verbose-doc.tex</code> 1	vo.7b General: Removed package option <code>romanvol</code> . Added package option <code>volumeformat</code> . Added package option <code>editionformat</code> . Activated the option <code>singletitle</code> for style <code>philosophy-verbose</code> . Added bibliography driver <code>@review</code> . Added bibliography string <code>cit</code> . Added bibliography string <code>reviewof</code> . Updated documentation 1
vo.7	General: Removed package option <code>colonloc</code> . Removed package options <code>origparens</code> <code>origbrackets</code> . Added package options <code>origfieldsformat</code> , <code>publocformat</code> , <code>commacit</code> , <code>inbeforejournal</code> , <code>romanvol</code> , <code>volnumformat</code> . Added command <code>volnumpunct</code> . Added citation commands <code>\sdcite</code> , <code>\ccite</code> . Updated	vo.7c General: Fixed some bugs. New <code>origfieldtype</code> option. Added <code>nodate</code> bibliography string. Updated documentation 1
vo.8a		vo.8a General: New <code>entrysubtype</code> field for citing classical texts. New <code>related</code> field mechanism. New <code>relatedformat</code> option. New English documentation. Fixed some bugs 1
vo.8b		vo.8b General: Added <code>biber.conf</code> configuration file 1
vo.8c		vo.8c General: Removed <code>biber.conf</code> configuration file. Added internal <code>biber</code> settings with <code>\DeclareDriverSourcemap</code> command. Added <code>trans-</code> field alias 1

vo.8d	General: Fixed some bugs related to \DeclareDriverSourcemap, \ccite, and @review entry type	1	vo.9i	General: Corrected a bug with shorthandintro option.	1
vo.8e	General: Improved relatedformat option for cascading entries. Implemented cross-referencing mechanism for @inproceedings entries. Improved \ccite command. Changed the values for the entrysubtype from classical to classic. Added nodate package option.	1	vo.1o	General: Corrected a bug in volumeformat and volnumformat options. Change value romanupp to Roman in volume format and edition format. Corrected bug in related format options: now the related block is not preceded by semicolon when using values parens and brackets styles. \$updated documentation	1
vo.8f	General: New option nodate for \printbibliography command	1	v1.1	General: Maintenance release. Updated documentation.	1
vo.9a	General: Maintenance release. Corrected some bugs.	1	v1.2	General: Maintenance release. New value superscript for editionformat option.	1
vo.9b	General: Updated bibliography drivers to correct a bug when using the related mechanism.	1	v1.3	General: Maintenance release. Corrected a spurious space in article entries.	1
vo.9c	General: Maintenance release. Corrected some bugs.	1	v1.4	General: Maintenance release. Updated style for working with biblatex v.3.4.	1
vo.9d	General: Maintenance release. Corrected some bugs.	1	v1.5	General: Improved compatibility with legacy BibTeX backend.	1
vo.9e	General: Maintenance release. Updated documentation.	1	v1.6	General: Removed compatibility with legacy BibTeX backend.	1
vo.9f	General: Updated documentation. Corrected a bug in the volnumformat option.	1	v1.7	General: Maintenance release. Updated documentation.	1
vo.9g	General: Added localization module for spanish. Corrected a bug in @inbook and @incollection entries when using crossref field. Updated documentation.	1	v1.8	General: Maintenance release. Corrected an incompatibility with scauthors option.	1
vo.9h	General: New option lowscauthors. Corrected some bugs. Updated documentation.	1	v1.9	General: Redefined ibidem and loccit strings in file english-philosophy.lbx according to the Chicago Manual of Style.	1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

- Symbols**
- \` 3208, 3212, 3214, 3216, 3217, 3219, 3221, 3225, 3228, 3229, 3232, 3235
 - \` 2725, 2736, 2831
 - \` 2725, 2736, 2831
 - \` 3209, 3229–3231
- A**
- \addabrvspace . 3150, 3223
 - \addcolon . . 287, 449, 467, 592, 601, 610, 1449
 - \addcomma . 147, 150, 275, 289, 299, 301, 309, 323, 356, 360, 463, 479, 502, 508, 565, 574, 583, 619, 628, 637, 645, 666, 1543, 1551, 1554, 1671, 1676, 1790, 1917, 1946, 2021, 2106, 2139, 2176, 2525, 2527, 2542, 2544, 2726, 2737, 2832, 2897, 3056
 - \adddot 551, 3131– 3133, 3136, 3137, 3140–3150, 3155, 3158, 3178–3184, 3186–3188, 3204, 3205, 3208–3211, 3213, 3215, 3217– 3220, 3222, 3223, 3228, 3230, 3232, 3234
 - \adddotspace 1528, 1538, 3131, 3133, 3136, 3157, 3158, 3182, 3225, 3226, 3229, 3230, 3235
 - \addperiod 148, 540, 546, 557
 - \addsemicolon . . . 350, 379, 678, 679, 719, 770, 810, 859, 924, 987, 1052, 1102, 1140, 1180, 1221, 1253, 1304, 1348, 1388, 1422,
 - 1484, 1509, 1616, 2222, 2272, 2316, 2358, 2410, 2462, 2511
 - \addspace . 149, 181, 182, 272, 277, 285, 297, 367, 440, 444, 447, 455, 460, 465, 487, 499, 591, 600, 609, 618, 627, 636, 642, 664, 676, 1201, 1205, 1325, 1539, 1547, 1549, 1673, 1687, 1701, 1727, 1756, 1759, 1786, 1789, 1794, 1797, 1813, 1817, 1820, 1830, 1843, 1877, 1913, 1922, 1955, 1968, 2017, 2020, 2025, 2028, 2043, 2047, 2050, 2104, 2124, 2137, 2152, 2173, 2528, 2540, 2545, 2655, 2680, 2750, 2761, 2771, 2826, 3057
 - \AND 2724, 2735, 2830
 - \andmoredelim 2954
 - \andothersdelim 2943
 - \annotationfont . 166, 192
 - \AtBeginBibliography 92, 1868
 - \AtBeginDocument 84, 1732
 - \AtBeginShorthands 1669, 1876, 2077
 - \AtEveryBibitem 1741
 - \AtEveryCite 2563, 2931
- B**
- \bbx@crossref@inbook 883, 886, 1678, 1822, 1947, 2079, 2519
 - \bbx@crossref@incollection 948, 951, 1011, 1014, 1692, 1835, 1960, 2086, 2534
- \bbx@editionformat 39, 53, 169, 171, 238, 240, 242, 244, 246, 2065, 2067, 2069, 2071, 2073, 2174, 2177, 2192, 2242, 2288, 2330, 2381, 2432, 2481
- \bbx@lasthash 1795, 1818, 1920, 1940, 2026, 2048, 2109, 2128, 2141, 2155
- \bbx@origfields 51, 58, 315, 386, 396, 1564
- \bbx@publocformat 35, 43, 261, 263, 513, 515, 517, 521, 523, 525, 529, 531, 533
- \bbx@relatedformat 37, 47, 49, 254, 256, 258, 346, 348, 373, 376, 719, 769, 809, 858, 923, 986, 1051, 1101, 1139, 1179, 1220, 1252, 1303, 1347, 1387, 1421, 1483, 1508, 1615, 2221, 2271, 2315, 2357, 2409, 2461, 2510
- \bbx@volnumformat 36, 45, 216, 230, 472, 474, 476, 1754
- \bbx@volumeformat 40, 55, 206, 208, 210, 212, 220, 222, 224, 226
- \bibclosebracket 1735
- \bibcloseparen 1735, 2669, 2687, 2691, 2793, 2803, 2807
- \bibtcpstring 1523
- \bibdatedash 3125, 3172, 3198
- \bibhang 1866, 1873, 1883, 1991
- \bibhyperlink . 3041, 3049
- \bibhyperref 2572, 2585
- \bibhypertarget 3097
- \bibitemsep 1864

\bibnamedash	1782, 1811, 2013, 2041, 2101, 2122	
\bibnamesep	1865	
\bibopenbracket	1734	
\bibopenparen	1734, 2655, 2680, 2750, 2761, 2771	
\bibpagespunct	262, 264, 266	
\bibrangedash		
 3123, 3170, 3196	
\bibsstring	1521	
\bibstring	181, 182, 204, 217, 231, 234, 235, 239, 241, 243, 245, 316–318, 549, 550, 675, 686, 687, 1716, 1772, 1890, 1983, 2003, 2066, 2068, 2070, 2072, 2529, 2546, 2943, 2954, 3037, 3042, 3050, 3058, 3088, 3089, 3140, 3141, 3213, 3215	
\blx@blxinit	153	
\blx@postpunct	155	
\blx@setsfcodes	154	
\boolfalse 2618, 2669, 2687, 2691, 2696, 2793, 2803, 2807, 2860, 2861, 2869, 2870, 2878, 2879, 2892, 2893	
\booltrue	2654, 2679, 2749, 2760, 2770	
C		
\cbx@lasthash	2619, 2622, 2625, 2629, 2635, 2648, 2656, 2697, 2701, 2705, 2722, 2790, 2829, 2840	
\cbx@lastyear	2698, 2702, 2706, 2724, 2730, 2735, 2741, 2744, 2779, 2786, 2788, 2830, 2836, 2842	
\ccite	3105	
\cite	2843	
\citetitle	2859, 2868	
\citeyear	2877	
\ClassError	198, 247	
\clearfield	1708, 1709, 1764, 1765, 1881,	
	1882, 1898, 1975, 1976, 1995, 1996, 2056	
\clearname	1816, 1945, 2046, 2127, 2154	
\compitedelim 2630, 2649, 2728, 2731, 2739, 2834	
\csuse	3041, 3049	
D		
\DeclareBibliographyDriver 681, 728, 779, 819, 868, 933, 996, 1061, 1111, 1149, 1189, 1230, 1262, 1313, 1357, 1397, 1431, 1570, 2179, 2231, 2368	
\DeclareBibliographyExtras 3122, 3169, 3195	
\DeclareBibliographyOption 16, 18, 20, 22, 24, 26, 28, 31, 42, 44, 46, 48, 50, 52, 54, 1655, 1657, 1856, 2555, 2917, 2919, 2921	
\DeclareBibliographyStrings 3129, 3176, 3202	
\DeclareCiteCommand 658, 1678, 1692, 1822, 1835, 1947, 1960, 2079, 2086, 2519, 2534, 2843, 2851, 2859, 2868, 2877, 2885, 2891, 2903, 3105, 3111	
\DeclareDataInheritance 1643	
\DeclareEntryOption	57	
\DeclareFieldAlias 1645–1647	
\DeclareFieldFormat 180–195, 203, 215, 229, 232, 236, 253, 1517, 1518, 1520–1522, 1524, 1526, 1528, 2063	
\DeclareLanguageMapping 3–5	
\DeclareNameAlias	661, 1530, 2530, 2547, 2907, 3066, 3067, 3078, 3079, 3115, 3116	
\DeclarerNameFormat 94, 110, 2571, 2583, 2957, 2973, 3007, 3017	
\DeclareStyleSourcemap 1624	
E		
\edfnt	175	
\editionfont	168, 177	
\emph	1527, 2933	
\ExecuteBibliographyOptions 60, 1519, 1660, 1858, 2558, 2924	
F		
\finalandcomma	2941, 2952	
\finentry	556, 558, 559	
\footcitet	2885	
\footnotesize	166	
\fullcite	2903, 3111	
G		
\global	1795, 1818, 1920, 1940, 2026, 2048, 2109, 2128, 2141, 2155, 2618, 2619, 2622, 2625, 2654, 2669, 2679, 2687, 2691, 2696–2698, 2701, 2702, 2705, 2706, 2744, 2749, 2760, 2770, 2788, 2793, 2803, 2807, 3043, 3062, 3074, 3095, 3096	
H		
\hskip	1873, 1892	
\hyphenpenalty 3124, 3171, 3197	
I		
\ifbibindex	160	
\ifbibstring	235	
\ifblank	103	
\ifbool	2668, 2686, 2690, 2792, 2802, 2806	
\ifboolexe	128	
\ifboolexpr	336, 493, 1531, 1710, 1748, 1766, 1776, 1805, 1884, 1903, 1930, 1977, 1997,	

2007, 2035, 2095,
 2116, 2130, 2146,
 2158, 2164, 2935, 2946
`\ifciteindex` 158
`\ifcitereseen` 2521,
 2536, 2663, 2713,
 2733, 2756, 2781, 3098
`\ifdefstring` 169,
 171, 206, 208, 210,
 212, 216, 220, 222,
 224, 226, 230, 238,
 240, 242, 244, 246,
 254, 256, 258, 261,
 263, 315, 346, 348,
 373, 376, 386, 396,
 472, 474, 476, 513,
 515, 517, 521, 523,
 525, 529, 531, 533,
 719, 769, 809, 858,
 923, 986, 1051, 1101,
 1139, 1179, 1220,
 1252, 1303, 1347,
 1387, 1421, 1483,
 1508, 1564, 1615,
 1754, 2065, 2067,
 2069, 2071, 2073,
 2174, 2177, 2192,
 2221, 2242, 2271,
 2288, 2315, 2330,
 2357, 2381, 2409,
 2432, 2461, 2481, 2510
`\ifdefvoid` 129, 131
`\ifentrytype` 677
`\iffieldequals`
 . 2629, 2648, 2722,
 2724, 2735, 2829, 2830
`\iffieldequalstr` 1527,
 1537, 1546, 1742, 2613
`\iffieldequal` 307
`\iffieldundef` 306,
 310, 314, 321, 324,
 329, 337, 339, 341,
 343, 354, 357, 361,
 415, 417, 421, 430,
 441, 456, 484, 494,
 496, 538, 555, 674,
 685, 751, 832, 881,
 882, 907, 946, 947,
 970, 1009, 1010,
 1035, 1275, 1445,
 1459, 1494, 1525,
 1541, 1552, 1582,
 1593, 1680, 1694,
 1711, 1713, 1724, 1749,
 1751, 1767, 1769, 1785,
 1788, 1791, 1885, 1887,
 1896, 1897, 1912, 1915,
 1943, 1978, 1980,
 1998, 2000, 2016,
 2019, 2022, 2053,
 2054, 2081, 2088,
 2103, 2136, 2203,
 2245, 2299, 2341,
 2443, 2484, 2620,
 2628, 2642, 2660,
 2699, 2709, 2723,
 2725, 2736, 2746,
 2775, 2776, 2783,
 2824, 2831, 2841, 3099
`\iffirstinits` 100, 106, 3013
`\iffootnote`
 2958, 2974, 3008, 3018
`\ifgiveninits` 117, 134, 3024
`\ifinteger` 205,
 219, 233, 237, 1523, 2064
`\iflistundef`
 270, 282, 284, 294,
 296, 372, 544, 562,
 571, 580, 590, 599,
 608, 617, 626, 635, 1203
`\ifloccit` 3046
`\ifmoreitems` 2949
`\ifmorenames` 2938
`\ifnamesequal` 1440
`\ifnameundef` 1534, 1779,
 1808, 1906, 1933,
 2010, 2038, 2098,
 2119, 2133, 2149,
 2161, 2167, 2631,
 2650, 2677, 2745, 2824
`\ifnumequal`
 99, 116, 2657, 2751,
 2762, 2772, 2936, 2947
`\ifnumgreater` 548, 2940, 2951
`\ifnumless` 2617, 2695
`\ifsingletitle` 3053
`\ifstrequal` 1851, 1990
`\ifthenelse` 1683,
 1697, 1826, 1839,
 1951, 1964, 2522,
 2537, 2683, 2724,
 2735, 2799, 2824, 2830
`\iftoggle` 85,
 88, 93, 537, 554,
 703, 710, 718, 760,
 768, 808, 849, 857,
 914, 922, 977, 985,
 1042, 1050, 1092,
 1100, 1138, 1170, 1178,
 1219, 1243, 1251, 1294,
 1302, 1338, 1346,
 1378, 1386, 1414,
 1420, 1474, 1482,
 1501, 1507, 1606,
 1614, 1715, 1733, 1771,
 1869, 1889, 1982,
 2002, 2212, 2220,
 2262, 2270, 2306,
 2314, 2348, 2356,
 2400, 2408, 2452,
 2460, 2501, 2509,
 2527, 2544, 2564,
 2662, 2711, 2732,
 2755, 2780, 2933,
 2956, 3056, 3065,
 3072, 3077, 3087,
 3114, 3142–3145,
 3147–3149, 3216,
 3218–3220, 3222, 3233
`\ifuseauthor`
 . . 1532, 1777, 1904,
 2008, 2096, 2131, 2159
`\ifuseditor` 1682, 1696,
 1806, 1825, 1838,
 1931, 1950, 1963,
 2036, 2117, 2147, 2165
`\ifuseprefix`
 2576, 2592, 2966, 2987
`\ignorespaces` 1873
`\indexfield` 2863, 2872, 2898
`\indexnames`
 . . 158, 160–164, 2895
`\InheritBibliographyExtras`
 3120, 3167, 3193
`\intitlepunct` 149
`\isdot` 252, 2075

L

`\labelnamepunct` . 656,
 692, 732, 783, 823,
 873, 938, 1001, 1065,
 1115, 1153, 1193, 1234,
 1266, 1317, 1361, 1401,
 1574, 1671, 1874,
 1878, 1992, 2183,
 2235, 2372, 2423, 2474

\libraryfont 167, 193

M

\MakeLowercase 86

\map 1626

\maps 1625

\midsentence . . 155, 425,
 434, 444, 460, 1716,
 1772, 1890, 1983,
 2003, 2528, 2545, 3057

\mkbibbrackets . . 257, 679

\mkbibemph
 . 180, 184, 185, 187, 188

\mkbibfootnote 2885

\mkbibnameaffix
 . 98, 114, 2568,
 2962, 2978, 3012, 3022

\mkbibnamefamily
 . 95, 111, 2565,
 2959, 2975, 3009, 3019

\mkbibnamegiven
 . 96, 112, 2566,
 2960, 2976, 3010, 3020

\mkbibnameprefix
 . 97, 113, 2567,
 2961, 2977, 3011, 3021

\mkbibbordedition . 239, 2066

\mkbibbordseries 234

\mkbibparens 2851

\mkbibquote 183, 186, 189

\mkbibsc 86, 87, 95–
 98, 111–114, 2565–
 2568, 2959–2962,
 2975–2978, 3009–
 3012, 3019–3022, 3088

\mkbibsupserscript . . 2074

\mkibid . 2933, 2943, 2954,
 3037, 3042, 3050, 3089

\mkpageprefix 190, 1525

\mkpureparens
 . 151, 194, 195,
 255, 678, 3138, 3139,
 3183, 3184, 3210, 3211

\multicitedelim . 2639,
 2645, 2671, 2693,
 2719, 2795, 2809,
 2865, 2874, 2882,
 2900, 2909, 3109, 3118

N

\namepartfamily
 . 119, 124, 136,

141, 2587, 2594, 2599,
 2605, 2982, 2989,
 2994, 3000, 3026, 3031

\namepartgiven
 125, 129, 142, 2588,
 2606, 2983, 3001, 3032

\namepartgiveni
 . 120, 137, 2595,
 2600, 2990, 2995, 3027

\namepartprefix 121, 126,
 131, 138, 143, 2589,
 2596, 2607, 2984,
 2991, 3002, 3028, 3033

\namepartprefixi 2601, 2996

\nameparts
 . 115, 2584, 2979, 3023

\namepartsuffix 122, 127,
 139, 144, 2590, 2608,
 2985, 3003, 3029, 3034

\namepartsuffixi
 2597, 2602, 2992, 2997

\nametitledelim 2634, 3090

\nameyeardelim 2838

\NewBibliographyString
 3127, 3174, 3200

\newbibmacro . 260, 269,
 281, 293, 305, 313,
 320, 327, 335, 353,
 365, 371, 392, 402,
 407, 414, 536, 561,
 570, 579, 588, 597,
 606, 615, 624, 633,
 641, 644, 647, 890,
 955, 1018, 1444, 1452,
 1493, 1529, 1558,
 1706, 1719, 1973,
 2129, 2143, 2145,
 2157, 2419, 2470,
 2616, 2624, 2627,
 2641, 2647, 2673,
 2676, 2694, 2704,
 2708, 2721, 2797,
 2823, 3036, 3039, 3092

\newblock 332, 384,
 387, 389, 394, 397,
 399, 692, 696, 698,
 700, 702, 705, 707,
 709, 713, 715, 717,
 724, 732, 736, 738,
 740, 744, 746, 748,
 755, 759, 763, 765,
 767, 775, 783, 787,

789, 791, 793, 795,
 797, 799, 803, 805,
 807, 815, 823, 827,
 829, 838, 840, 842,
 844, 848, 852, 854,
 856, 864, 873, 877,
 879, 884, 887, 892,
 894, 896, 900, 902,
 904, 911, 913, 917,
 919, 921, 929, 938,
 942, 944, 949, 952,
 957, 959, 963, 965,
 967, 974, 976, 980,
 982, 984, 992, 1001,
 1005, 1007, 1012,
 1015, 1020, 1022,
 1026, 1028, 1030,
 1039, 1041, 1045,
 1047, 1049, 1057,
 1065, 1069, 1071,
 1073, 1075, 1077,
 1083, 1087, 1091,
 1095, 1097, 1099,
 1107, 1115, 1119, 1121,
 1123, 1125, 1131, 1133,
 1135, 1137, 1145, 1153,
 1157, 1159, 1161, 1165,
 1167, 1169, 1173, 1175,
 1177, 1185, 1193, 1197,
 1199, 1208, 1210, 1212,
 1214, 1216, 1218, 1226,
 1234, 1238, 1240,
 1242, 1246, 1248,
 1250, 1258, 1266,
 1270, 1272, 1274,
 1281, 1283, 1285,
 1289, 1293, 1297,
 1299, 1301, 1309,
 1317, 1321, 1323, 1327,
 1331, 1333, 1337, 1341,
 1343, 1345, 1353,
 1361, 1365, 1367,
 1369, 1373, 1377,
 1381, 1383, 1385,
 1393, 1401, 1405,
 1407, 1409, 1411,
 1413, 1417, 1419, 1427,
 1454, 1456, 1465,
 1467, 1469, 1471,
 1473, 1477, 1479,
 1481, 1489, 1498,
 1500, 1504, 1506,

1514, 1560, 1562,
 1565, 1567, 1574,
 1576, 1579, 1581, 1585,
 1590, 1599, 1601,
 1603, 1605, 1609,
 1611, 1613, 1621, 2183,
 2187, 2189, 2191,
 2196, 2198, 2200,
 2207, 2211, 2215,
 2217, 2219, 2227,
 2235, 2239, 2241,
 2251, 2253, 2255,
 2257, 2261, 2265,
 2267, 2269, 2277,
 2283, 2285, 2287,
 2292, 2294, 2296,
 2303, 2305, 2309,
 2311, 2313, 2321,
 2327, 2329, 2334,
 2336, 2338, 2345,
 2347, 2351, 2353,
 2355, 2363, 2372,
 2376, 2378, 2380,
 2383, 2385, 2391,
 2395, 2399, 2403,
 2405, 2407, 2415,
 2423, 2427, 2429,
 2431, 2436, 2438,
 2440, 2447, 2451,
 2455, 2457, 2459,
 2467, 2474, 2478,
 2480, 2490, 2492,
 2494, 2496, 2500,
 2504, 2506, 2508, 2516
`\newcounter` 82, 83
`\newlength` 1860, 1861
`\newrobustcmd` 86, 87, 151, 175
`\newtoggle`
 6–12, 14, 1652, 1653,
 1855, 2553, 2913–2915
`\newunit` 279, 291,
 303, 332, 363, 384,
 387, 389, 394, 397,
 399, 443, 445, 451,
 458, 461, 469, 489,
 504, 510, 568, 577,
 586, 595, 604, 613,
 622, 631, 640, 694,
 696, 698, 700, 702,
 705, 707, 709, 713,
 715, 724, 734, 736,
 738, 740, 742, 744,
 746, 748, 750, 755,
 757, 759, 763, 765,
 775, 785, 787, 789,
 791, 793, 795, 797,
 799, 801, 803, 805,
 815, 825, 827, 829,
 831, 836, 838, 840,
 842, 844, 846, 848,
 852, 854, 864, 875,
 877, 879, 884, 887,
 892, 894, 896, 898,
 900, 902, 904, 906,
 911, 913, 917, 919,
 929, 940, 942, 944,
 949, 952, 957, 959,
 961, 963, 965, 967,
 969, 974, 976, 980,
 982, 992, 1003, 1005,
 1007, 1012, 1015,
 1020, 1022, 1024,
 1026, 1028, 1030,
 1032, 1034, 1039,
 1041, 1045, 1047,
 1057, 1067, 1069,
 1071, 1073, 1075,
 1077, 1079, 1081,
 1083, 1085, 1087,
 1089, 1091, 1095,
 1097, 1107, 1117, 1119,
 1121, 1123, 1125, 1127,
 1129, 1131, 1133, 1135,
 1145, 1155, 1157, 1159,
 1161, 1163, 1165, 1167,
 1169, 1173, 1175, 1185,
 1195, 1197, 1199, 1208,
 1210, 1212, 1214, 1216,
 1226, 1236, 1238,
 1240, 1242, 1246,
 1248, 1258, 1268,
 1270, 1272, 1274,
 1279, 1281, 1283,
 1285, 1287, 1289,
 1291, 1293, 1297,
 1299, 1309, 1319,
 1321, 1323, 1327, 1329,
 1331, 1333, 1335, 1337,
 1341, 1343, 1353, 1363,
 1365, 1367, 1369, 1371,
 1373, 1375, 1377, 1381,
 1383, 1393, 1403,
 1405, 1407, 1409,
 1411, 1413, 1417, 1427,
 1454, 1456, 1458,
 1463, 1465, 1467,
 1469, 1471, 1473,
 1477, 1479, 1489,
 1498, 1500, 1504,
 1514, 1560, 1562,
 1565, 1567, 1576,
 1579, 1581, 1585,
 1590, 1592, 1597,
 1599, 1601, 1603,
 1605, 1609, 1611, 1621,
 1729, 1761, 2185, 2187,
 2189, 2191, 2194,
 2196, 2198, 2200,
 2202, 2207, 2209,
 2211, 2215, 2217,
 2227, 2237, 2239,
 2241, 2244, 2249,
 2251, 2253, 2255,
 2257, 2259, 2261,
 2265, 2267, 2277,
 2283, 2285, 2287,
 2290, 2292, 2294,
 2296, 2298, 2303,
 2305, 2309, 2311,
 2321, 2327, 2329,
 2332, 2334, 2336,
 2338, 2340, 2345,
 2347, 2351, 2353,
 2363, 2374, 2376,
 2378, 2380, 2383,
 2385, 2387, 2389,
 2391, 2393, 2395,
 2397, 2399, 2403,
 2405, 2415, 2425,
 2427, 2429, 2431,
 2434, 2436, 2438,
 2440, 2442, 2447,
 2449, 2451, 2455,
 2457, 2467, 2476,
 2478, 2480, 2483,
 2488, 2490, 2492,
 2494, 2496, 2498,
 2500, 2504, 2506, 2516
`\newunitpunct` 147, 1878, 1992
`\nobreak` 557, 1872
`\noinherit` 1643
`\nopunct` 149, 317, 318, 347,
 349, 374, 377, 408, 551
O
`\optionerror`

- . 197, 213, 227, 259,
478, 518, 526, 534, 2075
\OR . . . 2725, 2736, 2824, 2831
- P**
- \PackageWarningNoLine 1432
\parencite 2851
\penalty . . . 3124, 3171, 3197
\postnamesep
. 1861, 1863, 1864, 1872
\postnotedelim 2681
\postsep 1872,
1877, 1901, 1919, 1938
\ppspace 549, 550
\printdate 643, 646, 664,
666, 1674, 1677, 1721,
1757, 1760, 2174, 2177
\printdateextra
. 1717, 1773, 1891, 2004
\printeventdate . 503, 1556
\printfield 263, 265, 267,
308, 311, 322, 325,
355, 359, 362, 383,
385, 393, 395, 403,
405, 410, 412, 416,
418, 424, 427, 433,
436, 444, 459, 464,
480, 486, 492, 501,
507, 509, 541, 558,
701, 711, 741, 743,
747, 752, 753, 758,
761, 792, 794, 796,
802, 830, 833, 834,
837, 841, 847, 850,
897, 899, 903, 908,
909, 915, 960, 962,
966, 971, 972, 978,
1025, 1029, 1036,
1037, 1043, 1074,
1078, 1080, 1082,
1090, 1093, 1124,
1126, 1128, 1130, 1162,
1164, 1200, 1202,
1211, 1241, 1244, 1276,
1277, 1280, 1284,
1292, 1295, 1324,
1326, 1328, 1330,
1336, 1339, 1368,
1370, 1376, 1379,
1408, 1410, 1447,
1448, 1450, 1457,
- 1460, 1461, 1464,
1468, 1475, 1495,
1496, 1502, 1553,
1559, 1561, 1563, 1587,
1588, 1591, 1594, 1595,
1598, 1600, 1607,
1726, 1756, 1759,
1787, 1898–1900,
1914, 1985, 1986,
2018, 2055, 2057,
2058, 2105, 2138,
2174, 2177, 2193,
2195, 2199, 2204,
2205, 2210, 2213,
2243, 2246, 2247,
2250, 2254, 2260,
2263, 2289, 2291,
2295, 2300, 2301,
2307, 2331, 2333,
2337, 2342, 2343,
2349, 2382, 2386,
2388, 2390, 2398,
2401, 2433, 2435,
2439, 2444, 2445,
2450, 2453, 2482,
2485, 2486, 2489,
2493, 2499, 2502,
2526, 2543, 2674,
2682, 2811, 2864,
2873, 2881, 2899, 3055
- \printlist . . . 271, 274,
276, 283, 288, 295,
300, 551, 564, 566,
573, 575, 582, 584,
589, 593, 598, 602,
607, 611, 616, 620,
625, 629, 634, 638,
695, 735, 786, 826,
876, 941, 1004, 1031,
1068, 1084, 1118,
1156, 1166, 1196, 1207,
1237, 1269, 1286,
1320, 1364, 1404,
1578, 2186, 2238,
2375, 2392, 2426, 2477
- \printnames 1442,
1540, 1684, 1685,
1698, 1699, 1784,
1812, 1827, 1828,
1840, 1841, 1911, 1937,
1952, 1953, 1965,
1966, 2015, 2042,
- 2102, 2123, 2135,
2151, 2523, 2524,
2538, 2539, 2633,
2652, 2768, 2837, 2896
- \printorigdate . . . 273,
278, 286, 290, 298, 302
- \printtext 315,
318, 347, 349, 351,
374, 377, 380, 409,
423, 432, 483, 500,
547, 558, 676, 1206,
1538, 1548, 1553,
1586, 1715, 1717, 1723,
1755, 1758, 1771, 1773,
1787, 1883, 1889,
1891, 1900, 1914,
1946, 1982, 1984,
2002, 2004, 2018,
2105, 2138, 2525,
2542, 2674, 2685,
2801, 2811, 2864,
2873, 2881, 2896,
2899, 3037, 3040,
3048, 3054, 3063, 3075
- \protect 1432
- \protected . 3123, 3125,
3170, 3172, 3196, 3198
- R**
- \relatedcite . 658, 680, 688
\renewbibmacro 157,
159, 382, 420, 429,
438, 453, 471, 482,
491, 506, 512, 520,
528, 543, 553, 648,
649, 651–655, 663,
665, 671, 682, 1439,
1672, 1675, 1721,
1722, 1745–1747,
1762, 1775, 1800,
1802, 1804, 1879,
1895, 1902, 1925,
1927, 1929, 1993,
2006, 2030, 2032,
2034, 2052, 2094,
2111, 2113, 2115, 2172,
2175, 2281, 2325,
2810, 2812, 2814,
2816, 2818, 2820,
2934, 2945, 3045,
3052, 3060, 3071, 3086
- \RequireBiber 1

\RequireBibliographyStyle 2, 1649, 1650, 1854, 2060, 2061
 \RequireCitationStyle 2551, 2902, 2911
 \RN 209, 223, 241, 1520, 1523, 2068
 \Rn 211, 213, 225, 227, 243, 245, 2070, 2072
 \romannumeral 178

S

\savefield 2635, 2656, 2730, 2741, 2779, 2786, 2790, 2836, 2840, 2842
 \sdcite 2891
 \setlength 1862–1866, 1870, 1991
 \settoggle 17, 19, 21, 23, 25, 27, 29, 32, 1656, 1658, 1857, 2556, 2918, 2920, 2922
 \setunit . . 262, 264, 266, 272, 275, 277, 285, 287, 289, 297, 299, 301, 309, 323, 350, 356, 360, 367, 379, 404, 411, 416, 426, 435, 440, 444, 447, 449, 455, 460, 463, 465, 467, 479, 487, 499, 502, 508, 540, 546, 557, 565, 574, 583, 591, 592, 600, 601, 609, 610, 618, 619, 627, 628, 636, 637, 642, 645, 664, 666, 687, 692, 719, 720, 732, 770, 771, 783, 810, 811, 823, 859, 860, 873, 924, 925, 938, 987, 988, 1001, 1052, 1053, 1065, 1102, 1103, 1115, 1140, 1141, 1153, 1180, 1181, 1193, 1201, 1205, 1221, 1222, 1234, 1253, 1254, 1266, 1304, 1305, 1317, 1325, 1348, 1349, 1361, 1388, 1389, 1401, 1422, 1423, 1449, 1484, 1485, 1509, 1510, 1539, 1543, 1547, 1549, 1551, 1554, 1574, 1616, 1617, 1673, 1676, 1687, 1701, 1727, 1756, 1759, 1786, 1789, 1790, 1794, 1797, 1813, 1817, 1820, 1830, 1843, 1913, 1917, 1922, 1955, 1968, 2017, 2020, 2021, 2025, 2028, 2043, 2047, 2050, 2104, 2106, 2124, 2137, 2139, 2152, 2173, 2176, 2183, 2222, 2223, 2235, 2272, 2273, 2316, 2317, 2358, 2359, 2372, 2410, 2411, 2423, 2462, 2463, 2474, 2511, 2512, 2525, 2527, 2528, 2540, 2542, 2544, 2545, 2630, 2634, 2639, 2645, 2649, 2653, 2667, 2678, 2681, 2684, 2689, 2719, 2726, 2728, 2731, 2737, 2739, 2748, 2759, 2769, 2791, 2800, 2805, 2826, 2832, 2834, 2838, 2897, 3056, 3057, 3090
 \step 1627–1639
 \subtitlepunct 148, 426, 435
 \switchclass 2612, 2813, 2815, 2817, 2819, 2821, 2847, 2855

T

\textendash 3125, 3172, 3198
 \textsc 86, 87, 211, 225, 243, 2070
 \thefield 667, 680, 688, 883, 886, 948, 951, 1011, 1014, 2908, 3041, 3049, 3068, 3080, 3088, 3089, 3117
 \togglefalse . . 672, 673, 683, 684, 869, 934, 997, 1670, 1743, 1852, 2078, 2932, 3095, 3096
 \togglettrue 89, 90, 3043, 3062, 3074

U

\undef 1795, 1818, 1920, 1940, 2026, 2048, 2109, 2128, 2141, 2155, 2619, 2622, 2625, 2697, 2698, 2701, 2702, 2705, 2706, 2744, 2788
 \unspace 678, 679, 720, 771, 811, 860, 925, 988, 1053, 1103, 1141, 1181, 1222, 1254, 1305, 1349, 1389, 1423, 1485, 1510, 1617, 2223, 2273, 2317, 2359, 2411, 2463, 2512
 \uppercase 170
 \url 191
 \usebibmacro 101, 102, 105, 107–109, 118, 123, 133, 135, 140, 145, 262, 264, 266, 328, 330, 331, 333, 347, 349, 351, 358, 366, 368, 369, 375, 378, 381, 388, 390, 398, 400, 439, 446, 448, 450, 454, 462, 466, 468, 473, 475, 477, 485, 488, 514, 516, 518, 522, 524, 526, 530, 532, 534, 567, 576, 585, 594, 603, 612, 621, 630, 639, 648, 650– 655, 662, 689–691, 693, 697, 699, 703, 704, 706, 708, 714, 716, 721, 722, 725, 726, 729–731, 733, 737, 739, 745, 749, 756, 764, 766, 772, 773, 776, 777, 780– 782, 784, 788, 790, 798, 800, 804, 806, 812, 813, 816, 817,

- 820–822, 824, 828,
 839, 843, 845, 853,
 855, 861, 862, 865,
 866, 870–872, 874,
 878, 880, 882, 885,
 888, 891, 893, 895,
 901, 905, 912, 918,
 920, 926, 927, 930,
 931, 935–937, 939,
 943, 945, 947, 950,
 953, 956, 958, 964,
 968, 975, 981, 983,
 989, 990, 993, 994,
 998–1000, 1002,
 1006, 1008, 1010,
 1013, 1016, 1019,
 1021, 1023, 1027,
 1033, 1040, 1046,
 1048, 1054, 1055,
 1058, 1059, 1062–
 1064, 1066, 1070,
 1072, 1076, 1086,
 1088, 1096, 1098,
 1104, 1105, 1108,
 1109, 1112–1114, 1116,
 1120, 1122, 1132, 1134,
 1136, 1142, 1143, 1146,
 1147, 1150–1152, 1154,
 1158, 1160, 1168, 1171,
 1174, 1176, 1182, 1183,
 1186, 1187, 1190–1192,
 1194, 1198, 1209, 1213,
 1215, 1217, 1223, 1224,
 1227, 1228, 1231–
 1233, 1235, 1239,
 1247, 1249, 1255,
 1256, 1259, 1260,
 1263–1265, 1267,
 1271, 1273, 1282,
 1288, 1290, 1298,
 1300, 1306, 1307,
 1310, 1311, 1314–1316,
 1318, 1322, 1332,
 1334, 1342, 1344,
 1350, 1351, 1354, 1355,
 1358–1360, 1362,
 1366, 1372, 1374,
 1382, 1384, 1390,
 1391, 1394, 1395,
 1398–1400, 1402,
 1406, 1412, 1415,
 1418, 1424, 1425,
 1428, 1429, 1453,
 1455, 1466, 1470,
 1472, 1478, 1480,
 1486, 1487, 1490,
 1491, 1499, 1505,
 1511, 1512, 1515, 1516,
 1544, 1566, 1568,
 1571–1573, 1575, 1577,
 1580, 1583, 1584,
 1589, 1602, 1604,
 1610, 1612, 1618, 1619,
 1622, 1623, 1681,
 1686, 1688, 1689,
 1695, 1700, 1702,
 1703, 1725, 1728,
 1781, 1783, 1793, 1796,
 1798, 1801, 1803,
 1810, 1814, 1815, 1819,
 1821, 1824, 1829, 1831,
 1837, 1842, 1844,
 1908, 1910, 1918,
 1921, 1923, 1926,
 1928, 1935, 1939,
 1941, 1942, 1944,
 1949, 1954, 1956,
 1962, 1967, 1969,
 2012, 2014, 2024,
 2027, 2029, 2031,
 2033, 2040, 2044,
 2045, 2049, 2051,
 2082, 2083, 2089,
 2090, 2100, 2107,
 2108, 2112, 2114,
 2121, 2125, 2126,
 2140, 2144, 2153,
 2163, 2169, 2170,
 2180–2182, 2184,
 2188, 2190, 2197,
 2201, 2208, 2216,
 2218, 2224, 2225,
 2228, 2229, 2232–
 2234, 2236, 2240,
 2252, 2256, 2258,
 2266, 2268, 2274,
 2275, 2278, 2279,
 2282, 2284, 2286,
 2293, 2297, 2304,
 2310, 2312, 2318,
 2319, 2322, 2323,
 2326, 2328, 2335,
 2339, 2346, 2352,
 2354, 2360, 2361,
- \usedriver 660,
 2906, 3064, 3076, 3113

V			
\value	99, 116, 548, 551, 1207, 1683– 1685, 1697–1699, 1737, 1738, 1826– 1828, 1839–1841, 1951–1953, 1964–	1966, 2522–2524, 2537–2539, 2573, 2585, 2617, 2657, 2683, 2695, 2725, 2736, 2751, 2762, 2772, 2799, 2831, 2936, 2940, 2947,	2951, 2963, 2980, 3097 \volnumpunct 150, 404, 411, 416
		Y	
		\yeartitle	
		. 1860, 1862, 1870, 1892	